





EU Type Examination Certificate CML 19ATEX1333X Issue 0

- 1 Equipment intended for use in Potentially Explosive Atmospheres Directive 2014/34/EU
- 2 Equipment XLFE-MIB, XLFE-MIA & XLFE-LIB Signalling Luminaires
- 3 Manufacturer Cortem S.p.A.
- 4 Address Via Aquileia 10,
34070 Villesse,
Gorizia,
Italy
- 5 The equipment is specified in the description of this certificate and the documents to which it refers.
- 6 CML B.V. , Chamber of Commerce No 6738671, Hoogoorddreef 15, Amsterdam, 1101 BA, The Netherlands, Notified Body Number 2776, in accordance with Article 17 of Directive 2014/34/EU of the European Parliament and of the Council, dated 26 February 2014, certifies that this equipment has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment intended for use in potentially explosive atmospheres given in Annex II to the Directive.
The examination and test results are recorded in the confidential reports listed in Section 12.
- 7 If an 'X' suffix appears after the certificate number, it indicates that the equipment is subject to conditions of safe use (affecting correct installation or safe use). These are specified in Section 14.
- 8 This EU Type Examination certificate relates only to the design and construction of the specified equipment or component. Further requirements of Directive 2014/34/EU Article 13 apply to the manufacture of the equipment or component and are separately certified.
- 9 Compliance with the Essential Health and Safety Requirements, with the exception of those listed in the confidential report, has been demonstrated through compliance with the following documents:
EN IEC 60079-0:2018 EN 60079-28:2015
EN 60079-1:2014 EN 60079-31:2014
EN 60079-7:2015

- 10 The equipment shall be marked with the following:

 II 2 G D

 II 2 G D

Ex db op is IIC T4 Gb

Ex db eb op is IIC T4 Gb

Ex tb op is IIIC T110°C Db

Ta=-40°C to +40°C or +60°C

See description for specific T-Class and temperature range



**CML 19ATEX1333X
Issue 0**

11 Description

The XLFE-MIB, XLFE-MIA & XLFE-LIB Signalling Luminaires are designed for signalling of obstacles in high-risk areas for the presence of highly corrosive elements, combustible powders, flammable vapours and flammable gasses.

The equipment is cylindrical, with the body constructed from aluminium alloy and a cylindrical glass, sealed with resin. All models are composed from two parts: a terminal enclosure with types of protection increased safety (Ex e) and dust protection by enclosure (Ex t) and; light engine enclosure with types of protection flameproof ("Ex d) and dust protection by enclosure (Ex t). The separate enclosures are assembled with screws and the electrical connections between the two compartments are made through a certified bushing.

Ratings

The equipment has the following ratings:

Model	Power	Voltage	Frequency
XLFE-LIB	6W	100~240VAC 9~32VDC	50/60 Hz
XLFE-MIA	60W	279.4~294.7 VDC	20 or 40 fpm
XLFE-MIB	30W	110~121.5 VDC	20 or 40 fpm

Temperature Class (EPL Gb) and Maximum Surface Temperature (EPL Db)

The equipment models have the following temperature class:

	Tamb			
	40°C	60°C	40°C	60°C
	T class	T class	Max T _{surface}	Max T _{surface}
XLFE-LIB	T6	T6	55°C	75°C
XLFE-MIB	T4	N/A	110°C	N/A
XLFE-MIB/1	T4	T4	110°C	130°C
XLFE-MIA	T6	T5	70°C	90°C

12 Certificate history and evaluation reports

Issue	Date	Associated report	Notes
Draft	22 Jan 2020	R12582A/00	Prime Issue

Note: Drawings that describe the equipment or component are listed in the Annex.



**CML 19ATEX1333X
Issue 0**

13 Conditions of manufacture

The following conditions are required of the manufacturing process for compliance with the certification.

- i. Where the product incorporates certified parts or safety critical components the manufacturer shall ensure that any changes to those parts or components do not affect the compliance of the certified product that is the subject of this certificate.
- ii. Each luminaire shall be subjected to the following routine overpressure test for at least 10 seconds, as required by EN 60079-1:2014 / IEC 60079-1:2014 Clause 16.1, at the following pressures:
 -) XLFE-MIB – 14.4 Bar
 -) XLFE-MIA – 16.3 Bar
 -) XLFE-LIB – 14.7 Bar
- iii. An electric strength test shall be carried out on each luminaire. The test shall be carried out at a value as indicated below and applied between the supply conductors and the metal body of the luminaire in accordance with EN 60079-7:2015 / IEC 60079-7:2015 Ed 5.0 clause 7.1.
 - i. XLFE-MIB – 1,500 V
 - ii. XLFE-MIA – 1,590 V
 - iii. XLFE-LIB – 1,500 V
- iv. The Cabur TPL4 terminals shall not be used with the XLFE-MIA model luminaire.

14 Specific Conditions of Use (Special Conditions)

The following conditions relate to safe installation and/or use of the equipment.

- i. Flameproof joints must not be repaired
- ii. Use screws with property class A2-70
- iii. The device must be installed in order to avoid high mechanical risk of impact.



Certificate Annex

Certificate Number CML 19ATEX1333X
Equipment XLFE-MIB, XLFE-MIA & XLFE-LIB Signalling Luminaires
Manufacturer Cortem S.p.A.

The following documents describe the equipment or component defined in this certificate:

Issue 0

Drawing No	Sheets	Rev	Approved date	Title
A3-6716	1 of 4	0	22/01/2020	Obstruction Light Fixtures XLFE-MIB Assembly and External Dimensions
A3-6716	2 of 4	0	22/01/2020	Obstruction Light Fixtures XLFE-MI.. Flameproof features and Gasket Details
A3-6716	3 of 4	0	22/01/2020	Obstruction Light Fixtures XLFE-MIB Ex-op is / Ex-eb details
A3-6716	4 of 4	0	22/01/2020	Obstruction Light Fixtures XLFE-MIB Earth Connection / Circuit Diagrams
A3-7290	1 of 2	0	22/01/2020	Obstruction Light Fixtures XLFE-LIB Assembly and External Dimensions
A3-7290	2 of 2	0	22/01/2020	Obstruction Light Fixtures XLFE-LI.. Flameproof features and Gasket Details
A3-7291	1 of 4	0	22/01/2020	Obstruction Light Fixtures XLFE-MIA Flameproof features and Gasket Details
A3-7291	2 of 4	0	22/01/2020	Obstruction Light Fixtures XLFE-MIA Flameproof features and Gasket Details
A3-7291	3 of 4	0	22/01/2020	Obstruction Light Fixtures XLFE-MIA Ex-eb Details
A3-7291	4 of 4	0	22/01/2020	Obstruction Light Fixtures XLFE-MIA Op is details / Electrical details
A4-7456	1 to 7	0	22/01/2020	Technical Note