



Signal and control equipment, sockets and plugs

2026

Explosion-protected electrical equipment




CORTÉM
GROUP

To be sure to be safe.

CSC, EFSCO, EFDC, EMHA

Command and control stations 'Ex d'

- Group IIC
- Zone 1, 2, 21, 22
- Aluminium alloy, stainless steel or cast iron enclosures
- Category 2GD or M2



CSC Series... Control and signalling station

The Ex d IIC stations and controllers are suitable for the control and signalling of devices installed both "onboard" the machine and remotely (e.g. on a field control column). They are easily installed using wall mount lugs and have threaded entries for connection by means of a cable gland or metal pipe.

Used specifically in offshore and onshore environments, the chemical, petrochemical and pharmaceutical industries, and all locations which require an explosion proof system.

The switches, circuit breakers and selectors which make up the CSC series are 16 A rotary type with a front control handle. Supplied with 1" Male to 3/4" Female reducer. They are recommended for controlling devices both on board machine and on wall mounted columns. The various available cable arrangements make devices in the CSC series versatile for any type of use.

Cortem Group labels its products with a non-removable adhesive label featuring a hologram and an alphanumerical univocal code, as a safety measure against the illegal sale of fakes so that all the products are guaranteed as original. Non-compliance with the International standards entails serious risks for the environment, especially for those working daily on the plants.



Sectors of application:



Petroleum
refineries



Chemical and
petrochemical
plants



Onshore
plants



Offshore
plants



Petroleum loading/
unloading
pontoons



Low
temperatures



Mining
operations



100%
produced by
Cortem

CERTIFICATION DATA

Classification:

Group II

Category 2GD/M2

Installation:

EN 60079-14

zone 1 - zone 2 (Gas)

zone 21 - zone 22 (Dust)

Marking:

CE 0722 Ex I M2 Ex db I Mb (stainless steel and cast iron ONLY)

CE 0722 Ex II 2 GD; Ex db IIC T...°C Gb; Ex tb IIIC T...°C Db

Certificate:

ATEX CESI 01 ATEX 092 X

IEC Ex CES 17.0001X

TR CU AVAILABLE

For all IEC Ex and TR CU certification data,
download the certificate from
www.cortemgroup.com

Standards:

CENELEC EN 60079-0: 2012, EN 60079-0/A11: 2013, EN 60079-1: 2014 EN60079-31
2014 and European Directive 2014/34/EU
IEC 60079-0: 2011, IEC 60079-1: 2014, IEC 60079-31: 2013
RoHS Directive 2002/95/EC.

Temperature class:

T6 (Ta +40°C)

T5 (Ta +55°C)

Ambient Temp.:

-20°C +55°C

Standard

-50°C +55°C

Only for group II. The Group II monitoring and signalling units, equipped with polycarbonate signalling lenses, are limited to -40°C

Degree of protection:

IP66



CROSS-SECTION VIEW



MECHANICAL FEATURES OF ENCLOSURES

Body and lid:	Low copper content aluminium alloy, complete with wall fastening lugs.
Gaskets:	Acid, hydrocarbon and high temperature resistant silicon positioned between the body and the cover
Instrument casing:	Borosilicate glass
Certification label:	Adhesive affixed to external surface
Screws:	Stainless steel
Earth screw:	Internal M5 on body and lid connected by a 2.5 mm ² wire
Coating:	Polyester RAL 7035 (Light grey)
Threaded entries:	One upper and one lower Ø 1" complete with Male 1"- Female 3/4" adapter
Resistenza alla corrosione :	The STANDARD of the aluminium alloy used by Cortem has passed the tests required by standards EN60068-2-30 (hot-humid cycles) and EN60068-2-11 (salt fog test)

MECHANICAL FEATURES OF CONTROL AND SIGNALLING DEVICES

Pushbutton:	Coloured nylon
Illuminated pushbutton:	Clear coloured polycarbonate
Control levers:	Coated aluminium alloy
Badge:	Anodised aluminium, white lettering on black background
Internal bushing and pin:	Stainless steel
Gaskets:	Acid and hydrocarbon resistant NBR
Coating:	Polyester RAL 7035 (Light grey), where applicable
Station assembly:	Screwed onto cover
Contacts assembly:	Snap action on an appropriate flange to ensure the quick connection of entire contacts block to the station
External body lens:	Impact and UV resistant polycarbonate lens, coloured or transparent

ELECTRICAL FEATURES


Contacts for pushbuttons:	Max. 10A 600 V
Switches:	16A, 690 V
Indicator lights:	24/250V, 3W
Analogue instruments:	600V

ACCESSORIES UPON REQUEST / SPECIAL REQUESTS

RAL 2004 (Pure orange) internal anti-condensation coating
External polyester coatings in various colours (specify RAL colour)
Stainless steel or cast iron version available with minimum production batches. Contact your sales representative for more details. (sample code stainless steel CSC-DIN, cast iron sample code CSC-DGJ)
Cable gland / fittings
System protecting against accidental operation for mushroom-head push-buttons serie CSC-R (code **M-990**)

CSC Series... Control and signalling station

DIMENSIONAL DRAWING



SELECTOR ARRANGEMENT

Description	Badge	Single pole arrangement	Contacts	Single pole arrangement	Contacts	Codes																																								
Motors "start-stop" control, with spring return to 0 from both STOP and START.			<table border="1"> <tr><th>POS.</th><th>CONTACT</th><th>1-2</th><th>3-4</th></tr> <tr><td>STOP</td><td>O</td><td>O</td><td></td></tr> <tr><td>0</td><td>X</td><td>O</td><td></td></tr> <tr><td>START</td><td>X</td><td>X</td><td></td></tr> </table>	POS.	CONTACT	1-2	3-4	STOP	O	O		0	X	O		START	X	X			<table border="1"> <tr><th>POS.</th><th>CONTACT</th><th>1-2</th><th>3-4</th><th>5-6</th><th>7-8</th></tr> <tr><td>STOP</td><td>O</td><td>O</td><td>O</td><td>O</td><td>O</td></tr> <tr><td>0</td><td>X</td><td>O</td><td>X</td><td>O</td><td></td></tr> <tr><td>START</td><td>X</td><td>X</td><td>X</td><td>X</td><td>X</td></tr> </table>	POS.	CONTACT	1-2	3-4	5-6	7-8	STOP	O	O	O	O	O	0	X	O	X	O		START	X	X	X	X	X	X
POS.	CONTACT	1-2	3-4																																											
STOP	O	O																																												
0	X	O																																												
START	X	X																																												
POS.	CONTACT	1-2	3-4	5-6	7-8																																									
STOP	O	O	O	O	O																																									
0	X	O	X	O																																										
START	X	X	X	X	X																																									
Motors "start-stop" control with spring return from START to 0, and in fixed STOP position can be padlocked.			<table border="1"> <tr><th>POS.</th><th>CONTACT</th><th>1-2</th><th>3-4</th></tr> <tr><td>STOP</td><td>O</td><td>O</td><td></td></tr> <tr><td>0</td><td>X</td><td>O</td><td></td></tr> <tr><td>START</td><td>X</td><td>X</td><td></td></tr> </table>	POS.	CONTACT	1-2	3-4	STOP	O	O		0	X	O		START	X	X			<table border="1"> <tr><th>POS.</th><th>CONTACT</th><th>1-2</th><th>3-4</th><th>5-6</th><th>7-8</th></tr> <tr><td>STOP</td><td>O</td><td>O</td><td>O</td><td>O</td><td>O</td></tr> <tr><td>0</td><td>X</td><td>O</td><td>X</td><td>O</td><td></td></tr> <tr><td>START</td><td>X</td><td>X</td><td>X</td><td>X</td><td>X</td></tr> </table>	POS.	CONTACT	1-2	3-4	5-6	7-8	STOP	O	O	O	O	O	0	X	O	X	O		START	X	X	X	X	X	R
POS.	CONTACT	1-2	3-4																																											
STOP	O	O																																												
0	X	O																																												
START	X	X																																												
POS.	CONTACT	1-2	3-4	5-6	7-8																																									
STOP	O	O	O	O	O																																									
0	X	O	X	O																																										
START	X	X	X	X	X																																									
Switch with two fixed-positions, suitable for "automatic-manual" service			<table border="1"> <tr><th>POS.</th><th>CONTACT</th><th>1-2</th><th>3-4</th></tr> <tr><td>0</td><td>X</td><td>O</td><td></td></tr> <tr><td>1</td><td>O</td><td>X</td><td></td></tr> </table>	POS.	CONTACT	1-2	3-4	0	X	O		1	O	X			<table border="1"> <tr><th>POS.</th><th>CONTACT</th><th>1-2</th><th>3-4</th><th>5-6</th><th>7-8</th></tr> <tr><td>0</td><td>X</td><td>O</td><td>X</td><td>O</td><td></td></tr> <tr><td>1</td><td>O</td><td>X</td><td>O</td><td>X</td><td></td></tr> </table>	POS.	CONTACT	1-2	3-4	5-6	7-8	0	X	O	X	O		1	O	X	O	X		Z										
POS.	CONTACT	1-2	3-4																																											
0	X	O																																												
1	O	X																																												
POS.	CONTACT	1-2	3-4	5-6	7-8																																									
0	X	O	X	O																																										
1	O	X	O	X																																										
Switch			<table border="1"> <tr><th>POS.</th><th>CONTACT</th><th>1-2</th><th>3-4</th></tr> <tr><td>0</td><td>O</td><td>O</td><td></td></tr> <tr><td>1</td><td>X</td><td>X</td><td></td></tr> </table>	POS.	CONTACT	1-2	3-4	0	O	O		1	X	X			<table border="1"> <tr><th>POS.</th><th>CONTACT</th><th>1-2</th><th>3-4</th><th>5-6</th></tr> <tr><td>0</td><td>O</td><td>O</td><td>O</td><td>O</td></tr> <tr><td>1</td><td>X</td><td>X</td><td>X</td><td>X</td></tr> </table>	POS.	CONTACT	1-2	3-4	5-6	0	O	O	O	O	1	X	X	X	X	I													
POS.	CONTACT	1-2	3-4																																											
0	O	O																																												
1	X	X																																												
POS.	CONTACT	1-2	3-4	5-6																																										
0	O	O	O	O																																										
1	X	X	X	X																																										
Three fixed position switch can be padlocked in the centre position. Versions: single pole - double pole - triple pole			<table border="1"> <tr><th>POS.</th><th>CONTACT</th><th>1-2</th><th>3-4</th></tr> <tr><td>1</td><td>X</td><td>O</td><td></td></tr> <tr><td>0</td><td>O</td><td>O</td><td></td></tr> <tr><td>2</td><td>O</td><td>X</td><td></td></tr> </table>	POS.	CONTACT	1-2	3-4	1	X	O		0	O	O		2	O	X			<table border="1"> <tr><th>POS.</th><th>CONTACT</th><th>1-2</th><th>3-4</th><th>5-6</th><th>7-8</th></tr> <tr><td>1</td><td>X</td><td>O</td><td>X</td><td>O</td><td></td></tr> <tr><td>0</td><td>O</td><td>O</td><td>O</td><td>O</td><td></td></tr> <tr><td>2</td><td>O</td><td>X</td><td>O</td><td>X</td><td></td></tr> </table>	POS.	CONTACT	1-2	3-4	5-6	7-8	1	X	O	X	O		0	O	O	O	O		2	O	X	O	X		C
POS.	CONTACT	1-2	3-4																																											
1	X	O																																												
0	O	O																																												
2	O	X																																												
POS.	CONTACT	1-2	3-4	5-6	7-8																																									
1	X	O	X	O																																										
0	O	O	O	O																																										
2	O	X	O	X																																										
Three position switch can be padlocked in centre position with spring return to 0 from positions 1 and 2.			<table border="1"> <tr><th>POS.</th><th>CONTACT</th><th>1-2</th><th>3-4</th></tr> <tr><td>1</td><td>X</td><td>O</td><td></td></tr> <tr><td>0</td><td>O</td><td>O</td><td></td></tr> <tr><td>2</td><td>O</td><td>X</td><td></td></tr> </table>	POS.	CONTACT	1-2	3-4	1	X	O		0	O	O		2	O	X			<table border="1"> <tr><th>POS.</th><th>CONTACT</th><th>1-2</th><th>3-4</th><th>5-6</th><th>7-8</th></tr> <tr><td>1</td><td>X</td><td>O</td><td>X</td><td>O</td><td></td></tr> <tr><td>0</td><td>O</td><td>O</td><td>O</td><td>O</td><td></td></tr> <tr><td>2</td><td>O</td><td>X</td><td>O</td><td>X</td><td></td></tr> </table>	POS.	CONTACT	1-2	3-4	5-6	7-8	1	X	O	X	O		0	O	O	O	O		2	O	X	O	X		W
POS.	CONTACT	1-2	3-4																																											
1	X	O																																												
0	O	O																																												
2	O	X																																												
POS.	CONTACT	1-2	3-4	5-6	7-8																																									
1	X	O	X	O																																										
0	O	O	O	O																																										
2	O	X	O	X																																										
5 position reversing start switch. Lever with fixed C position and spring return to 0 from A and B			<table border="1"> <tr><th>POS.</th><th>CONTACT</th><th>1-2</th><th>3-4</th><th>5-6</th><th>7-8</th></tr> <tr><td>A</td><td>X</td><td>O</td><td>O</td><td>O</td><td>O</td></tr> <tr><td>0</td><td>O</td><td>X</td><td>O</td><td>O</td><td>O</td></tr> <tr><td>C</td><td>O</td><td>O</td><td>O</td><td>O</td><td>O</td></tr> <tr><td>0</td><td>O</td><td>O</td><td>X</td><td>O</td><td>O</td></tr> <tr><td>B</td><td>O</td><td>O</td><td>X</td><td>X</td><td>X</td></tr> </table>	POS.	CONTACT	1-2	3-4	5-6	7-8	A	X	O	O	O	O	0	O	X	O	O	O	C	O	O	O	O	O	0	O	O	X	O	O	B	O	O	X	X	X			Y				
POS.	CONTACT	1-2	3-4	5-6	7-8																																									
A	X	O	O	O	O																																									
0	O	X	O	O	O																																									
C	O	O	O	O	O																																									
0	O	O	X	O	O																																									
B	O	O	X	X	X																																									
"Start" motors control with lever spring return to position B			<table border="1"> <tr><th>POS.</th><th>CONTACT</th></tr> <tr><td>1</td><td></td></tr> <tr><td>A</td><td>X</td><td>O</td></tr> <tr><td>B</td><td>O</td><td>O</td></tr> </table>	POS.	CONTACT	1		A	X	O	B	O	O			M																														
POS.	CONTACT																																													
1																																														
A	X	O																																												
B	O	O																																												

CSC Series... Control and signalling station

CODE SELECTION TABLE

Illustration	Entry ØD	Description	Diagram	Weight Kg	Codes
	1" ISO 7/1 1" NPT	Single body: double pushbutton		0.85	CSC-D CSC-DN
	1" ISO 7/1 1" NPT	Single body: illuminated pushbutton		0.90	CSC-G CSC-GN
	1" ISO 7/1 1" NPT	Double body: double illuminated pushbutton		1.60	CSC-GG CSC-GGN
	1" ISO 7/1 1" NPT	Single body: single signal lamp		0.80	CSC-L CSC-LN
	1" ISO 7/1 1" NPT	Double body: double signal lamp		1.57	CSC-LL CSC-LLN
	1" ISO 7/1 1" NPT	Single body: single pushbutton (1NA+1NC)		0.74	CSC-P CSC-PN
	1" ISO 7/1 1" NPT	Single body: single pushbutton 2NO+2NC		0.88	CSC-2P CSC-2PN
	1" ISO 7/1 1" NPT	Double body: pushbutton + indicator light		1.63	CSC-PL CSC-PLN
	1" ISO 7/1 1" NPT	Double body: two pushbuttons		1.69	CSC-PP CSC-PPN
	1" ISO 7/1 1" NPT	Single body: single maintained pushbutton (maintained) (1NA+1NC)		0.90	CSC-B CSC-BN
	1" ISO 7/1 1" NPT	Single body: single maintained pushbutton (maintained) (2NA+2NC)		0.92	CSC-2B CSC-2BN

CSC Series... Control and signalling station

CODE SELECTION TABLE

Illustration	Entry ØD	Description	Diagram	Weight Kg	Codes
	1" ISO 7/1	Single body: mushroom head pushbutton (1NO+ 1NC)		0.92	CSC-F
	1" NPT				CSC-FN
	1" ISO 7/1	Single body: mushroom head pushbutton (2NO+ 2NC)			CSC-2F
	1" NPT				CSC-2FN
	1" ISO 7/1	Single body: 'twist to release' mushroom head pushbutton (1NO+ 1NC)		0.92	CSC-R
	1" NPT				CSC-RN
	1" ISO 7/1	Single body: 'twist to release' mushroom head pushbutton (2NA+2NC)			CSC-2R
	1" NPT				CSC-2RN
Selectors					
	1" ISO 7/1			0.87	CSC-1C
	1" NPT	Single body: single pole selector			CSC-1CN
	1" ISO 7/1			0.89	CSC-2C
	1" NPT	Single body: double pole selector			CSC-2CN
	1" ISO 7/1			0.91	CSC-3C
	1" NPT	Single body: triple pole selector			CSC-3CN
	1" ISO 7/1			0.87	CSC-1I
	1" NPT	Single body: single pole switch			CSC-1IN
	1" ISO 7/1			0.89	CSC-2I
	1" NPT	Single body: double pole switch			CSC-2IN
	1" ISO 7/1			0.91	CSC-3I
	1" NPT	Single body: triple pole switch			CSC-3IN
	1" ISO 7/1			0.89	CSC-1R
	1" NPT	Single body: run/stop selector			CSC-1RN
	1" ISO 7/1			0.89	CSC-1W
	1" NPT	Single body: single pole selector			CSC-1WN
	1" ISO 7/1			0.91	CSC-2W
	1" NPT	Single body: double pole selector			CSC-2WN
	1" ISO 7/1			0.89	CSC-1X
	1" NPT	Single body: run/stop selector			CSC-1XN
	1" ISO 7/1			0.89	CSC-1Y
	1" NPT	Single body: reversing start switch			CSC-1YN
	1" ISO 7/1			0.89	CSC-1Z
	1" NPT	Single body: single pole circuit breaker			CSC-1ZN
	1" ISO 7/1			0.89	CSC-2Z
	1" NPT	Single body: double pole circuit breaker			CSC-2ZN
	1" ISO 7/1			0.89	CSC-3Z
	1" NPT	Single body: triple pole circuit breaker			CSC-3ZN

CSC Series... Control and signalling station

CODE SELECTION TABLE

Illustration	Entry ØD	Combinations		Weight Kg	Codes
		Description			
	1" ISO 7/1	Double body:	single pole changeover switch + indicator light	1.65	CSC-1CL
	1" NPT	CSC-1CLN			
	1" ISO 7/1	Double body:	double pole changeover switch + indicator light	1.67	CSC-2CL
	1" NPT	CSC-2CLN			
	1" ISO 7/1	Double body:	triple pole changeover switch + indicator light	1.69	CSC-3CL
	1" NPT	CSC-3CLN			
	1" ISO 7/1	Double body:	pushbutton + single pole selector	1.70	CSC-P1C
	1" NPT	CSC-P1CN			
	1" ISO 7/1	Double body:	pushbutton + double pole selector	1.72	CSC-P2C
	1" NPT	CSC-P2CN			
	1" ISO 7/1	Double body:	pushbutton + triple pole selector	1.74	CSC-P3C
	1" NPT	CSC-P3CN			
	1" ISO 7/1	Double body:	single pole circuit breaker + indicator light	1.65	CSC-1ZL
	1" NPT	CSC-1ZLN			
	1" ISO 7/1	Double body:	double pole circuit breaker + indicator light	1.67	CSC-2ZL
	1" NPT	CSC-2ZLN			
	1" ISO 7/1	Double body:	triple pole circuit breaker + indicator light	1.65	CSC-3ZL
	1" NPT	CSC-3ZLN			
	1" ISO 7/1	Double body:	pushbutton + single pole circuit breaker	1.70	CSC-P1Z
	1" NPT	CSC-P1ZN			
	1" ISO 7/1	Double body:	pushbutton + double pole circuit breaker	1.72	CSC-P2Z
	1" NPT	CSC-P2ZN			
	1" ISO 7/1	Double body:	pushbutton + triple pole circuit breaker	1.74	CSC-P3Z
	1" NPT	CSC-P3ZN			
	1" ISO 7/1	Double body:	run/stop selector + single pole switch	1.74	CSC-1R1C
	1" NPT	CSC-1R1CN			
	1" ISO 7/1	Double body:	run/stop selector + double pole switch	1.76	CSC-1R2C
	1" NPT	CSC-1R2CN			
	1" ISO 7/1	Double body:	run/stop selector + triple pole switch	1.78	CSC-1R3C
	1" NPT	CSC-1R3CN			
	1" ISO 7/1	Double body:	run/stop selector + single pole circuit breaker	1.73	CSC-1R1Z
	1" NPT	CSC-1R1ZN			
	1" ISO 7/1	Double body:	run/stop selector + double pole circuit breaker	1.76	CSC-1R2Z
	1" NPT	CSC-1R2ZN			
	1" ISO 7/1	Double body:	run/stop selector + triple pole circuit breaker	1.78	CSC-1R3Z
	1" NPT	CSC-1R3ZN			

CSC Series... Control and signalling station

CODE SELECTION TABLE

Illustration	Entry ØD	Description	Weight Kg	Codes
	1" ISO 7/1	Double body: run/stop selector + single pole switch	1.73	CSC-1X1C
	1" NPT			CSC-1X1CN
	1" ISO 7/1	Double body: run/stop selector + double pole changeover switch	1.75	CSC-1X2C
	1" NPT			CSC-1X2CN
	1" ISO 7/1	Double body: run/stop selector + triple pole changeover switch	1.73	CSC-1X3C
	1" NPT			CSC-1X3CN
	1" ISO 7/1	Double body: run/stop selector + single pole circuit breaker	1.73	CSC-1X1Z
	1" NPT			CSC-1X1ZN
	1" ISO 7/1	Double body: run/stop selector + double pole circuit breaker	1.75	CSC-1X2Z
	1" NPT			CSC-1X2ZN
	1" ISO 7/1	Double body: run/stop selector + triple pole circuit breaker	1.77	CSC-1X3Z
	1" NPT			CSC-1X3ZN
	1" ISO 7/1	Double body: run/stop selector + indicator light	1.67	CSC-1RL
	1" NPT			CSC-1RLN
	1" ISO 7/1	Double body: run/stop selector + indicator light	1.66	CSC-1XL
	1" NPT			CSC-1XLN
	1" ISO 7/1	Single body: instrument casing	0.75	CSC-H
	1" NPT			CSC-HN
	1" ISO 7/1	Double body: instrument casing	1.50	CSC-HH
	1" NPT			CSC-HHN
	1" ISO 7/1	Double body: run/stop selector + instrument casing	1.67	CSC-1RH
	1" NPT			CSC-1RHN
	1" ISO 7/1			CSC-1XH
	1" NPT			CSC-1XHN
	1" ISO 7/1	Double body: run/stop selector + instrument casing	1.67	CSC-1ZK
	1" NPT			CSC-1ZKN
	1" ISO 7/1	Single body: Key operated handle with quick coupling for cam switch. Stainless steel bushing.	0.95	CSC-2ZK
	1" NPT			CSC-2ZKN
	1" ISO 7/1	Single body: break glass emergency pushbutton with hammer	1.10	CSCPEA2
	1" NPT			CSCPEA2N

Note:

For non-standard arrangements, contact the Sales Office.

EFDC Series... Control and signalling station



CROSS-SECTION VIEW



DESCRIPTION

EFDC series control and monitoring units are suitable for the control and signalling of devices, both on board the machine or remotely, and are used in the chemical, petrochemical and pharmaceutical industries, and any location which requires an explosion proof system. A feature of this station is the ability to mount up to four operators on the cover.

MECHANICAL FEATURES OF ENCLOSURES

Body and lid:

Low copper content aluminium alloy, complete with wall fastening lugs.

Gaskets:

Acid, hydrocarbon and high temperature resistant silicon positioned between the body and the cover

Certification label:

Adhesive affixed to external surface

Screws:

Stainless steel

Earth screw:

Internal M5 on body and lid connected by a 2.5 mm² wire

Coating:

Polyester RAL 7035 (Light grey)

Threaded entries:

One upper and one lower Ø 1"

Resistenza alla corrosione :

The STANDARD of the aluminium alloy used by Cortem has passed the tests required by standards EN60068-2-30 (hot-humid cycles) and EN60068-2-11 (salt fog test)

MECHANICAL FEATURES OF CONTROL AND SIGNALLING DEVICES

Pushbutton:

Coloured nylon

Illuminated pushbutton:

Clear coloured polycarbonate

Control lever:

Aluminium alloy

Badge:

Anodised aluminium, white lettering on black background

Outer body:

Aluminium alloy

Internal bushing and pin:

Stainless steel

Gaskets:

Acid and hydrocarbon resistant NBR

Station assembly:

Screwed onto cover

Contacts assembly:

Snap action on an appropriate flange to ensure the quick connection of entire contacts block to the station

External body lens:

Impact and UV resistant polycarbonate lens, coloured or transparent

ELECTRICAL FEATURES

Contacts for pushbuttons:

Max. 10A 600 V

Switches:

16A, 690 V

Indicator lights:

24/250V, 3W

ACCESSORIES UPON REQUEST / SPECIAL REQUESTS

RAL 2004 (Pure orange) internal anti-condensation coating


External polyester coatings in various colours (specify RAL colour)

Cablegland / fittings

System protecting against accidental operation for mushroom-head push-buttons serie EFDC-21EMR and EFDC-21EMC (code **M-990**)

EFDC Series... Control and signalling station

DIMENSIONAL DRAWING



CODE SELECTION TABLE

Illustration	Entry ØD	Description	Diagram	Weight Kg	Codes
	1" ISO 7/1 1" NPT	Single body: button	Y _R	1.4	EFDC-21 EFDC-21N
	1" ISO 7/1 1" NPT	Single body: indicator light	⊗ _R	1.4	EFDC-25 EFDC-25N
	1" ISO 7/1 1" NPT	Single body: two buttons	Y _N Y _R	1.5	EFDC-22 EFDC-22N
	1" ISO 7/1 1" NPT	Single body: two indicator lights	⊗ _R ⊗ _V	1.5	EFDC-24 EFDC-24N
	1" ISO 7/1 1" NPT	Single body: pushbutton with indicator light	⊗ _R Y _N	1.5	EFDC-23 EFDC-23N
	1" ISO 7/1 1" NPT	Single body: three buttons	Y _N Y _R Y _N	1.6	EFDC-27 EFDC-27N
	1" ISO 7/1 1" NPT	Single body: three indicator lights	⊗ _V ⊗ _R ⊗ _R	1.6	EFDC-20 EFDC-20N
	1" ISO 7/1 1" NPT	Single body: two pushbuttons and an indicator light	⊗ _N Y _R Y _R	1.6	EFDC-28 EFDC-28N
	1" ISO 7/1 1" NPT	Single body: pushbutton with two indicator lights	⊗ _V ⊗ _R Y _N	1.6	EFDC-29 EFDC-29N



EFDC Series... Control and signalling station

CODE SELECTION TABLE

Illustration	Entry ØD	Description	Diagram	Weight Kg	Codes
	1" ISO 7/1 1" NPT	Single body: four pushbuttons		1.8	EFDC-30 EFDC-30N
	1" ISO 7/1 1" NPT	Single body: four indicator lights		1.8	EFDC-31 EFDC-31N
	1" ISO 7/1 1" NPT	Single body: three pushbuttons with an indicator light		1.8	EFDC-32 EFDC-32N
	1" ISO 7/1 1" NPT	Single body: two pushbuttons with two indicator lights		1.8	EFDC-33 EFDC-33N
	1" ISO 7/1 1" NPT	Single body: pushbutton with three indicator lights		1.8	EFDC-34 EFDC-34N
	1" ISO 7/1 1" NPT	Single body: emergency pushbutton station with protective glass and hammer		1.4	EFDC-21EMV EFDC-21EMVN
	1" ISO 7/1 1" NPT	Single body: emergency pushbutton station		1.4	EFDC-21EM EFDC-21EMN
	1" ISO 7/1 1" NPT	Emergency pushbutton station with 'twist to release' mushroom head pushbutton		1.4	EFDC-21EMR EFDC-21EMRN
	1" ISO 7/1 1" NPT	Emergency pushbutton station with key release mushroom head pushbutton (when the button is pressed, turn the key to release)		1.4	EFDC-21EMC EFDC-21EMCN

EFDC Series... Control and signalling station

CODE SELECTION TABLE

Illustration	Entry ØD	Description	Diagram	Weight Kg	Codes
	1" ISO 7/1 1" NPT	Emergency pushbutton station with 'twist to release' mushroom head pushbutton and pushbutton		1.5	EFDC-21EMRV1
					EFDC-21EMRV1N
	1" ISO 7/1 1" NPT	Emergency pushbutton station with 'twist to release' mushroom head pushbutton, pushbutton and indicator light		1.5	EFDC-21EMRV2
					EFDC-21EMRV2N
	1" ISO 7/1 1" NPT	Single body: emergency pushbutton station with mushroom head pushbutton and key reset		1.4	EFDC-21EMCV1
					EFDC-21EMCV1N
	1" ISO 7/1 1" NPT	Single body: emergency pushbutton station with mushroom head pushbutton and key reset, pushbutton and indicator light		1.4	EFDC-21EMCV2
					EFDC-21EMCV2N
	1" ISO 7/1 1" NPT	Single body: Single pole selector		2.0	EFDC-1C
					EFDC-1CN
	1" ISO 7/1 1" NPT	Single body: Double pole selector		2.1	EFDC-2C
					EFDC-2CN

Note:


For non-standard arrangements, contact the Sales Office.

EFDC Series... Control and signalling station (Double body)

DESCRIPTION

EFDC series control and signalling stations -.../... are double bodied enclosures and can contain up to eight devices. They are used for the remote control of devices such as distribution panels for lights, pumps, starter motors, etc.

DIMENSIONAL DRAWING



CODE SELECTION TABLE

Use the code in the selection table of EFDC single body stations to compose the code for double body stations.


Example:

EFDC-20/22

Double body station with three indicator lights in the left-hand enclosure and two pushbuttons in the one to the right. Two 1" ISO7/1 fittings.

EFDC-23/21N

Double body station with pushbutton and indicator light in the left-hand enclosure and a pushbutton in the one to the right. Two 1" NPT fittings.



EFDC33/2C connected to an instrument casing CSC-H with ammeter.





EXPLODED VIEW



DESCRIPTION

The switches, circuit breakers and selectors which make up the CSC series are 16 A rotary type with a front control handle. Supplied with 1" Male to 3/4" Female reducer

MECHANICAL FEATURES

Body and lid:	Low copper content aluminium alloy, complete with wall fastening lugs.
Gaskets:	Acid, hydrocarbon and high temperature resistant silicon positioned between the body and the cover
Control lever:	Coated aluminium alloy
Certification label:	Adhesive affixed to external surface
Badge:	Anodised aluminium, white lettering on black background
Internal bushing and pin:	Stainless steel
Control lever:	Aluminium alloy
Screws:	Stainless steel
Earth screw:	Internal M5 on body and lid connected by a 2.5 mm ² wire
Coating:	Polyester RAL 7035 (Light grey)
Threaded entries:	One upper and one lower Ø 1" complete with Male 1"- Female 3/4" adapter
Resistenza alla corrosione :	The STANDARD of the aluminium alloy used by Cortem has passed the tests required by standards EN60068-2-30 (hot-humid cycles) and EN60068-2-11 (salt fog test)

ELECTRICAL FEATURES


Switches:	16A, 690 V
------------------	------------

ACCESSORIES UPON REQUEST / SPECIAL REQUESTS

RAL 2004 (Pure orange) internal anti-condensation coating
External polyester coatings in various colours (specify RAL colour)
Stainless steel or cast iron version available with minimum production batches. Contact your sales representative for more details. (sample code stainless steel CSC-216IN, cast iron sample code CSC-216GJ)
Cablegland / fittings

CSC Series... Switches, selectors and circuit breaker


DIMENSIONAL DRAWING




SELECTION TABLE

Illustration	Entry ØD (*)	Description	Badge	Arrangement	Capacity	Poles	Weight Kg	Code
	1" ISO 7/1	Switch with 2 fixed positions '0-1'			16 A	2	0.95	CSC-216
	1" NPT							CSC-216N
	1" ISO 7/1	Switch with 2 fixed positions '0-1'			16 A	3	0.86	CSC-316
	1" NPT							CSC-316N
	1" ISO 7/1	Switch with 2 fixed positions '0-1'			16 A	4	0.85	CSC-416
	1" NPT							CSC-416N
	1" ISO 7/1	Switch with 3 fixed positions '1-0-2'			16 A	2	0.89	CSCC-216
	1" NPT							CSCC-216N
	1" ISO 7/1	Switch with 3 fixed positions '1-2'			16 A	2	0.89	CSCD-216
	1" NPT							CSCD-216N
	1" ISO 7/1	Inverter with 3 fixed positions '1-0-2'			16 A	2	0.89	CSCI-216
	1" NPT							CSCI-216N

* Supplied with 1" Male to 3/4" Female reducer



EXPLODED VIEW



The switches, circuit breakers and selectors which make up the EFSCO series are 25, 32, 40 and 63 A rotary type with a front control handle.

MECHANICAL FEATURES

Body and lid:	Low copper content aluminium alloy, complete with wall fastening lugs.
Gaskets:	Acid, hydrocarbon and high temperature resistant silicon positioned between the body and the cover
Control lever:	Coated aluminium alloy
Certification label:	Adhesive affixed to external surface
Badge:	Anodised aluminium, white lettering on black background
Internal bushing and pin:	Stainless steel
Screws:	Stainless steel
Earth screw:	Internal M5 on body and lid connected by a 2.5 mm ² wire
Coating:	Polyester RAL 7035 (Light grey)
Resistenza alla corrosione :	The STANDARD of the aluminium alloy used by Cortem has passed the tests required by standards EN60068-2-30 (hot-humid cycles) and EN60068-2-11 (salt fog test)

ELECTRICAL FEATURES


Switches:	25 A to 63 A, 690 V
------------------	---------------------

ACCESSORIES UPON REQUEST / SPECIAL REQUESTS















RAL 2004 (Pure orange) internal anti-condensation coating
External polyester coatings in various colours (specify RAL colour)
Stainless steel version available with minimum production batches. Contact your sales representative for more details. (sample code stainless steel EFSCO-266IN)
Cablegland / fittings

EFSCO Series... Switches, selectors and circuit breaker

DIMENSIONAL DRAWING



CODE SELECTION TABLE

Illustration	Entry D ISO7/1	A	G	I	Description	Arrangement	Capacity	Poles	Weight Kg	Code
	1"	140	110	60			25 A	2	1.14	EFSCO-22
	1"	140	110	60			32 A	2	1.20	EFSCO-32
	1"	140	110	60	Switch with 2 fixed positions '0-1'		40 A	2	1.35	EFSCO-42
	1 1/2"	160	120	80			63 A	2	1.35	EFSCO-62
	1"	140	110	60			25 A	3	1.14	EFSCO-23
	1"	140	110	60			32 A	3	1.20	EFSCO-33
	1"	140	110	60	Switch with 2 fixed positions '0-1'		40 A	3	1.35	EFSCO-43
	1 1/2"	160	120	80			63 A	3	1.40	EFSCO-63
	1"	140	110	60			25 A	4	1.18	EFSCO-24
	1"	140	110	60			32 A	4	1.20	EFSCO-34
	1"	140	110	60	Switch with 2 fixed positions '0-1'		40 A	4	1.35	EFSCO-44
	1 1/2"	160	120	80			63 A	4	1.40	EFSCO-64
	1"	140	110	60			25 A	1	1.20	EFSCO-26
	1"	140	110	60			32 A	1	1.18	EFSCO-36
	1"	140	110	60			40 A	1	1.20	EFSCO-46
	1"	140	110	60	Circuit breaker with 2 fixed positions '1-2'		63 A	1	1.40	EFSCO-66
	1"	140	110	60			25 A	2	1.18	EFSCO-266
	1"	140	110	60			32 A	2	1.18	EFSCO-366
	1 1/2"	160	120	80			40 A	2	1.20	EFSCO-466
	1"	140	110	60			25 A	1	1.14	EFSCO-242
	1"	140	110	60			32 A	1	1.18	EFSCO-342
	1"	140	110	60			40 A	1	1.18	EFSCO-442
	1"	140	110	60			63 A	1	1.40	EFSCO-642
	1"	140	110	60			25 A	2	1.14	EFSCO-244
	1"	140	110	60			32 A	2	1.18	EFSCO-344
	1 1/2"	160	120	80			40 A	2	1.18	EFSCO-444

EMHA-9 and CSC-H Series... Instrument housings



CROSS-SECTION VIEW



DESCRIPTION

EMHA-9 instrument housings are normally used to contain medium-sized analogue instruments such as ammeters and voltmeters. CSC-H instrument housings are normally used to contain small-sized analogue instruments such as ammeters and voltmeters.

MECHANICAL FEATURES


Body and lid:	Low copper content aluminium alloy, complete with wall fastening lugs.
Gaskets:	Acid, hydrocarbon and high temperature resistant silicon positioned between the body and the cover
Glass	tempered and temperature resistant
Internal frame:	Aluminium
Certification label:	Adhesive affixed to external surface
Screws:	Stainless steel
Earth screw:	Internal M5 on body and lid connected by a 2.5 mm ² wire
Coating:	Polyester RAL 7035 (Light grey)
Threaded entries:	One upper and one lower Ø 3/4"
Resistenza alla corrosione :	The STANDARD of the aluminium alloy used by Cortem has passed the tests required by standards EN60068-2-30 (hot-humid cycles) and EN60068-2-11 (salt fog test)

ACCESSORIES UPON REQUEST / SPECIAL REQUESTS

Measuring instruments (Voltmeter - Ammeter)
RAL 2004 (Pure orange) internal anti-condensation coating
External polyester coatings in various colours (specify RAL colour)
Stainless steel or cast iron version available with minimum production batches. Contact your sales representative for more details. (sample code stainless steel EMHA-9IN, cast iron sample code EMHA-9GJ)
Cable gland / fittings

EMHA-9 and CSC-H Series... Instrument housings

DIMENSIONAL DRAWING



Dimensions in mm


CODE SELECTION TABLE

Illustration	Entry ØD	Description	Weight Kg	Codes
	3/4" ISO7/1	Instrument casing Ø85 mm	1.88	EMHA-9
	3/4" NPT			EMHA-9N
	1" ISO 7/1	Single body: instrument casing	0.75	CSC-H
	1" NPT			CSC-HN

CSE, EFD

Command and control stations

- Group IIB
- Zone 1, 2, 21, 22
- Aluminium alloy housings
- Category 2GD



CSE Series... Control and signalling station

The Ex d IIB stations and controllers are suitable for the control and signalling of devices installed both "on board" the machine and remotely (P.E on a field control column). They are easily installed using wall mount lugs and have threaded entries for connection by means of a cable gland or metal pipe.

Used specifically in offshore and onshore environments, the chemical, petrochemical and pharmaceutical industries, and all locations which require an explosion proof system.

Cortem Group labels its products with a non-removable adhesive label featuring a hologram and an alphanumeric univocal code, as a safety measure against the illegal sale of fakes so that all the products are guaranteed as original. Non-compliance with the International standards entails serious risks for the environment, especially for those working daily on the plants.



Sectors of application:



Petroleum refineries



Chemical and petrochemical plants



Onshore plants



Offshore plants



Petroleum loading/unloading pontoons



Low temperatures



Mining operations



100% produced by Cortem

CERTIFICATION DATA

Classification:

Group II

Category 2GD

Installation:

EN 60079-14

zone 1 - zone 2 (Gas)

zone 21 - zone 22 (Dust)

Marking:

CE 0722 Ex II 2 GD; Ex d IIB T6; Ex tD A21 T85°C

CE 0722 Ex II 2 GD; Ex d IIB T5; Ex tD A21 T100°C

Certificate:

ATEX

CESI 03 ATEX 172

Standards:

CENELEC EN 60079-0: 2012, EN 60079-1:2007, EN 60079-31: 2009 and EUROPEAN DIRECTIVE 2014/34/EU
RoHS Directive 2002/95/EC.

Temperature class:

T6 (Ta +40°C)

T5 (Ta +55°C)

Temp. Temperature:


-20 °C +55 °C

-20 °C +40 °C

Degree of protection:

IP66

EXPLODED VIEW



MECHANICAL FEATURES OF ENCLOSURES

Body and lid:**Gaskets:****Certification label:****Screws:****Earth screw:****Coating:****Threaded entries:****Resistenza alla corrosione :**

Low copper content aluminium alloy, complete with wall fastening lugs.

Acid, hydrocarbon and high temperature resistant silicon positioned between the body and the cover

Adhesive affixed to external surface

Stainless steel

Internal and external stainless steel

Polyester RAL 7035 (Light grey)

One upper and one lower Ø 3/4"

The STANDARD of the aluminium alloy used by Cortem has passed the tests required by standards EN60068-2-30 (hot-humid cycles) and EN60068-2-11 (salt fog test)

MECHANICAL FEATURES OF CONTROL AND SIGNALLING DEVICES

Pushbutton:

Coloured nylon

Illuminated pushbutton:

Clear coloured polycarbonate

Outer body:

Aluminium

Internal bushing and pin:

Stainless steel

Gaskets:

Acid and hydrocarbon resistant NBR

Station assembly:

Screwed onto cover

Contact assembly:

snap action on a dedicated flange to ensure the quick connection of entire contacts block to the station

External body lens:

Impact and UV resistant polycarbonate lens, coloured or transparent

ELECTRICAL FEATURES

Contacts for pushbuttons:

Max. 25A 600 V

Indicator lights:

24/250V, 3W

ACCESSORIES UPON REQUEST / SPECIAL REQUESTS


RAL 2004 (Pure orange) internal anti-condensation coating

External polyester coatings in various colours (specify RAL colour)

Cable gland / fittings

CSE Series... Control and signalling station

DIMENSIONAL DRAWING





CODE SELECTION TABLE

Illustration	Entry ØD	Description	Diagram	Weight Kg	Codes
	3/4" IS07/1 _____ 3/4" NPT	Unit with single indicator light	⊗ _R	1.01	CSE-L CSE-LN
	3/4" IS07/1 _____ 3/4" NPT	Unit with double indicator light	⊗ _R ⊗ _V	1.12	CSE-LL CSE-LLN
	3/4" IS07/1 _____ 3/4" NPT	Unit with three indicator light	⊗ _R ⊗ _V ⊗ _R	1.53	CSE-LLL CSE-LLLN
	3/4" IS07/1 _____ 3/4" NPT	Single pushbutton unit	⊗ _R	0.97	CSE-P CSE-PN
	3/4" IS07/1 _____ 3/4" NPT	Unit with double pushbutton	⊗ _R ⊗ _N ⊗ _R	1.05	CSE-PP CSE-PPN
	3/4" IS07/1 _____ 3/4" NPT	Three pushbutton unit	⊗ _R ⊗ _V ⊗ _R	1.42	CSE-PPP CSE-PPPN

CSE Series... Control and signalling station

SELECTION TABLE

Illustration	Entry ØD	Description	Diagram	Weight Kg	Codes
	3/4" IS07/1	Pushbutton unit and indicator light		1.09	CSE-PL
	3/4" NPT				CSE-PLN
	3/4" IS07/1	Pushbutton unit plus two indicator lights		1.50	CSE-PLL
	3/4" NPT				CSE-PLLN
	3/4" IS07/1	Unit with two pushbuttons plus indicator light		1.60	CSE-PPL
	3/4" NPT				CSE-PPLN
	3/4" IS07/1	Break glass emergency pushbutton		1.50	CSEPEA-2
	3/4" NPT				CSEPEA-2N
	3/4" IS07/1	Break glass emergency pushbutton with hammer		1.55	CSEPEA-2M
	3/4" NPT				CSEPEA-2MN
	3/4" IS07/1	Emergency mushroom head pushbutton		1.00	CSEPEP-2
	3/4" NPT				CSEPEP-2N


Note:

For non-standard arrangements, contact the Sales Office.

EFD3 Series... Breakers



DIMENSIONAL DRAWING



DESCRIPTION

EFD3 series three pole, magnetothermic breakers are used for control (start - stop) and protection of three-phase motors. Circuit breaker with adjustable magnetothermic protection and external control handle.

MECHANICAL FEATURES

Body and lid:	Rectangular casing constructed from low copper content aluminium alloy, complete with wall fastening lugs.
Gaskets:	Acid, hydrocarbon and high temperature resistant silicon positioned between the body and the cover
Control levers:	Coated aluminium alloy
ON - OFF plate:	Stainless steel
Certification label:	Adhesive affixed to external surface
Screws:	Stainless steel
Earth screw:	Internal M5 on body and lid connected to each other with a 2.5 mm ² wire
Coating:	Polyester RAL 7035 (Light grey)
Threaded entries:	One upper and one lower Ø 3/4"

Resistenza alla corrosione:

The STANDARD of the aluminium alloy used by Cortem has passed the tests required by standards EN60068-2-30 (hot-humid cycles) and EN60068-2-11 (salt fog test)

CODE SELECTION TABLE

Illustration	Rated current (A)	Temperature range (A)	Weight Kg	Codes
	0.25	0.16 0.25	2.25	EFD3-02
	0.40	0.25 0.40	2.25	EFD3-04
	0.60	0.40 0.60	2.52	EFD3-06
	1.00	0.60 1.00	2.52	EFD3-10
	1.60	1.00 1.60	2.52	EFD3-16
	2.50	1.60 2.50	2.52	EFD3-25
	4.00	2.50 4.00	2.52	EFD3-40
	6.00	4.00 6.00	2.52	EFD3-63
	10.00	6.00 10.00	2.52	EFD3-100
	16.00	10.00 16.00	2.52	EFD3-160
	20.00	16.00 20.00	2.52	EFD3-200
	25.00	20.00 25.00	2.52	EFD3-250



Ex d control, monitoring and control devices

M-0 series control, monitoring and control devices are installed as accessories outside of 'Ex d' enclosures, panels and stations used in all industrial environments where there may be an explosive atmosphere classified as Zone 1, 2, 21, 22. The M-0 devices allow the electrical or mechanical equipment assembled inside the 'Ex d' enclosures to be opened or closed, and signalling of the operating status light. Device components are constructed from stainless steel to ensure maximum efficiency and durability in most environmental conditions.



M-0 Series... Control, monitoring and signalling devices

Contact block for pushbuttons

ELECTRICAL FEATURES

Rated voltage:	600V
Rated current:	10A
Lightning impulse withstand voltage:	4 kV
Ambient temperature:	For operating temperature range, see the control station folders
Insulation class:	Group C conforming to VDE 0110
Degree of protection of terminals:	IP2x conforming to CENELEC EN 60529
Contact operation:	<ul style="list-style-type: none"> – slow action – self-cleaning (wiping action) – NC contact forced opening – double movable bridge – four points of contact – double break

Contact resistance
 $\leq 25 \text{ m}\Omega$ per IEC 255.7 category 3

Short-circuit protection
 16A gG time-delay fuses (on request)
 per IEC 269.1 and 269.3

Electrical performance

Rated thermal current $I_{th} = 10 \text{ A}$

Operational limits per IEC 947.5.1:


Category AC15							
EU voltage (V)	24	48	60	110	220	380	500
Current I_e (A)	10	10	10	6	3	2	1.5
Category DC13							
EU voltage (V)	24	48	60	110	220	300	
Current I_e (A)	2.5	1.5	1	0.22	0.27	0.2	

Operational limits per IEC 947.5.1:

AC Heavy Duty	A600
DC Standard Duty	Q300

MECHANICAL FEATURES

Outer body:	Aluminium
Internal bushing:	Stainless steel
Internal pin:	Stainless steel
Gaskets:	Acid and hydrocarbon resistant NBR
Pushbutton:	Coloured nylon
Illuminated pushbutton:	Clear coloured polycarbonate
Station assembly:	Screwed onto cover
Contact assembly:	snap action on a dedicated flange to ensure the quick connection of entire contacts block to the station



M-0 Series... Control, monitoring and signalling devices

Contacts block for control handles

ELECTRICAL FEATURES (Contacts block for control handles)

Alternating current

Series		10	16	20	32	40/63
Rated voltage	E_u VDE/IEC	V	690	690	690	690
Rated current	I_{th} VDE/IEC	A	20	25	32	45
	220V-240V	kW	2.2	4.5	5.5	7.5
	380V-440V	kW	4.0	7.5	9.0	11.0
AC3 VDE/IEC, Direct squirrel cage induction motor start up and stop during operation	660V-690V	kW	4.0	7.5	11.0	15.0
	110 V	kW	0.4	1.5	1.5	2.5
	220V-240V	kW	0.75	2.5	4.5	4.0
	400 V	kW	1.3	4.0	5.5	7.5

Internal switch

Rotating cam type, snap action cell made of explosion proof, thermoplastic material, steel shaft and tie rods, contacts covered with silver alloy and protected according to IP20 specification (rated insulation voltage = 690V), the terminal screws with matching cross head / screwdriver cannot be lost.

Conforms to the following standards: UL 508, CSA C22, IEC 947-1, IEC 947-3, DIN VDE0660 P.100/02.92, DIN VDE 0660 P.107/12.92, (CE-CSA-UL), European directive 2002/95/EG (ROHS), 2003/11/EG

MECHANICAL FEATURES


Internal bushing:	Stainless steel
Internal pin:	Stainless steel
Gaskets:	Acid and hydrocarbon resistant NBR
Control handle levers:	Coated aluminium alloy
Coating:	Polyester RAL 7035 (Light grey), where applicable



ILLUSTRATION



DIMENSIONS mm




DESCRIPTION

Normal pushbutton with standard 10A 600V 1NO+1NC contacts.
Button available in six different colours.

CODE

BLUE (B)	M-0429../B..
WHITE (W)	M-0429../W..
YELLOW (G)	M-0429../G..
BLACK (N)	M-0429../N..
RED (R)	M-0429../R..
GREEN (V)	M-0429../V..


Insert **IN** for a stainless steel body
L suffix for padlock option



Illuminated pushbutton with standard 10A 600V 1NO+1NC contacts.
(lamp on request)
Illuminated button available in five different colours.

BLUE (B)	M-0428../B
WHITE (W)	M-0428../W
YELLOW (G)	M-0428../G
RED (R)	M-0428../R
GREEN (V)	M-0428../V

Insert **IN** for a stainless steel body



Double pushbutton with standard 10A 600V contacts.
One red 1NO+1NC button and one black 1NO+1NC button.

Add suffix **L** for padlock option

M-0427..


M-0 Series... Control, monitoring and signalling devices

Ex e

ILLUSTRATION



DIMENSIONS mm




DESCRIPTION

Emergency mushroom head pushbutton with standard 10A 600V 1NO+1NC contacts. Comprises a red mushroom head push-button.

CODE

M-0430..


Add IN for a stainless steel body



Twist-to-release emergency stop push-button with standard 10A 600V 1NO+1NC contacts. Comprises a red button with twist mechanism for push-button release (turn to release when button is pressed)

M-0445..




Add IN for a stainless steel body



Pull-to-release emergency stop push-button with standard 10A 600V 1NO+1NC contacts. Comprises a red button with mechanism for push-button release (pull to release when button is pressed)

M-0447..

Add IN for a stainless steel body


ILLUSTRATION	DIMENSIONS mm	DESCRIPTION	CODE
		<p>Key-to-release emergency stop push-button with standard 10A 600V contacts. Comprises a red button with key mechanism for push-button release (use key to release when button is pressed)</p>	<p>M-0446.. Add IN for a stainless steel body</p>
		<p>Key-to-release push-button with OFF setting and standard 10A 600V contacts (use key to release when button is pressed)</p>	<p>M-093/CF</p>
		<p>Quick-connect handle for cam or rotary switch. Fixed pin length.</p>	<p>Add IN for a stainless steel body M-0553..L</p>


MECHANICAL FEATURES OF CONTROL AND SIGNALLING DEVICES

External body:	Impact and UV resistant, clear coloured polycarbonate
Bushing (for M-0487):	Aluminium
Gaskets:	Acid and hydrocarbon resistant NBR
Device assembly:	Screwed onto cover

ELECTRICAL FEATURES

Rated voltage:	12/240 VAC/DC
Power:	max. 3W (signalling light)
Frequency:	50/60 Hz

ILLUSTRATION	DIMENSIONS mm	DESCRIPTION	CODE
		Indicator lights with lamps (on request*) from 3W, 12/240 VAC/DC Illuminated lens available in five different colours.	
		Blue	M-0457/B
		Yellow	M-0457/G
		Red	M-0457/R
		Green	M-0457/V
		Colourless	M-0457/I
		* lamp	12V: LAMPBA9S12V
		24 V	LAMPBA9S24V
		110 V	LAMPBA9S110V
		240 V	LAMPBA9S240V



Command and control stations 'Ex e'

- Group IIC
- Zone 1, 2, 21, 22
- Three casing sizes in reinforced polyester
- Standard or custom models
- Speed of delivery
- Designed to customer specifications
- Category 2GD



Control and signalling station CMD

The CMD command and monitoring units, in fiberglass reinforced polyester, can be equipped with a complete series of switches and control, monitoring, and signalling devices. The innovative design has been studied to minimize the overall dimensions, while guaranteeing resistance, reliability, and simplicity of installation. They can be mounted both onboard machine and remotely for powering circuits such as light or motive power in any type of industrial application. The large number of components that can be installed allows a wide range of customizations to achieve the optimal solution for the operation of the system located in a hazardous area.

Cortem Group applies a tamper-evident holographic security label to its products, complete with a unique authentication numeric code, to combat the illegal sale of imitations and counterfeits, as well as guarantee the authenticity of its products. Failure to observe international standards creates serious risks for the environment and, above all, for the personnel who work with the systems on a daily basis.



Sectors of application:



Petroleum
refineries



Chemical and
petrochemical
facilities



Onshore
facilities



Offshore
facilities



Petroleum
loading/unloading
pontoons



Low
temperatures



Fuel storage
facilities



Agribusiness
facilities

CERTIFICATE DATA

Classification:

Group II

Category 2GD

Installation: EN 60079-14

zone 1 - zone 2 (Gas)

zone 21 - zone 22 (Dust)

Marking:

CE 0722 Ex II 2 GD; Ex db eb IIC T6, T5, T4 Gb; Ex tb IIIC T85°C, T100°C, T135°C Db

Certificate:

ATEX

[CML 21 ATEX 3848X](#)

IECEx

[IECEx CML 21.0104X](#)

For all IECEx certification data, download the certificate from [www.cortemgroup.com](#)

Standards:

CENELEC EN 60079-0: 2018, EN 60079-1: 2014, EN 60079-7: 2015, EN 60079-11: 2012, EN 60079-18: 2015, EN 60079-31: 2014 and European Directive 2014/34/EU. IEC 60079-0: 2018, IEC 60079-0: 2017, IEC 60079-7: 2015, IEC 60079-11: 2011, IEC 60079-18: 2014, IEC 60079-31: 2013 RoHS Directive 2002/95/EC.

Temperature class:

T85°C (T4)

Temp. Temperature:

-40°C +60°C

Degree of protection:

IP66

Control and signalling station CMD



MECHANICAL FEATURES

Body and lid:	Black antistatic fibreglass reinforced polyester complete with fixing lugs
Gaskets:	Acid, hydrocarbon and high temperature resistant silicon positioned between the body and the lid
Certificate label:	Adhesive
Screws:	Stainless steel
Earth screw:	Internal M5 on body
Cable gland:	Polyamide series NAVP

CONTACTS ELECTRICAL FEATURES



Code HL0101 (Contact)

Rated voltage/current:	220-250 Vac/10A, 380Vac/10A, 415Vac/10A 24Vdc/0.4A, 60Vdc/0.9A, 110Vdc/1.6A, 220Vdc/0.25A
Connection:	Max. 2.5 mm ²
Lightning impulse withstand voltage:	2 kV
Pollution degree:	3
Conditional short circuit current:	1 kA
Minimum force to achieve positive opening operation:	2 mm
Minimum force required to achieve positive opening of all opening contacts:	5 N
Maximum travel (+ overtravel):	5 mm (2 mm)



Code HL0102 (Indicator light)


Rated voltage:	12-36 Vac/dc, 48-127 Vac/dc, 220-415 Vac, 220-250 Vdc
Power input:	36V/0.6W, 127V/1.3W, 415V/3.8W, 250V/1.8W
Connection:	Max. 2.5 mm ²
Frequency:	50/60 Hz
Power consumption:	Max. 1 W
Lifespan:	10 ⁵ hours
Lightning impulse withstand voltage:	2 kV
Pollution degree:	3
Conditional short circuit current:	1 kA

ACCESSORIES UPON REQUEST / SPECIAL REQUESTS


Brass continuity plate for earthing
Breather or drainage valve
Metal cable glands

Control and signalling station CMD

DIMENSIONAL DRAWING



PLUS




Control and signalling station CMD

CONTROL STATION ORDER CODES

Art.

CMD-



CODING EXAMPLES

CMD-1TV2

"Type 1" control station with one \varnothing 20.5 hole on the bottom and one green pushbutton with 1NC contact.

CMD-3NR9V91R

"Type 3" control station with one \varnothing 25.5 hole on the bottom and one on the top, a red LED indicator light, a 12-36Vac/dc green indicator light and a "start-stop" control, with spring return from START to 0, and fixed STOP position.


Body holes



Through holes

Position	\varnothing 20.5	\varnothing 25.5
	T	Y
	B	N

Operator codes



OPERATOR + CONTACTS
Max. 3 operators

Note.

The control stations are supplied complete with NAVP series polyamide cable glands.







OPERATOR - PUSH-BUTTON -	DESCRIPTION OF OPERATOR AND RELATIVE CONTACTS	OPERATOR CODES
	Black push-button without contacts	N
	Red push-button without contacts	R
	Green push-button without contacts	V
	Yellow push-button without contacts	G
	White push-button without contacts	I
	Contact assembly 1NO	1
	Contact assembly 1NC	2
	Contact assembly 1NO+1NC	3
	Contact assembly 2NO	4
	Contact assembly 2NC	5

OPERATOR - INDICATOR LIGHT -	DESCRIPTION OF OPERATOR AND RELATIVE CONTACTS	OPERATOR CODES
	Component for green indicator light	V
	Component for red indicator light	R
	Component for yellow indicator light	G
	Component for blue indicator light	B
	Component for colourless indicator light	I
	12-36 Vac/dc LED indicator light	9
	48-127 Vac/dc LED indicator light	8
	220-415 Vac LED indicator light	7
	220-250 Vdc LED indicator light	6

Control and signalling station CMD



CONTROL STATION ORDER CODES

OPERATOR - ILLUMINATED PUSH-BUTTON -	DESCRIPTION OF OPERATOR AND RELATIVE CONTACTS	OPERATOR CODES
 	Blue push-button without contacts	BL
	Red push-button without contacts	RL
	Green push-button without contacts	VL
	Yellow push-button without contacts	GL
	Transparente push- button without contacts	IL
	Contact assembly 1NO	1
	Contact assembly 1NC	2
	Contact assembly 1NO+1NC	3
	Contact assembly 2NO	4
	Contact assembly 2NC	5

OPERATOR - SELECTOR -	SINGLE POLE ARRANGEMENT	CONTACTS	DESCRIPTION OF OPERATOR AND RELATIVE CONTACTS	OPERATOR + CONTACT CODES										
  	 <table border="1"> <tr> <th>POS.</th> <th>CONTACT</th> </tr> <tr> <td>1-2</td> <td>3-4</td> </tr> <tr> <td>STOP</td> <td>O O</td> </tr> <tr> <td>0</td> <td>X O</td> </tr> <tr> <td>START</td> <td>X X</td> </tr> </table>	POS.	CONTACT	1-2	3-4	STOP	O O	0	X O	START	X X		Motors "start-stop" control, with spring return to 0 from both STOP and START	1X
POS.	CONTACT													
1-2	3-4													
STOP	O O													
0	X O													
START	X X													
 <table border="1"> <tr> <th>POS.</th> <th>CONTACT</th> </tr> <tr> <td>1-2</td> <td>3-4</td> </tr> <tr> <td>STOP</td> <td>O O</td> </tr> <tr> <td>0</td> <td>X O</td> </tr> <tr> <td>START</td> <td>X X</td> </tr> </table>	POS.	CONTACT	1-2	3-4	STOP	O O	0	X O	START	X X		Motors "start-stop" control with spring return from START to 0, and in fixed STOP position	1R	
POS.	CONTACT													
1-2	3-4													
STOP	O O													
0	X O													
START	X X													
 <table border="1"> <tr> <th>POS.</th> <th>CONTACT</th> </tr> <tr> <td>1-2</td> <td>3-4</td> </tr> <tr> <td>0</td> <td>X O</td> </tr> <tr> <td>1</td> <td>O X</td> </tr> </table>	POS.	CONTACT	1-2	3-4	0	X O	1	O X		Switch with two fixed-positions, suitable for "automatic-manual" service	1Z			
POS.	CONTACT													
1-2	3-4													
0	X O													
1	O X													
 <table border="1"> <tr> <th>POS.</th> <th>CONTACT</th> </tr> <tr> <td>1-2</td> <td>3-4</td> </tr> <tr> <td>0</td> <td>O O</td> </tr> <tr> <td>1</td> <td>X X</td> </tr> </table>	POS.	CONTACT	1-2	3-4	0	O O	1	X X		Switch	2I			
POS.	CONTACT													
1-2	3-4													
0	O O													
1	X X													
 <table border="1"> <tr> <th>POS.</th> <th>CONTACT</th> </tr> <tr> <td>1-2</td> <td>3-4</td> </tr> <tr> <td>1</td> <td>X O</td> </tr> <tr> <td>0</td> <td>O O</td> </tr> <tr> <td>2</td> <td>O X</td> </tr> </table>	POS.	CONTACT	1-2	3-4	1	X O	0	O O	2	O X		Three fixed position switch.	1C	
POS.	CONTACT													
1-2	3-4													
1	X O													
0	O O													
2	O X													
 <table border="1"> <tr> <th>POS.</th> <th>CONTACT</th> </tr> <tr> <td>1-2</td> <td>3-4</td> </tr> <tr> <td>1</td> <td>X O</td> </tr> <tr> <td>0</td> <td>O O</td> </tr> <tr> <td>2</td> <td>O X</td> </tr> </table>	POS.	CONTACT	1-2	3-4	1	X O	0	O O	2	O X		Three position switch with spring return to 0 from positions 1 and 2	1W	
POS.	CONTACT													
1-2	3-4													
1	X O													
0	O O													
2	O X													

Control and signalling station CMD








CONTROL STATION ORDER CODES

OPERATOR - KEY SELECTOR -	SINGLE POLE ARRANGEMENT	CONTACTS	DESCRIPTION OF OPERATOR AND RELATIVE CONTACTS	OPERATOR CODES												
	 1Z	<table border="1"><tr><th>POS.</th><th>CONTACT</th><th>1-2</th><th>3-4</th></tr><tr><td>0</td><td>X</td><td>O</td><td></td></tr><tr><td>1</td><td>O</td><td>X</td><td></td></tr></table>	POS.	CONTACT	1-2	3-4	0	X	O		1	O	X		Switch with two fixed-positions, suitable for "automatic-manual" service	D3
POS.	CONTACT	1-2	3-4													
0	X	O														
1	O	X														
	 2I	<table border="1"><tr><th>POS.</th><th>CONTACT</th><th>1-2</th><th>3-4</th></tr><tr><td>0</td><td>O</td><td>O</td><td></td></tr><tr><td>1</td><td>X</td><td>X</td><td></td></tr></table>	POS.	CONTACT	1-2	3-4	0	O	O		1	X	X		Switch	D4
POS.	CONTACT	1-2	3-4													
0	O	O														
1	X	X														

OPERATOR - EMERGENCY PUSH-BUTTON -	DESCRIPTION OF OPERATOR AND RELATIVE CONTACTS	OPERATOR CODES
	Twist to release emergency stop push-button	F
	Key release emergency stop push-button	K
	Contact assembly 1NO	1
	Contact assembly 1NC	2
	Contact assembly 1NO+1NC	3
	Contact assembly 2NO	4
	Contact assembly 2NC	5

Control and signalling station CMD

TABLE OF STANDARD STOCK CONTROL STATIONS

Illustration	Description	Diagram	Codes
	Emergency mushroom head pushbutton with 1NO+1NC block (when pressed, rotate to release) Complete with NAVP20IXE cable gland (cable range 7-12 mm)		CMD-1TF3
	One black 1NO+1NC pushbutton Complete with NAVP20IXE cable gland (cable range 7-12 mm)		CMD-1TN3
	One red 220-415 VAC/DC indicator light		CMD-1TR7
	One colourless 220-415 VAC/DC indicator light		CMD-1TI7
	One green 220-415 VAC/DC indicator light		CMD-1TV7
	One blue 220-415 VAC/DC indicator light Complete with NAVP20IXE cable gland (cable range 7-12 mm)		CMD-1TB7
	One yellow 220-415 VAC/DC indicator light		CMD-1TG7
	Double pole switch Complete with two NAVP25IXE cable glands (cable range 14-18 mm)		CMD-1N2I
	Run/stop selector Complete with NAVP20IXE cable gland (cable range 7-12 mm)		CMD-1T1R
	Single pole switch Complete with NAVP20IXE cable gland (cable range 7-12 mm)		CMD-1T1Z
	One green 1NO+1NC pushbutton and one red 1NO+1NC pushbutton Complete with NAVP25IXE cable gland (cable range 14-18 mm)		CMD-2YV3R3
	Colourless 220-415 Vac/dc LED indicator light, one green 1NO+1NC pushbutton and one red 1NO+1NC pushbutton Complete with NAVP25IXE cable gland (cable range 14-18 mm)		CMD-3YV7V3R3

I, A

Command and control stations 'Ex e'

- Group IIC
- Zone 1, 2, 21, 22
- Aluminium, reinforced polyester or stainless steel enclosures
- Standard or custom products
- Speed of delivery, designed to customer specifications
- Category 2GD



Control stations I and A

The control and monitoring units of series P, I and A... are manufactured from fibreglass reinforced polyester, stainless steel or aluminium, and are suitable for housing electrical command and signal devices. **The units are preconfigured according to the following diagrams and can be ordered using their respective product code.** They can be installed both on board the machine or remotely, and are used in the chemical, petrochemical and pharmaceutical industries. In addition to the following listed standards, Cortem Group offers a wide range of accessories and versions manufactured to customer specification.

Cortem Group applies a tamper-evident holographic security label to its products, complete with a unique authentication numeric code, to combat the illegal sale of imitations and counterfeits, as well as guarantee the authenticity of its products. The failure to observe international standards involves serious hazards to the environment and, above all, personnel who work with the systems on a daily basis.



Sectors of application:



Petroleum refineries



Chemical and petrochemical plants



Onshore plants



Offshore plants



Petroleum loading/unloading pontoons



Low temperatures



Mining operations



100% produced by Cortem

CERTIFICATION DATA

Classification:

Group II

Category 2GD

Installation: EN 60079-14

zone 1 - zone 2 (Gas)

zone 21 - zone 22 (Dust)

Marking:

CE 0722 Ex II 2 GD; Ex de IIC T6, T5 Gb; Ex tb IIIC T85°C Db

Certificate:

ATEX

CESI 03 ATEX 115

IECEx

IECEx CES 11.0032

TR CU

AVAILABLE

For all IEC Ex and TR CU certification data, download the certificate from www.cortemgroup.com

Standards:

CENELEC EN 60079-0: 2012, EN 60079-1: 2007, EN 60079-7: 2007, EN 60079-31: 2009 and EUROPEAN DIRECTIVE 2014/34/UE RoHS Directive 2002/95/EC.

Temperature class:

T6 (Ta +40°C)

T5 (Ta +55°C)

Ambient Temp.:

-40°C +55°C

-40°C +40°C


IP66

Degree of protection:

Control station type I (stainless steel)



EXPLODED VIEW



MECHANICAL FEATURES

Body and cover:

Stainless steel complete with feet for fastening

Gaskets:

Acid, hydrocarbon and high temperature resistant silicon positioned between the body and the cover

Screws:

Stainless steel

Certificate plate:

Riveted stainless steel

Earth screw:Internal M5 on body and cover connected to each other with a 2.5 mm wire²**Cable gland:**

Nickel-plated brass

ACCESSORIES UPON REQUEST / SPECIAL REQUESTS

Safety measures and padlocks for stations

Safety measures against accidental contacts (padlockable)

Earthing rings for control units

Nameplates in various materials


Breather or drainage valve

Other contact types (see Ex e Control, monitoring and signalling stations folder)

Various possible configurations

Control station type I (stainless steel)

DIMENSIONAL DIAGRAM



CODE SELECTION TABLE

	Illustration	Description	Diagram	Codes
Indicator light		One red 24 VAC/DC indicator light		I1T01R9
		One green 24 VAC/DC indicator light		I1T01V9
		One blue 24 VAC/DC indicator light		I1T01B9
		One yellow 24 VAC/DC indicator light		I1T01G9
		One colourless 24 VAC/DC indicator light		I1T01I9
Button		One red 1NO+1NC pushbutton		I1T01R3
		One black 1NO+1NC pushbutton		I1T01N3
		One green 1NO+1NC pushbutton		I1T01V3
		One red 1NO pushbutton		I1T01R1
		One black 1NO pushbutton		I1T01N1
		One green 1NO pushbutton		I1T01V1
		One red 1NC pushbutton		I1T01R2
		One black 1NC pushbutton		I1T01N2
		One green 1NC pushbutton		I1T01V2
		One red 2NO pushbutton		I1T01R4
		One black 2NO pushbutton		I1T01N4
		One green 2NO pushbutton		I1T01V4
		One red 2NC pushbutton		I1T01R5
		One black 2NC pushbutton		I1T01N5
		One green 2NC pushbutton		I1T01V5













Control station type I (stainless steel)

CODE SELECTION TABLE

	Illustration	Description	Diagram	Codes
Selector				
		Switch with two fixed-positions, suitable for "automatic-manual" 1NO+1NC service		IIT011Z
		Motors "start-stop" control, with spring return to 0 from both STOP and START.		IIT011X
		Motors "start-stop" control with spring return from START to 0, and in fixed STOP position can be padlocked.		IIT011R
		Three fixed position switch can be padlocked in the centre position. Versions: single pole - double pole - triple pole.		IIT011C
Button		Emergency mushroom head pushbutton with 1NO+1NC block (when pressed, rotate to release)		IIT01F3
		Emergency mushroom head pushbutton with 1NC block (when pressed, rotate to release)		IIT01F2
Ammeter/voltmeter		Ammeter (scale on request)		IIT02A
		Voltmeter (scale on request)		IIT02V
Indicator light and pushbutton		24 VAC/DC red indicator light and one red 1NO+1NC pushbutton		I2T07R9R3
		24 VAC/DC green indicator light and one green 1NO+1NC pushbutton		I2T07V9V3
		24 VAC/DC red indicator light and one red 1NC pushbutton		I2T07R9R2
		24 VAC/DC green indicator light and one green 1NC pushbutton		I2T07V9V2
Indicator light and pushbutton		24 VAC/DC red indicator light and one red 1NO pushbutton		I2T07R9R1
		24 VAC/DC green indicator light and one green 1NO pushbutton		I2T07V9V1

Control station type I (stainless steel)

CODE SELECTION TABLE


Illustration	Description	Diagram	Codes
Indicator light and emergency pushbutton 	24 VAC/DC red indicator light and emergency 1NO+1NC mushroom pushbutton	 	I2T07R9F3
	24 VAC/DC green indicator light and 1NO+1NC emergency mushroom pushbutton	 	I2T07V9F3
Two pushbuttons and emergency pushbutton 	One green 1NO and one red 1NC pushbutton, one mushroom head 1NO pushbutton	  	I4T20V1R2F1
	One green 1NO and one red 1NC pushbutton, one mushroom head 1NC pushbutton	  	I4T20V1R2F2
Indicator light and two pushbuttons 	24 VAC/DC red LED indicator light, one green 1NO pushbutton and red 1NC pushbutton	  	I4T20R9V1R2
	24 VAC/DC green LED indicator light, one green 1NO pushbutton and red 1NC pushbutton	  	I4T20V9V1R2
	24 VAC/DC red LED indicator light, one green 1NO+1NC pushbutton and red 1NO+1NC pushbutton	  	I4T20R9V3R3
	24 VAC/DC green LED indicator light, one green 1NO+1NC pushbutton and red 1NO+1NC pushbutton	  	I4T20V9V3R3
Three buttons 	One black 1NO+1NC pushbutton, one red 1NO+1NC pushbutton, green 1NO+1NC pushbutton	  	I4T20N3R3V3
Ammeter, two indicator lights and two buttons 	Ammeter, one red and one green 24 VAC/DC indicator light, red 1NO+1NC pushbutton, green 1NO+1NC pushbutton	    	I4T32AR9V9R3V3

Control station type A (aluminium)

Ex e



EXPLODED VIEW



MECHANICAL FEATURES

Body and cover:

Gaskets:

Certificate plate:

Screws:

Earth screw:

Coating:

Cable gland:

Resistenza alla corrosione:

Low copper content aluminium alloy.

Acid, hydrocarbon and high temperature resistant silicon positioned between the body and the cover

Riveted aluminium

Stainless steel

Internal M5 on body and cover connected to each other with a 2.5 mm wire²

RAL 7035 epoxy (Light grey)

Polyamide type NAVP20IXE

The STANDARD of the aluminium alloy used by Cortem has passed the tests required by standards EN60068-2-30 (hot-humid cycles) and EN60068-2-11 (salt fog test)

ACCESSORIES UPON REQUEST / SPECIAL REQUESTS

Safety measures and padlocks for stations

Safety measures against accidental contacts (padlockable)

Earthing rings for control units

Nameplates in various materials

Breather or drainage valve


Metal cable glands

Other contact types (see Ex e Control, monitoring and signalling stations folder)

Various possible configurations

Control station type A (aluminium)

DIMENSIONAL DIAGRAM















CODE SELECTION TABLE

	Illustration	Description	Diagram	Codes
Indicator light		<ul style="list-style-type: none"> One red 24 VAC/DC indicator light One green 24 VAC/DC indicator light One blue 24 VAC/DC indicator light One yellow 24 VAC/DC indicator light One colourless 24 VAC/DC indicator light 		<ul style="list-style-type: none"> A1T01R9 A1T01V9 A1T01B9 A1T01G9 A1T01I9
Button		<ul style="list-style-type: none"> One red 1NO+1NC pushbutton One black 1NO+1NC pushbutton One green 1NO+1NC pushbutton One red 1NO pushbutton One black 1NO pushbutton One green 1NO pushbutton One red 1NC pushbutton One black 1NC pushbutton One green 1NC pushbutton One red 2NO pushbutton One black 2NO pushbutton One green 2NO pushbutton One red 2NC pushbutton One black 2NC pushbutton One green 2NC pushbutton 	 	<ul style="list-style-type: none"> A1T01R3 A1T01N3 A1T01V3 A1T01R1 A1T01N1 A1T01V1 A1T01R2 A1T01N2 A1T01V2 A1T01R4 A1T01N4 A1T01V4 A1T01R5 A1T01N5 A1T01V5


Control station type A (aluminium)

CODE SELECTION TABLE

	Illustration	Description	Diagram	Codes
Selector				
		Switch with two fixed-positions, suitable for "automatic-manual" 1NO+1NC service		A1T011Z
		Motors "start-stop" control, with spring return to 0 from both STOP and START.		A1T011X
		Motors "start-stop" control with spring return from START to 0, and in fixed STOP position can be padlocked.		A1T011R
		Three fixed position switch can be padlocked in the centre position. Versions: single pole - double pole - triple pole.		A1T011C
Button		Emergency mushroom head pushbutton with 1NO+1NC block (when pressed, rotate to release)		A1T01F3
		Emergency mushroom head pushbutton with 1NC block (when pressed, rotate to release)		A1T01F2
Ammeter/voltmeter		Ammeter (scale on request)		A1T02A
		Voltmeter (scale on request)		A1T02V
Two buttons		Red pushbutton + green pushbutton, 1NO+1NC contacts		A2T07R3V3
		Black pushbutton + green pushbutton, 1NO+1NC contacts		A2T07N3V3
		Red pushbutton + green pushbutton, 1NO contacts		A2T07R1V1
		Black pushbutton + green pushbutton, 1NC contacts		A2T07N1V1
Indicator light and pushbutton		24 VAC/DC red indicator light and one red 1NO+1NC pushbutton		A2T07R9R3
		24 VAC/DC green indicator light and one green 1NO+1NC pushbutton		A2T07V9V3
		24 VAC/DC red indicator light and one red 1NC pushbutton		A2T07R9R2
		24 VAC/DC green indicator light and one green 1NC pushbutton		A2T07V9V2

Control station type A (aluminium)

CODE SELECTION TABLE

Illustration	Description	Diagram	Codes
Indicator light and pushbutton	24 VAC/DC red indicator light and one red 1NO pushbutton		A2T07R9R1
	24 VAC/DC green indicator light and one green 1NO pushbutton		A2T07V9V1
Indicator light and emergency pushbutton	24 VAC/DC red indicator light and emergency 1NO+1NC mushroom pushbutton		A2T07R9F3
	24 VAC/DC green indicator light and 1NO+1NC emergency mushroom pushbutton		A2T07V9F3
Pushbutton and emergency pushbutton	Green 1NO pushbutton and one 1NO emergency mushroom head pushbutton		A2T07V1F1
	Yellow 1NO pushbutton and one 1NO emergency mushroom head pushbutton		A2T07G1F1
	Green 1NO+1NC pushbutton and one 1NO+1NC emergency mushroom head pushbutton		A2T07V3F3
	Yellow 1NO+1NC pushbutton and one 1NO+1NC emergency mushroom head pushbutton		A2T07G3F3
Indicator light and two pushbuttons	24 VAC/DC green LED indicator light, one green 1NO pushbutton and red 1NC pushbutton		A3T18V9V1R2
Two pushbuttons and Emergency pushbutton	One green 1NO and one red 1NC pushbutton, one mushroom head 1NO pushbutton		A3T17V1R2F1
	One green 1NO and one red 1NC pushbutton, one mushroom head 1NC pushbutton		A3T17V1R2F2
Two indicator lights and two pushbuttons	24 VAC/DC red and green LED indicator lights, one green 1NO pushbutton and red 1NC pushbutton		A3T19V9R9V1R2

Control station type A (aluminium)


CODE SELECTION TABLE

Illustration	Description	Diagram	Codes
Two indicator lights and two pushbuttons	24 VAC/DC red and green LED indicator lights, one green 1NO+1NC pushbutton and red 1NO+1NC pushbutton		A4T25V9R9V3R3
Three buttons	Two green pushbuttons and one red 1NO+1NC		A4T26V3R3V3
Two indicator lights and two selectors	24 VAC/DC red and green LED indicator lights, two switches arrangement 2 1		A4T27R9V92I2I
Ammeter and selector	Ammeter 1 A, scale 3 - 5 In and "start-stop" motors control switch, with spring return to 0 from both STOP and START.		A4T39A1X
Ammeter and two buttons	Ammeter 1 A, scale 3 - 5 In with red 1NO pushbutton and green 1NO pushbutton		A4T40AR1V1
	Ammeter 1 A, scale 3 - 5 In with red 1NO pushbutton and green 1NC pushbutton		A4T40AR1V2



Ex e control, monitoring and signalling devices

The M-0 control, monitoring and signalling stations are installed as accessories outside of 'Ex e' enclosures, panels and control stations used in all industrial environments where there may be an explosive atmosphere classified as Zone 1, 2, 21, 22. The M-0 devices allow the electrical or mechanical equipment assembled inside the 'Ex e' enclosures to be opened or closed, and the light signalling of the operating status. The components of the control stations are constructed from stainless steel to ensure maximum efficiency in almost any environmental conditions. The levers are constructed from aluminium, and the plastic pushbutton components ensure maximum durability over time, even in highly corrosive atmospheres. The M-0 control devices have an IP66 protection rating.




Contactblock for pushbuttons

ELECTRICAL FEATURES

Rated voltage							
400 V	500 V	690 V	400 V	400 V	400 V	48 V	230 V
Category of use							
AC-15	AC-15	AC-15	AC-1	AC-2	AC-3	DC-13	DC-13
Rated current							
10 A	4 A	2 A	16 A	6 A	2.4 A	10 A	0.5 A

Rated voltage:	max. 690 V
Frequency:	50/60 Hz
Rated current:	10 A
Connection:	max. 2.5 mm ²
Lightning impulse withstand voltage:	4 kV
Pollution degree:	2
Conditional short circuit current:	1kA
Maximum use of short circuit protection devices:	a gG 10A 500V fuse on each conductor
Minimum travel for positive opening:	3 mm
Minimum force required to achieve positive opening of all opening contacts:	5 N
Maximum travel (+ overtravel):	4.75 Hz
Body:	Polyamide
Contacts:	Brass
Pins, springs and screws:	Stainless steel



Installation

The new slot-in adapter system makes light work of fitting contacts in control panels with walls up to 7 mm thick. In addition, with the mushroom head pushbutton having a smaller diameter thread (M32x1.5), the cover can accommodate more control and signalling devices than the previous version.

Ex e control, monitoring and signalling devices

SAFETY MEASURES AND PADLOCKS FOR STATIONS, ACCESSORIES AND SPECIAL REQUESTS


Selector padlock system
(codes **M-962** and **M-963**)




Pushbutton padlock system
(code **M-0603/..L**)




Padlockable protection
(code **M-0631**)



Earthing rings for the installation control
units in polyester enclosures (code
A331IB)



Black mushroom head pushbutton
(code **M-0605/N**)



Ex e control, monitoring and signalling devices

Aluminium Cortem enclosure complete with:

- n°1 ammeter B-0140A
- n°1 M-0612/3R230 red indicator light
- n°1 green indicator light M-0612/3V230
- n°2 M-0604/1Z selectors
- n°1 NAV32IB type cable glands
- n°11 CBD2 type connections
- n°1 TE6O earth connection
- n°1 B32-229 internal frame
- External RAL7035 coating



Stainless steel Cortem enclosure complete with:

- n°1 ammeter B-0140A
- n°1 M-0605/K emergency pushbutton with key reset
- n°1 M-0603/NL padlockable black pushbutton
- n°1 M-0612/3G230 yellow indicator light
- n°1 green indicator light M-0612/3V230
- n°2 M-0604/1C selectors
- n°6 NAV32IB type cable glands
- n°1 B47-357 internal frame




SELECTOR ARRANGEMENT

Description	Badge	Single pole arrangement	Contacts	Single pole arrangement	Contacts	Codes																																																		
Motors "start-stop" control, with spring return to 0 from both STOP and START.			<table border="1"> <thead> <tr> <th>POS.</th> <th>1-2</th> <th>3-4</th> </tr> </thead> <tbody> <tr> <td>STOP</td> <td>O</td> <td>O</td> </tr> <tr> <td>0</td> <td>X</td> <td>O</td> </tr> <tr> <td>START</td> <td>X</td> <td>X</td> </tr> </tbody> </table>	POS.	1-2	3-4	STOP	O	O	0	X	O	START	X	X		<table border="1"> <thead> <tr> <th>POS.</th> <th>1-2</th> <th>3-4</th> <th>5-6</th> <th>7-8</th> </tr> </thead> <tbody> <tr> <td>STOP</td> <td>O</td> <td>O</td> <td>O</td> <td>O</td> </tr> <tr> <td>0</td> <td>X</td> <td>O</td> <td>X</td> <td>O</td> </tr> <tr> <td>START</td> <td>X</td> <td>X</td> <td>X</td> <td>X</td> </tr> </tbody> </table>	POS.	1-2	3-4	5-6	7-8	STOP	O	O	O	O	0	X	O	X	O	START	X	X	X	X	X																		
POS.	1-2	3-4																																																						
STOP	O	O																																																						
0	X	O																																																						
START	X	X																																																						
POS.	1-2	3-4	5-6	7-8																																																				
STOP	O	O	O	O																																																				
0	X	O	X	O																																																				
START	X	X	X	X																																																				
Motors "start-stop" control with spring return from START to 0, and in fixed STOP position can be padlocked.			<table border="1"> <thead> <tr> <th>POS.</th> <th>1-2</th> <th>3-4</th> </tr> </thead> <tbody> <tr> <td>STOP</td> <td>O</td> <td>O</td> </tr> <tr> <td>0</td> <td>X</td> <td>O</td> </tr> <tr> <td>START</td> <td>X</td> <td>X</td> </tr> </tbody> </table>	POS.	1-2	3-4	STOP	O	O	0	X	O	START	X	X		<table border="1"> <thead> <tr> <th>POS.</th> <th>1-2</th> <th>3-4</th> <th>5-6</th> <th>7-8</th> </tr> </thead> <tbody> <tr> <td>STOP</td> <td>O</td> <td>O</td> <td>O</td> <td>O</td> </tr> <tr> <td>0</td> <td>X</td> <td>O</td> <td>X</td> <td>O</td> </tr> <tr> <td>START</td> <td>X</td> <td>X</td> <td>X</td> <td>X</td> </tr> </tbody> </table>	POS.	1-2	3-4	5-6	7-8	STOP	O	O	O	O	0	X	O	X	O	START	X	X	X	X	R																		
POS.	1-2	3-4																																																						
STOP	O	O																																																						
0	X	O																																																						
START	X	X																																																						
POS.	1-2	3-4	5-6	7-8																																																				
STOP	O	O	O	O																																																				
0	X	O	X	O																																																				
START	X	X	X	X																																																				
Switch with two fixed-positions, suitable for "automatic-manual" service			<table border="1"> <thead> <tr> <th>POS.</th> <th>1-2</th> <th>3-4</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>X</td> <td>O</td> </tr> <tr> <td>1</td> <td>O</td> <td>X</td> </tr> </tbody> </table>	POS.	1-2	3-4	0	X	O	1	O	X		<table border="1"> <thead> <tr> <th>POS.</th> <th>1-2</th> <th>3-4</th> <th>5-6</th> <th>7-8</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>X</td> <td>O</td> <td>X</td> <td>O</td> </tr> <tr> <td>1</td> <td>O</td> <td>X</td> <td>O</td> <td>X</td> </tr> </tbody> </table>	POS.	1-2	3-4	5-6	7-8	0	X	O	X	O	1	O	X	O	X	Z																										
POS.	1-2	3-4																																																						
0	X	O																																																						
1	O	X																																																						
POS.	1-2	3-4	5-6	7-8																																																				
0	X	O	X	O																																																				
1	O	X	O	X																																																				
Switch			<table border="1"> <thead> <tr> <th>POS.</th> <th>1-2</th> <th>3-4</th> </tr> </thead> <tbody> <tr> <td>OFF</td> <td>O</td> <td>O</td> </tr> <tr> <td>ON</td> <td>X</td> <td>X</td> </tr> </tbody> </table>	POS.	1-2	3-4	OFF	O	O	ON	X	X		<table border="1"> <thead> <tr> <th>POS.</th> <th>1-2</th> <th>3-4</th> <th>5-6</th> </tr> </thead> <tbody> <tr> <td>OFF</td> <td>O</td> <td>O</td> <td>O</td> </tr> <tr> <td>ON</td> <td>X</td> <td>X</td> <td>X</td> </tr> </tbody> </table>	POS.	1-2	3-4	5-6	OFF	O	O	O	ON	X	X	X	I																													
POS.	1-2	3-4																																																						
OFF	O	O																																																						
ON	X	X																																																						
POS.	1-2	3-4	5-6																																																					
OFF	O	O	O																																																					
ON	X	X	X																																																					
Three fixed position switch can be padlocked in the centre position. Versions: single pole - double pole - triple pole			<table border="1"> <thead> <tr> <th>POS.</th> <th>1-2</th> <th>3-4</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>X</td> <td>O</td> </tr> <tr> <td>0</td> <td>O</td> <td>O</td> </tr> <tr> <td>2</td> <td>O</td> <td>X</td> </tr> </tbody> </table>	POS.	1-2	3-4	1	X	O	0	O	O	2	O	X		<table border="1"> <thead> <tr> <th>POS.</th> <th>1-2</th> <th>3-4</th> <th>5-6</th> <th>7-8</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>X</td> <td>O</td> <td>X</td> <td>O</td> </tr> <tr> <td>0</td> <td>O</td> <td>O</td> <td>O</td> <td>O</td> </tr> <tr> <td>2</td> <td>O</td> <td>X</td> <td>O</td> <td>X</td> </tr> </tbody> </table>	POS.	1-2	3-4	5-6	7-8	1	X	O	X	O	0	O	O	O	O	2	O	X	O	X	C																		
POS.	1-2	3-4																																																						
1	X	O																																																						
0	O	O																																																						
2	O	X																																																						
POS.	1-2	3-4	5-6	7-8																																																				
1	X	O	X	O																																																				
0	O	O	O	O																																																				
2	O	X	O	X																																																				
Three position switch can be padlocked in centre position with spring return to 0 from positions 1 and 2.			<table border="1"> <thead> <tr> <th>POS.</th> <th>1-2</th> <th>3-4</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>X</td> <td>O</td> </tr> <tr> <td>0</td> <td>O</td> <td>O</td> </tr> <tr> <td>2</td> <td>O</td> <td>X</td> </tr> </tbody> </table>	POS.	1-2	3-4	1	X	O	0	O	O	2	O	X		<table border="1"> <thead> <tr> <th>POS.</th> <th>1-2</th> <th>3-4</th> <th>5-6</th> <th>7-8</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>X</td> <td>O</td> <td>X</td> <td>O</td> </tr> <tr> <td>0</td> <td>O</td> <td>O</td> <td>O</td> <td>O</td> </tr> <tr> <td>2</td> <td>O</td> <td>X</td> <td>O</td> <td>X</td> </tr> </tbody> </table>	POS.	1-2	3-4	5-6	7-8	1	X	O	X	O	0	O	O	O	O	2	O	X	O	X	W																		
POS.	1-2	3-4																																																						
1	X	O																																																						
0	O	O																																																						
2	O	X																																																						
POS.	1-2	3-4	5-6	7-8																																																				
1	X	O	X	O																																																				
0	O	O	O	O																																																				
2	O	X	O	X																																																				
5 position reversing start switch. Lever with fixed C position and spring return to 0 from A and B			<table border="1"> <thead> <tr> <th>POS.</th> <th>1-2</th> <th>5-6</th> <th>7-8</th> <th>3-4</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>X</td> <td>X</td> <td>O</td> <td>O</td> </tr> <tr> <td>0</td> <td>O</td> <td>X</td> <td>O</td> <td>O</td> </tr> <tr> <td>C</td> <td>O</td> <td>O</td> <td>O</td> <td>O</td> </tr> <tr> <td>0</td> <td>O</td> <td>O</td> <td>X</td> <td>O</td> </tr> <tr> <td>B</td> <td>O</td> <td>O</td> <td>X</td> <td>X</td> </tr> </tbody> </table>	POS.	1-2	5-6	7-8	3-4	A	X	X	O	O	0	O	X	O	O	C	O	O	O	O	0	O	O	X	O	B	O	O	X	X		<table border="1"> <thead> <tr> <th>POS.</th> <th>1-2</th> <th>3-4</th> <th>5-6</th> <th>7-8</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>X</td> <td>O</td> <td>X</td> <td>O</td> </tr> <tr> <td>0</td> <td>O</td> <td>O</td> <td>O</td> <td>O</td> </tr> <tr> <td>2</td> <td>O</td> <td>X</td> <td>O</td> <td>X</td> </tr> </tbody> </table>	POS.	1-2	3-4	5-6	7-8	1	X	O	X	O	0	O	O	O	O	2	O	X	O	X	Y
POS.	1-2	5-6	7-8	3-4																																																				
A	X	X	O	O																																																				
0	O	X	O	O																																																				
C	O	O	O	O																																																				
0	O	O	X	O																																																				
B	O	O	X	X																																																				
POS.	1-2	3-4	5-6	7-8																																																				
1	X	O	X	O																																																				
0	O	O	O	O																																																				
2	O	X	O	X																																																				
"Start" motors control with lever spring return to position B			<table border="1"> <thead> <tr> <th>POS.</th> <th>1</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>X</td> <td>O</td> </tr> <tr> <td>B</td> <td>O</td> <td>O</td> </tr> </tbody> </table>	POS.	1	A	X	O	B	O	O		<table border="1"> <thead> <tr> <th>POS.</th> <th>1</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>X</td> <td>O</td> </tr> <tr> <td>B</td> <td>O</td> <td>O</td> </tr> </tbody> </table>	POS.	1	A	X	O	B	O	O	M																																		
POS.	1																																																							
A	X	O																																																						
B	O	O																																																						
POS.	1																																																							
A	X	O																																																						
B	O	O																																																						

Ex e control, monitoring and signalling devices

Pushbutton M-0603

ILLUSTRATION



CODE


DESCRIPTION

NOTES


MODULAR CODES

M-0603/N	Black Ex e pushbutton without contacts	Add requested contact assembly	N
M-0603/NL	Black Ex e pushbutton can be locked without contacts	Add requested contact assembly	E
M-0603/R	Red Ex e pushbutton without contacts	Add requested contact assembly	R
M-0603/RL	Red Ex e pushbutton without contacts, can be padlocked	Add requested contact assembly	L
M-0603/V	Green Ex e pushbutton without contacts	Add requested contact assembly	V
M-0603/G	Yellow Ex e pushbutton without contacts	Add requested contact assembly	G
M-0603/B	Blue Ex e pushbutton without contacts	Add requested contact assembly	B
M-0603/BI	White Ex e pushbutton without contacts	Add requested contact assembly	I
M-0606/10	Contact assembly 1NO		1
M-0606/01	Contact assembly 1NC		2
M-0606/11	Contact assembly 1NO+1NC		3
M-0606/20	Contact assembly 2NO		4
M-0606/02	Contact assembly 2NC		5

Range of pushbuttons designed to permit the installation of an increased number of controls on the cover. Polyamide 6 caps available in various colours and in a lockable version. Plates, listing dimensions and with customised wording on the cover, can be affixed to all stations.



Drilling arrangement (minimum distances)



- 1) control unit with 4 contacts - control unit with 4 contacts
- 2) control unit with 4 contacts - control unit with 2 contacts
- 3) control unit with 2 contacts - control unit with 2 contacts
- A) control unit with 4 contacts - control unit with 4 contacts
- B) control unit with 2 contacts - control unit with 2 contacts

Ex e control, monitoring and signalling devices


Ex e

Selector M-0604


ILLUSTRATION	CODE	DESCRIPTION	MODULAR CODES	NOTES
	M-0604/X	Selector Ex e arrangement X	1X	
	M-0604/R	Selector Ex e arrangement R	1R	
	M-0604/RSX	Selector Ex e arrangement R left	RS	
	M-0604/1Z	Selector Ex e arrangement 1Z	1Z	
	M-0604/2Z	Selector Ex e arrangement 2Z	2Z	
	M-0604/1I	Selector Ex e arrangement 1I	1I	
	M-0604/2I	Selector Ex e arrangement 2I	2I	
	M-0604/3I	Selector Ex e arrangement 3I	3I	
	M-0604/4I	Selector Ex e arrangement 4I	4I	
	M-0604/1C	Selector Ex e arrangement 1C	1C	
	M-0604/2C	Selector Ex e arrangement 2C	2C	
	M-0604/1W	Selector Ex e arrangement 1W	1W	
	M-0604/2W	Selector Ex e arrangement 2W	2W	
	M-0604/1M	Selector Ex e arrangement 1M	1M	
		M-0606/11	Contact assembly 1NO+1NC	Replacement part for arrangements: X - R - 1Z - RSX
		M-0606/22	Contact assembly 2NO+2NC	Replacement part for arrangements: 2Z
		M-0606/10	Contact assembly 1NO	Replacement part for arrangements: 1I 1M
		M-0606/20	Contact assembly 2NO	Replacement part for arrangements: 2I 2M 1C 1W
		M-0606/30	Contact assembly 3NO	Replacement part for arrangements: 3I 3M
		M-0606/40	Contact assembly 4NO	Replacement part for arrangements: 4I 4M 2C 2W

Selector complete with 2 or 4 contacts, available in different electrical arrangements for connection to the electrical enclosure and machine. Can be padlocked and have earthing connection

Selector complete with contacts



Drilling arrangement (minimum distances)




Ex e control, monitoring and signalling devices

Emergency pushbutton M-0605




The emergency pushbutton allows the operator to safely lock out the machine by pressing the key. With 2 keys provided with each order, the pushbutton of model M-0605/K can be locked.

CODE	DESCRIPTION	MODULAR CODES	NOTES
M-0605	Emergency Ex e pushbutton with reset, without contacts	F	
M-0605/K	Emergency Ex e pushbutton with key reset, without contacts	K	Add requested contact assembly
M-0605/P	Press and pull Ex e pushbutton without contacts	P	
M-0606/10	Contact assembly 1NO	1	
M-0606/01	Contact assembly 1NC	2	
M-0606/11	Contact assembly 1NO+1NC	3	
M-0606/20	Contact assembly 2NO	4	
M-0606/02	Contact assembly 2NC	5	



Drilling layout (minimum distances)*



* Standard drilling layout.
 Up to 2 contacts can be used per station with the M-0605 emergency pushbutton


M-0612/3 multi-LED indicator light




Multi-LED indicator lights available in various cap colours and different voltages. Easy to install and wire and long-lasting reliability with 50,000 hour lifespan LEDs

CODE	DESCRIPTION	MODULAR CODES
M-0612/3B110	Blue 110 VAC/DC multi-LED indicator light	B6
M-0612/3B12	Blue 12 VAC/DC multi-LED indicator light	B7
M-0612/3B230	Blue 230 VAC multi-LED indicator light	B8
M-0612/3B24	Blue 24 VAC/DC multi-LED indicator light	B9
M-0612/3G110	Yellow 110 VAC/DC multi-LED indicator light	G6
M-0612/3G12	Yellow 12 VAC/DC multi-LED indicator light	G7
M-0612/3G230	Yellow 230 VAC multi-LED indicator light	G8
M-0612/3G24	Yellow 24 VAC/DC multi-LED indicator light	G9
M-0612/3I110	Colourless 110 VAC/DC multi-LED indicator light	I6
M-0612/3I12	Colourless 12 VAC/DC multi-LED indicator light	I7
M-0612/3I230	Colourless 230 VAC multi-LED indicator light	I8
M-0612/3I24	Colourless 24 VAC/DC multi-LED indicator light	I9
M-0612/3R110	Red 110 VAC/DC multi-LED indicator light	R6
M-0612/3R12	Red 12 VAC/DC multi-LED indicator light	R7
M-0612/3R230	Red 230 VAC multi-LED indicator light	R8
M-0612/3R24	Red 24 VAC/DC multi-LED indicator light	R9
M-0612/3V110	Green 110 VAC/DC multi-LED indicator light	V6
M-0612/3V12	Green 12 VAC/DC multi-LED indicator light	V7
M-0612/3V230	Green 230 VAC multi-LED indicator light	V8
M-0612/3V24	Green 24 VAC/DC multi-LED indicator light	V9

Drilling arrangement (minimum distances)



Front part of switch
M-0605, comprised of:
1. body
2. mushroom head pushbutton
3. o-ring
4. moving part
5. locknut



Ex e control, monitoring and signalling devices


Ammeter B-0140A, voltmeter B-0140V


CODE	DESCRIPTION	NOTES	MODULAR CODES
B-0140A	Ammeter	*	A
B-0140V	Voltmeter		V
Maximum voltage:	600 V		
Rated frequency:	40 ÷ 60 Hz		
Accuracy class:	1.5		
Power dissipation:	1.1 VA (B-0140A) 3.0 VA B-0140V		
Field of measure - Direct measurement:		0 - 40mA 0 - 60 mA 0 - 100 mA 0 - 250 mA 0 - 400 mA 0 - 600 mA	0 - 0.1A 0 - 1.5 A 0 - 2.5 A 0 - 5 A 0 - 6 A 0 - 15 A
Field of measure - With current transformer:		0 - 2.5mA 0 - 5 mA 0 - 10 mA 0 - 15 mA 0 - 20 mA 0 - 25 mA 0 - 30 mA 0 - 40 mA	0 - 50A 0 - 60 A 0 - 75 A 0 - 100 A 0 - 150 A 0 - 200 A 0 - 300 A 0 - 400 A



Cortem certified ammeters and voltmeters are suitable for measuring electrical quantities, when accuracy and precision are required. The internal plates with field-scale measurement are made to customer specification.

* For ammeter mod. B-0140A4 (4-20 mA) 1200 Ω impedance. If the driver is incompatible with this impedance, it is recommended to use the Cortem supplied transducer, mod. NI-DT1. The transducer must be installed in a safe zone.






Ex e

Series 01 - Supporting posts


Supporting for lighting fixtures handrail mounted

Code: COLONNINA 01


Supporting



Sect. C - C



Bearing plate




Note:

- 2mm steel plate support. Hot dip galvanized. Zinc covering thickness to be 400 g/m² or 50 µm
- N°4 welded bolts M12 with relevant nut and elastic washer

Series 03 - Supporting posts

Supporting for equipment on structure

Code: COLONNINA 03




Series 04 - Supporting posts

Supporting for equipment on structure on foundation block

Code: COLONNINA 04

Supporting






Series 05 - Supporting posts

Supporto apparecchiature, installazione su struttura.

Code: COLONNINA 05

Supporting



Note:


- 2mm steel plate support. Hot dip galvanized. Zinc covering thickness to be 400 g/m² or 50 µm
- N°4 welded bolts M12 with relevant nut and elastic washer

Series 06 - Supporting posts

Supporting for equipment on foundation block

Code: COLONNINA 06


Supporting



Protection cap

Protection cap for posts

Supporting



Code	Dimensions (mm)			Thickness
	A	B	C	
N1-300	600	200	180	20/10
N2-300	600	450	180	
N3-300	300	200	180	

Note:

- Material: Hot dip galvanized plate

PYN, SPYN

Sockets and plugs

- Group IIC
- Zone 1, 2, 21, 22
- Aluminium alloy
- Ergonomic
- Plugs can be used with industrial sockets
- Suitable for use in extreme temperatures



-60°C


Sockets and plugs designed for low temperatures



Cast metal fixing lugs



Steel chain



RAL7035 polyester coating

Aluminium alloy with low copper content

Series PYN... SPYN... Sockets and plugs from 16 A to 125 A

The PYN, SPYN series of sockets and plugs consists of 16 A and 32 A models and 63 A and 125 A models designed with 'Ex db eb, Ex tb' and 'Ex eb, Ex tb' protection and tested for operation at low temperatures down to -60°C.

The 16A and 32A sockets are equipped with an interlocked disconnect switch with the plug positioned beneath. The rotary movement together with the closing/opening operations which occur inside a special explosion-proof chamber ensure the electrical circuit is only connected after the SPYN series plug has been correctly inserted into its seat and can only be removed once the electrical circuit has been disconnected. The 63A and 125A models are equipped with an automatic circuit breaker as they are designed to withstand high electric loads.

The range includes two pole sockets + earth (PE); three pole sockets + earth (PE) and three pole sockets + neutral + earth (PE), with current capacities of 16A and reduced overall dimensions, up to a maximum of 125A. Voltages range from 50V to a maximum of 690VAC, with a maximum frequency of 50/60Hz. All plug models can also be used in normal industrial sockets conforming to standard IEC/EN 60309-2, whereas all socket models are manufactured so that they cannot be used with industrial type plugs.

Cortem Group applies a tamper-evident holographic security label to its products, complete with a unique authentication numeric code, to combat the illegal sale of imitations and counterfeits, as well as guarantee the authenticity of its products. Failure to observe international standards creates serious risks for the environment and, above all, for the personnel who work with the systems on a daily basis.



Sectors of application:



Petroleum
refineries



Chemical and
petrochemical
plants



Onshore
facilities



Offshore
facilities



Petroleum load-
ing/unloading
pontoons



Low
temperatures



Fuel storage
facilities



100%
produced by
Cortem

CERTIFICATE DATA

Classification:

Group II	Category 2GD		
zone 1 - zone 2 (Gas)	zone 21 - zone 22 (Dust)		

Installation: EN 60079-14

zone 1 - zone 2 (Gas)	zone 21 - zone 22 (Dust)		
-----------------------	--------------------------	--	--

Marking:

CE 0722 II 2 GD Ex db eb IIC T... Gb; Ex tb IIIC T... °C Db	Socket
CE 0722 II 2 GD Ex eb IIC T... Gb; Ex tb IIIC T... °C Db	Plug

Certificate:

ATEX IMQ 20 ATEX 049X		
IEC Ex IMQ 21.0003X	For all IEC Ex certificate data, download the certificate from www.cortemgroup.com	

Standards:

CENELEC EN 60079-0: 2018, EN 60079-1: 2014, EN 60079-7: 2017, EN 60079-31: 2014 and European Directive 2014/34/EU.
IEC 60079-0: 2017, IEC 60079-1: 2014, IEC 60079-7: 2017, IEC 60079-31: 2022
RoHS Directive 2002/95/EC.

Models:

16 A	32 A
------	------

Temperature class:

T85°C (T6)	T100°C (T4)
------------	-------------

Amb. Temperature:

-60°C +60°C	-60°C +60°C
-------------	-------------

Models:

63 A	125 A
------	-------

Temperature class:

T85°C (T6)	T140°C (T3)	T134°C (T4)
------------	-------------	-------------

Amb. Temperature:

-60°C +60°C	-60°C +55°C	-60°C +49°C
-------------	-------------	-------------

Degree of protection:

IP66

Series PYN... SPYN... Sockets and plugs from 16 A to 125 A

PYN..., SPYN... 16 A



SPYN..., PYN... 32 A



PYN... 63 A, 125 A



SPYN... 63 A e 125 A



MECHANICAL FEATURES

Socket body:

Low copper content aluminium alloy, complete with wall fastening lugs and plastic bayonet socket closure cap, with identifying colour and safety chain

Lid:

Screw fastened, aluminium alloy with low copper content. Used to access socket and make electrical connection

Plug:

Low copper content aluminium alloy, complete with colour coded plastic lock rings to identify the mains power supply voltage

Pins:

nickel-plated brass

Gasket:

Acid, hydrocarbon and high temperature resistant silicone positioned between the body and the lid

Certificate label:

Adhesive affixed to external surface

Screws, bolts and nuts:

Stainless steel

Coating:

Polyester RAL 7035 (Light grey)

Corrosion Resistance:

The STANDARD of the aluminium alloy used by Cortem has passed the tests required by standards EN60068-2-30 (hot-humid cycles) and EN60068-2-11 (salt fog test)


The SPYN series plugs can also be used with industrial solder type sockets. This possibility is also designed to allow the user to keep a limited stock of spare parts. In fact, the position of the phase and earth pins, together with the coloured lock rings which comply with the colour code required by IEC/EN 60309-2 for industrial sockets and plugs, identify them according to the power supply voltage and current used.

For a better understanding, we have included the earth pin (PE) positioning drawing and relative colours, in compliance with IEC/EN 60309-2, for voltages greater than 50V.

PIN POSITION

The hour position h is determined with the socket viewed from the front, observing the position of the earth contact in relation to the main reference point always positioned at 6 o'clock.

The different rated voltages are also given different colour-coded conventions.




Series PYN... SPYN... Sockets and plugs from 16 A to 125 A

ELECTRICAL FEATURES

Rated voltage:	Max. 690 V
Rated frequency:	Max. 50/60 Hz
Rated current:	16 A, 32 A, 63 A and 125 A
Cable entry:	no. 2 on the socket and no. 1 on the plug
Max. cable cross-section:	for 16A: 4 mm ² for 63 A: 10 - 16 mm ² for 32A: 6 mm ² for 125 A: 35 - 50 mm ²


DIMENSIONAL DRAWING

16 A and 32 A




Dimensions in mm

PYN... Socket




SPYN... Plug




MODEL	DIMENSIONS (mm)							WEIGHT (kg)
	A	B	C	y	x	w	Ø d	
PYN..16..	Ø 90	165	135	104	50	8	3/4" NPT	1,7
PYN..32..	Ø 120	240	175	140	80	8	1" NPT	2,1
SPYN..16..	Ø 66	116	-	-	-	-	3/4" NPT	0,3
SPYN..32..	Ø 92	145	-	-	-	-	1" NPT	0,6


63 A and 125 A



PYN... Socket



SPYN... Plug



Dimensions in mm

MODEL	DIMENSIONS (mm)						WEIGHT (kg)
	A	B	C	a	b	Ø d	
PYN..63..	280	337	210	213	213	1 1/2" NPT	11
PYN..125..	280	345	210	213	213	1 1/2" NPT	11,4
SPYN..63..	108	226	-	-	-	ISO M32x1,5	1,2
SPYN..125..	124	235	-	-	-	ISO M40x1,5	1,5

Series PYN... SPYN... Sockets and plugs from 16 A to 125 A






CODE SELECTION TABLE

RATED CURRENT	NUMBER OF POLES	FREQUENCY Hz	RATED VOLTAGE Vac	ARRANGEMENT	WEIGHT (kg)	SOCKET CODE	PLUG CODE
16 A	2P + $\frac{1}{-}$	50 / 60	20 / 25		1.70	PYN216V	SPYN216V
	2P + $\frac{1}{-}$	50 / 60	100 / 130		1.70	PYN216G	SPYN216G
	2P + $\frac{1}{-}$	50 / 60	200 / 250		1.70	PYN216B	SPYN216B
	2P + $\frac{1}{-}$	50 / 60	380 / 415		1.70	PYN216R	SPYN216R
	2P + $\frac{1}{-}$	50 / 60	480 / 500		1.70	PYN216N	SPYN216N
	3P + $\frac{1}{-}$	50 / 60	20 / 25		1.70	PYN316V	SPYN316V
	3P + $\frac{1}{-}$	50 / 60	200 / 250		1.70	PYN316B	SPYN316B
	3P + $\frac{1}{-}$	50 / 60	100 / 130		1.70	PYN316G	SPYN316G
	3P + $\frac{1}{-}$	50 / 60	380 / 415		1.70	PYN316R	SPYN316R
32 A	2P + $\frac{1}{-}$	50 / 60	200 / 250		2.10	PYN232B	SPYN232B
	2P + $\frac{1}{-}$	50 / 60	100 / 130		2.10	PYN232G	SPYN232G
	2P + $\frac{1}{-}$	50 / 60	380 / 415		2.10	PYN232R	SPYN232R

Features comply with CEI EN 60309-1/60309-2

Series PYN... SPYN... Sockets and plugs from 16 A to 125 A

CODE SELECTION TABLE

RATED CURRENT	NUMBER OF POLES	FREQUENCY Hz	RATED VOLTAGE Vac	ARRANGEMENT	WEIGHT (kg)	SOCKET CODE	PLUG CODE
32 A	2P + $\frac{1}{-}$	50 / 60	20 / 25		2.10	PYN232V	SPYN232V
	3P + $\frac{1}{-}$	50 / 60	200 / 250		2.10	PYN332B	SPYN332B
	3P + $\frac{1}{-}$	50 / 60	100 / 130		2.10	PYN332G	SPYN332G
	3P + $\frac{1}{-}$	50 / 60	500		2.10	PYN332N	SPYN332N
	3P + $\frac{1}{-}$	50 / 60	380 / 415		2.10	PYN332R	SPYN332R
	3P + $\frac{1}{-}$	50* / 60	440		2.10	PYN332RR	SPYN332RR
	3P + $\frac{1}{-}$	50 / 60	20 / 25		2.10	PYN332V	SPYN332V
	3P + N + $\frac{1}{-}$	50 / 60	200 / 250		2.10	PYN432B	SPYN432B
	3P + N + $\frac{1}{-}$	50 / 60	100 / 130		2.10	PYN432G	SPYN432G
	3P + N + $\frac{1}{-}$	50 / 60	500		2.10	PYN432N	SPYN432N
	3P + N + $\frac{1}{-}$	50 / 60	380 / 415		2.10	PYN432R	SPYN432R
	3P + N + $\frac{1}{-}$	50* / 60	440		2.10	PYN432RR	SPYN432RR

Features comply with CEI EN 60309-1/60309-2

* Frequency not covered by IEC 60309-2

Series PYN... SPYN... Sockets and plugs from 16 A to 125 A

CODE SELECTION TABLE

RATED CURRENT	NUMBER OF POLES	FREQUENCY Hz	RATED VOLTAGE Vac	ARRANGEMENT	WEIGHT (kg)	SOCKET CODE	PLUG CODE
63 A	2P + $\frac{1}{-}$	50 / 60	200 / 250	 6h	2.10	PYN263B	SPYN263B
	2P + $\frac{1}{-}$	50 / 60	380 / 415	 9h	2.10	PYN263R	SPYN263R
	3P + $\frac{1}{-}$	50 / 60	200 / 250	 9h	2.10	PYN363B	SPYN363B
	3P + $\frac{1}{-}$	50 / 60	500	 7h	2.10	PYN363N	SPYN363N
	3P + $\frac{1}{-}$	50 / 60	690	 5h	2.10	PYN363NN	SPYN363NN
	3P + $\frac{1}{-}$	50 / 60	380 / 415	 6h	2.10	PYN363R	SPYN363R
	3P + $\frac{1}{-}$	50 / 60	440	 11h	2.10	PYN363RR	SPYN363RR
	3P + N + $\frac{1}{-}$	50 / 60	200 / 250	 9h	2.10	PYN463B	SPYN463B
	3P + N + $\frac{1}{-}$	50 / 60	500	 7h	2.10	PYN463N	SPYN463N
	3P + N + $\frac{1}{-}$	50 / 60	690	 5h	2.10	PYN463NN	SPYN463NN
	3P + N + $\frac{1}{-}$	50 / 60	380 / 415	 6h	2.10	PYN463R	SPYN463R
	3P + N + $\frac{1}{-}$	50 / 60	440	 11h	2.10	PYN463RR	SPYN463RR

Features comply with CEI EN 60309-1/60309-2

Series PYN... SPYN... Sockets and plugs from 16 A to 125 A

CODE SELECTION TABLE

RATED CURRENT	NUMBER OF POLES	FREQUENCY Hz	RATED VOLTAGE Vac	ARRANGEMENT	WEIGHT (kg)	SOCKET CODE	PLUG CODE
125 A	2P + $\frac{1}{-}$	50 / 60	200 / 250		2.10	PYN2125B	SPYN2125B
	2P + $\frac{1}{-}$	50 / 60	380 / 415		2.10	PYN2125R	SPYN2125R
	3P + $\frac{1}{-}$	50 / 60	200 / 250		2.10	PYN3125B	SPYN3125B
	3P + $\frac{1}{-}$	50 / 60	500		2.10	PYN3125N	SPYN3125N
	3P + $\frac{1}{-}$	50 / 60	690		2.10	PYN3125NN	SPYN3125NN
	3P + $\frac{1}{-}$	50 / 60	380 / 415		2.10	PYN3125R	SPYN3125R
	3P + $\frac{1}{-}$	50 / 60	440		2.10	PYN3125RR	SPYN3125RR
	3P + N + $\frac{1}{-}$	50 / 60	200 / 250		2.10	PYN4125B	SPYN4125B
	3P + N + $\frac{1}{-}$	50 / 60	500		2.10	PYN4125N	SPYN4125N
	3P + N + $\frac{1}{-}$	50 / 60	690		2.10	PYN4125NN	SPYN4125NN
	3P + N + $\frac{1}{-}$	50 / 60	380 / 415		2.10	PYN4125R	SPYN4125R
	3P + N + $\frac{1}{-}$	50 / 60	440		2.10	PYN4125RR	SPYN4125RR

Features comply with CEI EN 60309-1/60309-2


Series PYN... SPYN... Sockets and plugs from 16 A to 125 A

ILLUSTRATION	DESCRIPTION	MODEL	FEATURES	CODE	LEGEND
	Cable gland	1 1/2" NPT ISO M32 ISO M40	Material: nickel-plated brass	NAV5NB NAV32IB NAV40IB	 
	Cap	1 1/2" NPT ISO M32 ISOM40	Material: nickel-plated brass	PLG5NB PLG3I PLG4I	 
	Coloured ring with bayonet connection	SPYN216... SPYN316... SPYN232... SPYN332... SPYN432... SPYN263... SPYN363... SPYN463... SPYN2125... SPYN3125... SPYN4125...	The rated voltage or frequency of each plug is identified by its colour	M16-523/1... M16-751/1... M32-523/1... M-766/1... M-1014/... M-1036/...	
	Coloured cap with bayonet connection and safety chain to prevent losing cap	PYN216... PYN316... PYN232... PYN332... PYN432... PYN263... PYN363... PYN463... PYN2125... PYN3125... PYN4125...	The rated voltage or frequency of each plug is identified by its colour	M-0384/1... M-0574/1... M-0385/1... M-0564/1... M-0681/... M-0682/...	

Series PYN... SPYN... Sockets and plugs from 16 A to 125 A

SAFETY SYSTEM


The **16 A** and **32 A** sockets are equipped with an internal disconnect switch which, by turning the attached plug, closes/opens the contacts inside a special explosion-proof chamber, thus containing any explosions in the presence of gas. The electrical circuit is only connected after the SPYN series plug has been correctly inserted into its seat and it can only be removed once the electrical circuit has been disconnected.




The plug cannot be removed from the socket if it has not first been turned anticlockwise to disconnect the internal electrical circuit.

The **63 A** and **125 A** sockets are equipped with a circuit breaker. Activating the switch via the external control handle triggers the closing/opening operations inside a special explosion-proof chamber, thus containing any explosions in the presence of gas. The electrical circuit is only connected after the SPYN series plug has been correctly inserted into its seat and it can only be removed once the electrical circuit has been disconnected.


Internal circuit breaker in
"ON" position.



Internal circuit breaker in
"ON" position.



Internal circuit breaker in
"OFF" position.




The plug will not come out of the socket if the switch is in "ON" position (with the control handle facing upwards).

YFC

Limit switch

- Group IIC
- Zone 1, 2, 21, 22
- Aluminium alloy
- Easy installation, wiring and maintenance
- Durable and safe over time

24 operating head types



YFC Series Limit switch

YFC Series explosion-proof limit switches feature an actuator linked mechanically to the contacts. The series includes both position switches and switches for safety applications. They are available in ten basic versions, depending on the type of actuator used, or sixty versions, if snap-action or slow-action contacts are considered.

Thanks to the combination of various types of actuators, bodies and contacts, YFC limit switches are ideal for a wide range of applications and for seamless system operation.

Being corrosion- and vibration-resistant, their mechanical and electrical components are able to withstand the extreme mechanical and thermal stresses they are continuously subjected to. Designed for installation in potentially explosive atmospheres, in the presence of combustible gases (hydrogen and acetylene), vapour, mist and powders, zones 1 and 21, 2 and 22, they are also used in watertight industrial and civil applications.

Cortem Group applies a tamper-evident holographic security label to its products, complete with a unique authentication numeric code, to combat the illegal sale of imitations and counterfeits, as well as guarantee the authenticity of its products. Failure to observe international standards creates serious risks for the environment and, above all, for the personnel who work with the systems on a daily basis.



Sectors of application:



Petroleum
refineries



Chemical and
petrochemical
facilities



Onshore
facilities



Offshore
facilities



Petroleum
loading/
unloading
pontoons



Agribusiness
facilities



Fuel storage
facilities



100%
produced by
Cortem

CERTIFICATION DATA

Classification:

Group II	Category 2GD		
----------	--------------	--	--

Installation: EN 60079-14

zone 1 - zone 2 (Gas)	zone 21 - zone 22 (Dust)		
-----------------------	--------------------------	--	--

Marking:

CE 0722 Ex II 2 GD Ex d IIC T6 Ex d tD A21 T85°C IP66/67			
--	--	--	--

Certificate:

ATEX	SIRA 07 ATEX 1316		
IEC Ex	IECEx SIR 07.0104	For all IEC Ex certification data download the certificate from www.cortemgroup.com	

Standard:

CENELEC EN 60079-0: 2006, EN 60079-1: 2004, EN 61241-0: 2006, EN 61241-1: 2004
and European Directive 2014/34/EU.
IEC 60079-0: 2004, IEC 60079-1: 2003, IEC 61241-0: 2004, IEC 61241-1: 2004
RoHS Directive 2002/95/EC.

Temperature class:

85°C (T6)				
-----------	--	--	--	--

Ambient Temp.:

-20°C	+55°C			
-------	-------	--	--	--

Degree of protection:

IP66/67				
---------	--	--	--	--



MECHANICAL FEATURES

Body:	Low copper content aluminium alloy, complete with wall fastening lugs
Gaskets:	Acid, hydrocarbon and high temperature resistant silicone positioned between the body and the cover
Certification label:	Adhesive affixed to external surface
Screws:	Stainless steel
Earth screw:	Internal and external stainless steel
Coating:	Polyester RAL 7035 (Light grey)
Entry points:	One entry point ISO M20x1.5
Mounting positions:	All positions
Consistency (measured following a million operations):	0.05 mm (at the point of closure)
Minimum control speed:	0.06 m/s slow action 0.001 m/s snap action
Corrosion Resistance:	The STANDARD of the aluminium alloy used by Cortem has passed the tests required by standards EN60068-2-30 (hot-humid cycles) and EN60068-2-11 (salt fog test)

ELECTRICAL FEATURES



Rated voltage:	max. 500 Vac, 250 Vdc
Rated frequency:	max. 50/60 Hz
Rated current:	24 Vac - 50/60 Hz: 10 A 120 Vac - 50/60 Hz: 6 A 230 Vac - 50/60 Hz: 3.1 240 Vac - 50/60 Hz: 3.1 A 400 Vac - 50/60 Hz: 1.8 A 24 Vdc: 2.8 A 125 Vdc: 0.55 A 250 Vdc: 0.27 A
Connecting cable cross-section:	0.75 ... 2.5 mm ²

ACCESSORIES UPON REQUEST / SPECIAL REQUESTS

Cable gland

YFC Series Limit switch

DIMENSIONAL DRAWING



TERMINOLOGY

Positive opening operation

 A control switch, with one or more break-contact elements, has a positive opening operation when the switch actuator (C) ensures the full opening of the contacts. For the part of travel that separates the contacts, there must be a positive zone with no resilient elements (e.g.: springs) between the moving contacts and the point where the actuator force is applied. The positive opening operation does not deal with N.O. contacts.

Control switches with positive opening operation may be provided with snap-action or slow-action contact elements. To use several contacts on the same control switch with positive opening operation, they must be electrically separated from each other; if not, only one contact may be used.

Snap action

Snap action contacts are characterised by a release position that is distinct from the operating position. The opening (or closure) of snap-action contacts is independent of the switch actuator speed and contributes to regular electric performance, even for slow switch actuator speeds.

Slow action



Slow-action contacts have a release position that is the same as the operating position. The switch actuator speed directly conditions the travel speed of contacts.

Minimum actuation force / torque


The minimum amount of force/torque that is to be applied to the switch actuator to produce a change in contact position.

Minimum force/torque to achieve positive opening operation

The minimum amount of force/torque that is to be applied to the switch actuator to ensure positive opening operation of the N.C. contact.



Travel for non-overlapping slow-action contacts



For slow-action contacts:

$C3 = 0$

$C1-1$ = pre-travel of contacts 21-22

$C1-2$ = pre-travel of contacts 13-14

Po Free position

Position of the switch actuator when no external force is exerted on it.

Pa Operating position

Position of the switch actuator, under the effect of force $F1$, when the contacts leave their initial free position.

Pp Positive opening position

Position of the switch actuator from which positive opening operation is ensured.

L Max. travel position

Maximum acceptable travel position of the switch actuator under the effect of a force $F1$.

Pr Release position

Position of the switch actuator when the contacts return to their initial free position.

C1 Pre-travel

Distance between the free position Po and the operating position Pa .

Cp Positive opening travel

Minimum travel of the switch actuator, from the free position Po , to ensure positive opening operation of the N.C. contacts.

C2 Max. travel

Distance between the operating position Pa and the max. travel position L .

CL Max. travel

Distance between the free position Po and the max. travel position L .

C3 Differential travel (C1-C4)

Travel difference between Pa and Pr .

C4 Release travel

Distance between Pr and Po .

YFC Series Limit switch

Sample order code

YFC - **E21** **Z11**
 MODEL OPERATING HEAD TYPE CONTACT TYPE

Limit switch with stainless steel lateral plain plunger and snap-action contact (1N.O. + 1N.C.)

CODE SELECTION TABLE

OPERATING HEAD MODEL	E21 Stainless steel lateral plain plunger	E22 Stainless steel lateral plunger with Ø12 vertical roller	E23 Stainless steel lateral plunger with Ø12 horizontal roller
Compliance / (positive opening operation N.C. contacts)	EN 50041	EN 50041	EN 50041
Max. control speed [m/s]	0.5	0.5	0.5
Minimum actuation force [N] or torque [Nm]	30 / 50	30 / 50	30 / 50
CONTACT TYPE			
Z11 Snap-action contacts (1N.O.+1N.C.)	<p>YFC-E21Z11</p> <p>0 2.0 3.2 4.8 6.0 mm 21-22 13-14 21-22 13-14</p>	<p>YFC-E22Z11</p> <p>0 3.7 5.9 8.8 10.2 mm 21-22 13-14 21-22 13-14</p>	<p>YFC-E23Z11</p> <p>0 3.7 5.9 8.8 10.2 mm 21-22 13-14 21-22 13-14</p>
X11 Slow action break before make (1N.O.+1N.C.)	<p>YFC-E21X11</p> <p>0 2.3 3.9 6.0 mm 21-22 13-14 3.2</p>	<p>YFC-E22X11</p> <p>0 4.6 7.5 10.2 mm 21-22 13-14 6.0</p>	<p>YFC-E23X11</p> <p>0 4.6 7.5 10.2 mm 21-22 13-14 6.0</p>
Y11 Slow action make before break 1NO+1NC	<p>YFC-E21Y11</p> <p>0 3.6 5.2 6.0 mm 21-22 13-14 2.2</p>	<p>YFC-E22Y11</p> <p>0 6.6 9.5 10.2 mm 21-22 13-14 4.3</p>	<p>YFC-E23Y11</p> <p>0 6.6 9.5 10.2 mm 21-22 13-14 4.3</p>
W02 Slow-action contacts (2N.C.)	<p>YFC-E21W02</p> <p>0 2.2 3.8 6.0 mm 21-22 11-12</p>	<p>YFC-E22W02</p> <p>0 4.3 7.2 10.2 mm 21-22 11-12</p>	<p>YFC-E23W02</p> <p>0 4.3 7.2 10.2 mm 21-22 11-12</p>
W20 Slow-action contacts (2N.O.)	<p>YFC-E21W20</p> <p>0 2.1 6.0 mm 23-24 13-14</p>	<p>YFC-E22W20</p> <p>0 4.1 10.2 mm 23-24 13-14</p>	<p>YFC-E23W20</p> <p>0 4.1 10.2 mm 23-24 13-14</p>
Z02 Snap action (2N.C.)	<p>YFC-E21Z02</p> <p>0 2.0 3.1 4.7 6.0 mm 21-22 11-12 21-22 11-12</p>	<p>YFC-E22Z02</p> <p>0 3.7 5.7 8.6 10.2 mm 21-22 11-12 21-22 11-12</p>	<p>YFC-E23Z02</p> <p>0 3.7 5.7 8.6 10.2 mm 21-22 11-12 21-22 11-12</p>
DIMENSIONS (mm)			











YFC Series Limit switch

CODE SELECTION TABLE

OPERATING HEAD MODEL	E3.. One way lever Ø22 E31: nylon roller E32: stainless steel roller E33: steel bearing	E4.. Lever with Ø22 roller E41: nylon roller E42: stainless steel roller E43: steel bearing	E44 Lever with Ø50 rubber roller
Compliance / (positive opening operation N.C. contacts)	EN 50041	EN 50041	EN 50041
Max. control speed [m/s]	1.5	1.5	1.5
Minimum actuation force [N] or torque [Nm]	12 / 40	0.15 / 0.30	0.15 / 0.30
CONTACT TYPE			
Z11 Snap-action contacts (1N.O.+1N.C.)	YFC-E3.Z11 0 3.1 6.3 10.8 15.5 mm 21-22 13-14 21-22 13-14	YFC-E4.Z11 0 20° 33° 49° 78° 21-22 13-14 21-22 13-14	YFC-E4.Z11 0 20° 33° 49° 78° 21-22 13-14 21-22 13-14
X11 Slow action break before make (1N.O.+1N.C.)	YFC-E3.X11 0 4.5 9.0 15.5 mm 21-22 13-14 6.1	YFC-E4.X11 0 22° 38° 78° 21-22 13-14 33°	YFC-E4.X11 0 22° 38° 78° 21-22 13-14 33°
Y11 Slow action make before break 1NO+1NC	YFC-E3.Y11 0 7.2 11.7 15.5 mm 21-22 13-14 4.0	YFC-E4.Y11 0 37° 53° 78° 21-22 13-14 21°	YFC-E4.Y11 0 37° 53° 78° 21-22 13-14 21°
W02 Slow-action contacts (2N.C.)	YFC-E3.W02 0 4.0 9.5 15.5 mm 21-22 11-12	YFC-E4.W02 0 21° 37° 78° 21-22 11-12	YFC-E4.W02 0 21° 37° 78° 21-22 11-12
W20 Slow-action contacts (2N.O.)	YFC-E3.W20 0 3.6 15.5 mm 21-22 13-14 23-24	YFC-E22W20 0 20° 78° 21-22 13-14 23-24	YFC-E4.W20 0 20° 78° 21-22 13-14 23-24
Z02 Snap action (2N.C.)	YFC-E3.Z02 0 3.1 6.1 10.6 15.5 mm 21-22 11-12 21-22	YFC-E4.Z02 0 20° 32° 48° 78° 21-22 11-12 21-22	YFC-E4.Z02 0 20° 32° 48° 78° 21-22 11-12 21-22
DIMENSIONS (mm)			

YFC Series Limit switch

CODE SELECTION TABLE

OPERATING HEAD MODEL	E5.. One way lever Ø22 E51: nylon roller E52: stainless steel roller E53: steel bearing	E61 Nylon actuator with a stainless steel spring	E62 Stainless steel spring actuator
Compliance / (positive opening operation N.C. contacts)	EN 50041	EN 50041	EN 50041
Max. control speed [m/s]	1.5	1.5	1.5
Minimum actuation force [N] or torque [Nm]	0.15 / 0.30	0.15 / -	0.15 / -
CONTACT TYPE			
Z11 Snap-action contacts (1N.O.+1N.C.)	 YFC-E5.Z11 0 20° 33° 49° 78° 21-22 13-14 21-22 13-14	 YFC-E61Z11 0 20° 33° 78° 21-22 13-14 21-22 13-14	 YFC-E62Z11 0 20° 33° 78° 21-22 13-14 21-22 13-14
X11 Slow action break before make (1N.O.+1N.C.)	 YFC-E5.X11 0 22° 38° 78° 21-22 13-14 33°	 YFC-E61X11 0 22° 78° 21-22 13-14 33°	 YFC-E62X11 0 22° 78° 21-22 13-14 33°
Y11 Slow action make before break 1NO+1NC	 YFC-E5.Y11 0 37° 53° 78° 21-22 13-14 21°	 YFC-E61Y11 0 37° 78° 21-22 13-14 21°	 YFC-E62Y11 0 37° 78° 21-22 13-14 21°
W02 Slow-action contacts (2N.C.)	 YFC-E3.W02 0 21° 37° 78° 11-12 21-22	 YFC-E61W02 0 21° 78° 11-12 21-22	 YFC-E62W02 0 21° 78° 11-12 21-22
W20 Slow-action contacts (2N.O.)	 YFC-E5.W20 0 20° 78° 13-14 23-24	 YFC-E61W20 0 20° 78° 13-14 23-24	 YFC-E62W20 0 20° 78° 13-14 23-24
Z02 Snap action (2N.C.)	 YFC-E5.Z02 0 20° 32° 48° 78° 11-12 21-22 11-12 21-22	 YFC-E61Z02 0 20° 32° 78° 11-12 21-22 11-12 21-22	 YFC-E62Z02 0 20° 32° 78° 11-12 21-22 11-12 21-22
DIMENSIONS (mm)			

YFC Series Limit switch

CODE SELECTION TABLE

OPERATING HEAD MODEL	E7.. Adjustable rod lever E71 : stainless steel rod Ø3 E72 : nylon rod Ø6 E73 : fibreglass rod Ø3 E75 : metal rod 3x3	E91 Multi-directional stainless steel spring actuator	E99 Pull action with ring
Compliance / (positive opening operation N.C. contacts)	EN 50041	EN 50041	EN 50041
Max. control speed [m/s]	1.5	1	0.5
Minimum actuation force [N] or torque [Nm]	0.15 / 0.30	0.18 / -	25 / -
CONTACT TYPE			
Z11 Snap-action contacts (1N.O.+1N.C.)	YFC-E7.Z11 	YFC-E91Z11 	YFC-E99Z11
X11 Slow action break before make (1N.O.+1N.C.)	YFC-E7.X11 	YFC-E91X11 	YFC-E99X11
Y11 Slow action make before break 1NO+1NC	YFC-E7.Y11 	YFC-E91Y11 	YFC-E99Y11
W02 Slow-action contacts (2N.C.)	YFC-E7.W02 	YFC-E91W02 	YFC-E99W02
W20 Slow-action contacts (2N.O.)	YFC-E7.W20 	YFC-E91W20 	YFC-E99W20
Z02 Snap action (2N.C.)	YFC-E7.Z02 	YFC-E91Z02 	
DIMENSIONS (mm)			

YFC Series Limit switch

CODE SELECTION TABLE

OPERATING HEAD MODEL	E11	E12	E13	
Compliance / (positive opening operation N.C. contacts)	EN 50041	EN 50041	EN 50041	
Max. control speed [m/s]	0.5	0.5	0.5	
Minimum actuation force or torque	30 / 45	30 / 45	22 / 40	
CONTACT TYPE				
Z11 Snap-action contacts (1N.O.+1N.C.)		YFC-E11Z11 0 1.8 3.0 4.6 6.0 mm 21-22 13-14	YFC-E12Z11 0 1.8 3.0 4.6 6.0 mm 21-22 13-14	YFC-E13Z11 0 3.1 5.3 8.2 10.5 mm 21-22 13-14
X11 Slow action break before make (1N.O.+1N.C.)		YFC-E11X11 0 2.1 3.7 6.0 mm 21-22 13-14 3.0	YFC-E61X11 0 2.1 3.7 6.0 mm 21-22 13-14 3.0	YFC-E13X11 0 4.0 6.9 10.5 mm 21-22 13-14 5.4
Y11 Slow action make before break 1NO+1NC		YFC-E11Y11 0 3.4 5.0 6.0 mm 21-22 13-14 2.0	YFC-E61Y11 0 3.4 5.0 6.0 mm 21-22 13-14 2.0	YFC-E13Y11 0 6.0 8.9 10.5 mm 21-22 13-14 3.7
W02 Slow-action contacts (2N.C.)		YFC-E11W02 0 2.0 3.6 6.0 mm 11-12 21-22	YFC-E61W02 0 2.0 3.6 6.0 mm 11-12 21-22	YFC-E13W02 0 3.7 6.6 10.5 mm 11-12 21-22
W20 Slow-action contacts (2N.O.)		YFC-E11W20 0 1.9 6.0 mm 13-14 23-24	YFC-E61W20 0 1.9 6.0 mm 13-14 23-24	YFC-E13W20 0 3.5 10.5 mm 13-14 23-24
Z02 Snap action (2N.C.)		YFC-E11Z02 0 1.8 2.9 4.5 6.0 mm 11-12 21-22	YFC-E61Z02 0 1.8 2.9 4.5 6.0 mm 11-12 21-22	YFC-E13Z02 0 3.1 5.1 8.0 10.5 mm 11-12 21-22
DIMENSIONS (mm)				

GRDC-4200

Electronic capacitive earthing system

'Ex eb / tb'

- Zone 1, 2, 21, 22
- High quality electronic components
- Aluminium or polyester casing
- High resistance to corrosion and extreme weather
- Safe and reliable over time
- Marking with one or two earthing pliers



GRDC-4200 Capacitive electronic earthing system 'Ex eb / tb'

The GRDC-4200 is a capacitive-type electronic earthing system that ensures earthing of tankers, rail tankers and IBCs (intermediate bulk containers) when transporting flammable liquids such as fuels, chemicals, powders and granulates.

The system analyses the overall capacitance of the vehicle, to provide consent for load activation, only in the case of actual connection. Thanks to the electrical capacitance reading of the connected device, the GRDC-4200 can distinguish whether it has been connected to the tank or to another metal object (pipe, ladder, etc.), thereby increasing the level of reliability and safety and preventing possible misuse by the operator.

During the whole loading and unloading phase, the device checks that the earthing system remains equipotential via the connection of earthing pliers.

The GRDC-4200 consists of a Cortem Ex eb/tb casing containing ATEX/IECEx-certified earthing control logic, Cortem Ex eb/tb control and signalling devices such as selector switches and LED indicators, and one or more earthing pliers for connecting to tankers or other metal parts.

Cortem Group applies a tamper-evident holographic security label to its products, complete with a unique authentication numeric code, to combat the illegal sale of imitations and counterfeits, as well as guarantee the authenticity of its products. Failure to observe international standards creates serious risks for the environment and, above all, for the personnel who work with the systems on a daily basis.



Sectors of application:



Petroleum
refineries



Chemical and
petrochemical
facilities



Onshore
facilities



Offshore
facilities



Petroleum
loading/
unloading
pontoons



Agribusiness
facilities



Fuel storage
facilities



100%
produced by
Cortem

CERTIFICATE DATA

Classification:

Group II	Category 2GD		
----------	--------------	--	--

Installation:

EN 60079-14	zone 1 - zone 2 (Gas)	zone 21 - zone 22 (Dust)		
-------------	-----------------------	--------------------------	--	--

Marking:

CE 0722 Ex II 2GD - Ex db eb mb [ia Ga] IIC T... Gb - Ex tb [ia Da] IIIC T... °C Db

Certificate:

ATEX	CML 20 ATEX 3235X		
IEC Ex	IECEx CML 20.0144X		
UKEX	AVAILABLE	For all IEC Ex, UKEX certificate data, download the certificate from www.cortemgroup.com	

Standards:

CENELEC EN 60079-0: 2018, EN 60079-1: 2014, EN 60079-7: 2015+A1:2018, EN 60079-11: 2012, EN 60079-18: 2015+A1:2017, EN 60079-31: 2014, EN 60529: 1991 and European Directive 2014/34/EU. IEC 60079-0: 2017, IEC 60079-1: 2014-06, IEC 60079-7: 2015, IEC 60079-11: 2011, IEC 60079-18: 2017, IEC 60079-31: 2013, IEC 60529: 2001. RoHS Directive 2002/95/EC.

Temperature class:

85°C (T6)

85°C (T5)

85°C (T4)

Ambient temperature:

-40°C +40°C

-40°C +50°C

-40°C +60°C

Degree of protection:

IP66

GRDC-4200 Capacitive electronic earthing system 'Ex eb / tb'

GRDC-4200..



GRDC-4200..P ..



MECHANICAL FEATURES

GRDC-4200..

Body and lid:
Resistant to knocks:
Gasket:

Inputs:
Certificate label:
Screws, bolts and nuts:
Earthing screw:
Mounting:
Coating:

Low copper content aluminium alloy

IK10

Acid, hydrocarbon and high temperature resistant silicone positioned between the body and the lid

ISO M20

Adhesive

Stainless steel, captive type

Stainless steel. Inside and outside the body, complete with anti-rotation brackets

Cast aluminium feet for M6 screws

Polyester RAL 7035 (Light grey)

Resistenza alla corrosione :

The STANDARD of the aluminium alloy used by Cortem has passed the tests required by the Standard EN60068-2-30 (hot-humid cycles) and EN60068-2-11 (salt fog test)

GRDC-4200..P..

Body and lid:
Resistant to knocks:
Gasket:

Mounting:
Certificate label:
Screws, bolts and nuts:
Inputs:

Black polyester resin with antistatic properties

IK10

Acid, hydrocarbon and high temperature resistant silicone positioned between the body and the lid

Polyester feet for M6 screws

Adhesive

Stainless steel, captive type

ISO M20

Pliers:

Bipolar, casting with aluminium with handles in neoprene, jaws with steel tips, auto-releasing. 16 mm opening.

Spiral cable:

Yellow with trim in rubber resistant to oil and chemical substances. Suitable for extremely high mechanical stresses. Length 8 m (extended).

In stainless steel.

In aluminium with black anodic oxidation.

Green polycarbonate.

Bracket for pliers:

Selector switch:

Indicator light:



ACCESSORIES UPON REQUEST / SPECIAL REQUESTS


Cable gland

Body and lid in stainless steel AISI 316L

Operation of the capacitive earthing system in Ex environments

The GRDC earthing system is designed to prevent the accumulation of electrostatic charges generated during loading and unloading from transport vehicles containing flammable and explosive liquid (e.g. fuels) or solid (e.g. coal, flour) products.


An earthing connection between the tanker truck and the earthing network of the system is not enough to prevent the generation of sparks. A series of safety measures must be taken to connect the two systems safely, ensuring the safety of people and the protection of property. These systems are commonly referred to as "earthing systems" and operate on the principle of equipotential bonding of metallic conducting and semiconducting objects present during loading or unloading of potentially explosive products.



This system, known as a capacitive earthing system, differs from the resistive type system (Cortem Product code GRDE) in terms of its ability to distinguish a tanker from a simple metal component (e.g. a tank cage, a container). This is necessary in order to ensure maximum safety, also in the event of a possible error or misuse by the operator who, by connecting the pliers to a simple metal part, can obtain consent from the resistive-type earthing system causing them to proceed with unsafe loading/unloading operations.


In fact, a resistive earthing system only checks that the pliers are connected to a component with good conductivity (low resistance) and that the resistance between ground and the component connected to the earthing pliers is below a certain limit.

Therefore, with a capacitive earthing system, if an operator connects the pliers to a simple metal element it recognises that it is not connected to a tanker truck and does not allow the loading/unloading of the liquid.



GRDC-4200 Capacitive electronic earthing system 'Ex eb / tb'

This system consists of a earthing control logic called PCBLCZ-4200 which, protected by the 'Ex mb' protection mode, not only monitors the parameters of the earth connection, but also has an intersectional safety barrier 'Ex ia' which ensures engagement of the pliers for safe earth connection. Furthermore, thanks to this logic, in addition to enabling the connection to ground in order to remove electrostatic charges from the tanker truck, tanker, etc., the GRDC system can also be used to enable the switching on of the loading/unloading pump through the use of a double contact relay. This way, in the unfortunate event that the ground connection fails, the flammable liquid loading/unloading operation is immediately stopped in complete safety until the connection to ground is restored. The GRDC system can be supplied with one or two earthing pliers for simultaneous connection of several tankers.



Operating guide

STEP 1

Switch on - Automatic check of the earth resistance connection

Set the selector switch from OFF to ON

- Positive result - yellow indicator light stops flashing after 5 seconds
- Negative result - continuous yellow indicator light flashes waiting for the earth connection to improve

STEP 2

Earthing pliers connection - Capacitive load control

After having connected the pliers to the tank:

- there is a capacitance to ground greater than the pre-set value, the white indicator light turns on giving the consent to STEP 3
- correct capacitive load to ground is not present (connect the pliers to a different metal object), white indicator light off, access to STEP 3 not permitted.

STEP 3

Electrostatic current discharge - Enabling or stopping the operation

- Once the correct earthing is verified, by turning and holding the switch in the START position for 2-3 seconds, the green indicator light turns on and the internal logic checks that the impedance value does not exceed 10Ω for the duration of the operation, thereby enabling or stopping the operation via a relay.




By-pass function

The GRDC earthing system has an integrated by-pass system, which in the event of critical conditions, e.g. rain, snow and excessive humidity, is still able to allow vehicle loading/unloading. In these cases, recognition of a tanker truck, for example, may not be reliable since the capacitive values can no longer be measured accurately. The by-pass consists of holding the selector switch on START for at least 10 seconds, thereby excluding the capacitive reading. If the pliers have been properly connected to a metal component, the green indicator light will come on giving consent for the operation.

GRDC-4200 Capacitive electronic earthing system 'Ex eb / tb'

DIMENSIONAL DRAWING




Dimensions in mm

SELECTION TABLE


Code	Housing material	Number of pliers	Power	Power supply	Rated frequency	Weight
GRDC-4200				220-240 VAC	50 - 60 Hz	3.73 kg
GRDC-4200-24	Aluminium			12-24 VDC	0 Hz	3.73 kg
GRDC-4200-110				110 VAC	50 - 60 Hz	3.73 kg
GRDC-4200-P		One set of pliers	< 10W	220-240 VAC	50 - 60 Hz	3.28 kg
GRDC-4200-P-24	Polyester			12-24 VDC	0 Hz	3.28 kg
GRDC-4200-P-110				110 VAC	50 - 60 Hz	3.28 kg

WIRING DIAGRAM



GRDC-4200 Capacitive electronic earthing system 'Ex eb / tb'

DIMENSIONAL DRAWING




Dimensions in mm


SELECTION TABLE

Code	Housing material	Number of pliers	Power	Power supply	Rated frequency	Weight
GRDC-4200-2				220-240 VAC	50 - 60 Hz	6.93 kg
GRDC-4200-2-24	Aluminium			12-24 VDC	0 Hz	6.93 kg
GRDC-4200-2-110				110 VAC	50 - 60 Hz	6.93 kg
GRDC-4200-2P		Two pliers	< 20W	220-240 VAC	50 - 60 Hz	6.13 kg
GRDC-4200-2P-24	Polyester			12-24 VDC	0 Hz	6.13 kg
GRDC-4200-2P-110				110 VAC	50 - 60 Hz	6.13 kg

WIRING DIAGRAM




GRDC-4200 Accessories upon request and spare parts

ILLUSTRATION	DESCRIPTION	MODEL	CODE	LEGEND
	Green 12 VAC/DC multi-LED indicator light	GRDC-..	M-0612/3V12	
	Yellow multi-LED indicator light	GRDC...	M-0487/G	
	Colourless multi-LED indicator light		M-0487/I	
	Switch	GRDC...	M-0604/3R	
	Monitoring logic	GRDC-4200...	LCZ-4200C	
		GRDC-4200...24	LCZ-4200C/24	
		GRDC-4200...110	LCZ-4200C/110	
	Earthing pliers	GRDC...	PZCC-4209	
	Yellow cable Length: 8 metres	GRDC...	20CE063	
	Cable gland cable range 6.5 - 14	GRDC...	NAV20SIB	 

GRDE-4200

Electronic earthing system 'Ex eb / tb'

- Zone 1, 2, 21, 22
- High quality electronic components
- Aluminum or polyester junction box
- High resistance to corrosion and extreme weather
- Safe and reliable over time
- Available with one or two earthing clamps



GRDE-4200 Electronic earthing system 'Ex eb / tb'

The GRDE-4200 electronic earthing system help to prevent fire and explosions in areas with hazardous levels of static electricity when trucks or trains load and unload liquids and dry materials.

During the entire loading and unloading phase, the device checks that the equipotentiality of the earthing system is maintained by using the connection of an earthing clamp.

In fact, the electronic system is equipped with a protection circuit that checks the resistance value and compares it to the set parameter and, if this value falls within the pre-set range, closes the electrical circuit between the two systems that are equipotential. Viceversa, it removes the operating consent from the loading pump and closes the loading valve.

The GRDE-4200 is composed by 'Ex eb/tb' Cortem enclosure, which contain the ATEX/IECEx certified grounding control logic LCZ-4200, and by Cortem 'Ex eb/ tb' control and signal devices such as selectors and alert LED lights. It can be provided with one or two earthing clamps for the connection to tank trucks or other metallic parts.

Cortem Group applies a tamper-evident holographic security label to its products, complete with a unique authentication numeric code, to combat the illegal sale of imitations and counterfeits, as well as guarantee the authenticity of its products. Failure to observe international standards creates serious risks for the environment and, above all, for the personnel who work with the systems on a daily basis.



Sectors of application:



Petroleum
refineries



Chemical and
petrochemical
facilities



Onshore
facilities



Offshore
facilities



Petroleum load-
ing/unloading
pontoons



Agribusiness
facilities



Fuel storage
facilities



100%
produced by
Cortem

CERTIFICATION DATA

Classification:

Group II	Category 2GD		
zone 1 - zone 2 (Gas)	zone 21 - zone 22 (Dust)		

Marking:

CE 0722 Ex II 2GD - Ex db eb mb [ia Ga] IIC T.. Gb - Ex tb [ia Da] IIIC T.. °C Da IP66

Certificate:

ATEX	CML 20 ATEX 3235X		
IEC Ex	IECEx CML 20.0144X		
UKEX	AVAILABLE	For all IEC Ex, UKEX certification data, download the certificate from www.cortemgroup.com	

Standards:

CENELEC EN 60079-0: 2018, EN 60079-1: 2014, EN 60079-7: 2015, EN 60079-11: 2012, EN 60079-18: 2015, EN 60079-31: 2014, EN 60529: 1991 and the European Directive 2014/34/UE.
IEC 60079-0: 2017, IEC 60079-1: 2014-06 IEC 60079-7: 2015, IEC 60079-11: 2011, IEC 60079-18: 2017, IEC 60079-31: 2013, IEC 60529: 2001. RoHS Directive 2002/95/EC.

Temperature class:

85°C (T6)	85°C (T5)		
-----------	-----------	--	--

Ambient Temperature:

-40°C	+50°C	+	+60°C	+	
-------	-------	---	-------	---	--

Degree of protection:

IP66		
------	--	--

GRDE-4200 Electronic earthing system 'Ex eb / tb'

GRDE-4200..



GRDE-4200..P ..



MECHANICAL FEATURES

GRDE-4200..

Body and lid:	Low copper content aluminium alloy
Impact protection rating:	IK10
Gasket:	Acid, hydrocarbon and high temperature-resistant silicone, located between body and lid
Inputs:	ISO M20
Certification label:	Aluminium plate riveted onto lid
Bolts and screws:	Stainless steel captive variety
Earth screws:	Stainless steel. On inside and outside of body complete with anti-rotation brackets
Mounting:	Cast aluminium feet for M6 screw
Coating:	Polyester RAL 7035 (Light grey)

Corrosion Resistance:

The STANDARD of the aluminium alloy used by Cortem has passed the tests required by standards EN 60068-2-30 (hot/humid cycles) and EN 60068-2-11 (salt mist tests)

GRDE-4200..P..

Body and lid:	Made from polyester resin in black with antistatic properties
Impact protection rating:	IK10
Gasket:	Acid, hydrocarbon and high temperature-resistant silicone, located between body and lid
Mounting:	Polyester feet for M6 screws
Certification label:	Aluminium plate riveted into lid
Bolts and screws:	Stainless steel captive variety
Inputs:	ISO M20

Plier:

Bipolar, casting with aluminium with handles in neoprene, jaws with steel tips, auto-releasing. 16 mm opening.

Spiral cable:

Yellow with oil and chemical resistant rubber coating. Suitable for very high mechanical stresses. Length 8 meters (extended).

Bracket for plier:

In stainless steel.

Selector lever:

In aluminum with black anodic oxidation.

Indicator light:

In transparent colored polycarbonate.



SPECIAL REQUESTS

Cable gland

Model with body and lid in stainless steel AISI 316L

The use of the grounding system in Ex environments

Equipotential bonding of electrostatically charged metal masses

Everyone must have experienced an electrostatic shock at least once, on a cold, dry afternoon, when exiting a car and touching the door handle to close it. The static energy accumulated by being in a car isolated from the ground, discharges to the ground itself through our body when we come into contact with it if we are not isolated (wearing rubberised shoes).

Static electricity in the human body can reach 10-15 kV (kilovolts) and its discharge can reach 20-30 mJ (millijoules), which is well above the ignition limit of propane, gasoline vapours and fine dust particles.

In potentially explosive atmospheres, these phenomena occur while loading and/or unloading vehicles carrying flammable and explosive products. Hazardous environments that require an earthing system are, for example:

- loading/unloading tanker bays,
- jetties used for loading/unloading oil, methane or gas tankers
- silos used to transfer liquid or solid products.


Filling, dispensing, transporting and tipping materials into vehicles or containers generates static electricity simply through the movement of the material being processed or handled.

The charge level is greater for poorly conductive solvents flowing through plastic pipes. Furthermore, a fast flow or large amounts of air bubbles flowing through the pipe can amplify the static electricity.

The flammable charge can ignite if the vehicle is not adequately earthed.

An earth connection between the tanker and the earth network of the plant is not enough to prevent sparks from being generated a number of safety measures must be adopted, which connect the two systems safely, guaranteeing the safety of people and the property. These systems are commonly referred to as "earthing systems" and function based on the principle of equipotential bonding of conductive and semi-conductive metal objects while loading or unloading potentially explosive products.

For this reason, the "earthing" systems must be implemented in such a way as to guarantee full plant functionality while protecting the safety of the operators assigned, in compliance with current regulations. The earthing system connects the object to the ground




GRDE-4200 Electronic earthing system 'Ex eb / tb'

and discharges any accumulated voltage, which is absorbed by the ground and neutralised.


Cortem Group's GRDE series earthing device meets all the functionality and safety specifications set forth in the regulations for such operations and is designed to be installed in environments at risk of explosion due to the presence of flammable gas and/or dust.

In fact, this system consists of an earth control logic called LCZ-4200, which thanks to the 'Ex mb' protection, besides controlling the earth connection parameters, also has an 'Ex ia' intrinsic safety barrier that ensures the coupling of the clamp for the safe earth




connection.

Moreover, thanks to this logic, besides enabling the earth connection so as to eliminate the electrostatic charges of the tanker, cistern, etc., the GRDE system can also be used to enable the loading/unloading pump to switch-on thanks to a double contact relay. In this way, in the unfortunate event that the earth connection fails, the loading/unloading of the flammable liquid is immediately blocked in complete safety until the earth connection is restored. The GRDE system can be supplied with one or two earthing clamps for the simultaneous connection of several tankers or other metal parts.



GRDE-4200 Electronic earthing system 'Ex eb / tb'


DIMENSIONAL DRAWING



Dimensions in mm


SELECTION TABLE

Code	Material of the junction box	Number of pliers	Power supply	Rated frequency	Power consumption	Weight
GRDE-4200			220-240 Vac	50 - 60 Hz		3,25 Kg
GRDE-4200-12	Aluminium		12 Vac/dc	0 - 50 - 60 Hz		3,25 Kg
GRDE-4200-24			24 Vac/dc	0 - 50 - 60 Hz		3,25 Kg
GRDE-4200-110			110 Vac	50 - 60 Hz		3,25 Kg
GRDE-4200-P	One plier		220-240 Vac	50 - 60 Hz	6 W	2,80 Kg
GRDE-4200-P-12			12 Vac/dc	0 - 50 - 60 Hz		2,80 Kg
GRDE-4200-P-24			24 Vac/dc	0 - 50 - 60 Hz		2,80 Kg
GRDE-4200-P-110			110 Vac	50 - 60 Hz		2,80 Kg




GRDE-4200 Electronic earthing system 'Ex eb / tb'

DIMENSIONAL DRAWING




SELECTION TABLE

Code	Material of the junction box	Number of pliers	Power supply	Rated frequency	Power consumption	Weight
GRDE-4200-2			220-240 Vac	50 - 60 Hz		6,45 Kg
GRDE-4200-2-12	Aluminium		12 Vac/dc	0 - 50 - 60 Hz		6,45 Kg
GRDE-4200-2-24			24 Vac/dc	0 - 50 - 60 Hz		6,45 Kg
GRDE-4200-2-110		Two pliers	110 Vac	50 - 60 Hz	12 W	6,45 Kg
GRDE-4200-2P			220-240 Vac	50 - 60 Hz		5,65 Kg
GRDE-4200-2P-12	Polyester		12 Vac/dc	0 - 50 - 60 Hz		5,65 Kg
GRDE-4200-2P-24			24 Vac/dc	0 - 50 - 60 Hz		5,65 Kg
GRDE-4200-2P-110			110 Vac	50 - 60 Hz		5,65 Kg



GRDE-4200 Accessories upon request and spare parts

ILLUSTRATION	DESCRIPTION	MODEL	CODE	KEY
	Red multi-LED indicator 12 Vca/cc	GRDE-4200..	M-0612/3R12	
	Green multi-LED indicator 12 Vca/cc		M-0612/3V12	
	Special switch	GRDE...	M-0604/2R	
	Monitoring logic	GRDE-4200...	LCZ-4200	
		GRDE-4200...12	LCZ-4200/12	
		GRDE-4200..24	LCZ-4200/24	
		GRDE-4200...110	LCZ-4200/110	
	Earthing pliers	GRDE...	PZCC-4209	
	Yellow cable Length: 8 metres	GRDE...	20CE063	
	Cable gland range cable 6,5÷14	GRDE...	NAV20IB	

GRD-4200

Electronic earthing system

- Zone 1, 2, 21, 22
- High quality electronic components
- High resistance to corrosion and extreme weather
- Safe and reliable over time



SIL certified
Level 2



GRD-4200 Electronic earthing system

The GRD-4200 series electronic earthing system ensures grounding of tankers and tank trucks during the transfer of flammable liquids, preventing the formation of electrostatic charges.

During the entire loading and unloading phase, the device checks that the equipotentiality of the earthing system is maintained.

In fact, the electronic system is equipped with a protection circuit that checks the resistance value and compares it to the set parameter and, if this value falls within the preset range, closes the electrical circuit between the two systems that are equipotential. Vice versa, it removes the operating consent from the loading pump and closes the loading valve.

The GRD-4200 electronic earthing system has obtained SIL (Safety Integrity Level) Level 2 certification in compliance with IEC-61508 and EN-50495 standards, which guarantees that the system is able to perform its safety function.

Cortem Group applies a tamper-evident holographic security label to its products, complete with a unique authentication numeric code, to combat the illegal sale of imitations and counterfeits, as well as guarantee the authenticity of its products. Failure to observe international standards creates serious risks for the environment and, above all, for the personnel who work with the systems on a daily basis.



Sectors of application:



Petroleum refineries



Chemical and petrochemical facilities



Onshore facilities



Offshore facilities



Petroleum load/unloading pontoons



Agribusiness facilities



Fuel storage facilities



100% produced by Cortem

CERTIFICATION DATA

Classification:

Group II	Category 2GD		
----------	--------------	--	--

Installation: EN 60079-14

zone 1 - zone 2 (Gas)	zone 21 - zone 22 (Dust)		
-----------------------	--------------------------	--	--

Marking:

CE 0722 Ex II 2(1) G - Ex d [ia Ga] ia IIB+H ₂ T6 Gb			
CE 0722 Ex II 2(1) D - Ex tb [ia Da] ia IIIC T85°C Db			

Certificate:

ATEX CESI 04 ATEX 129			
IEC Ex IECEx CES 14.0035X	For all IEC Ex certification data, download the certificate from www.cortemgroup.com		

Standards:

CENELEC EN 60079-0: 2012, EN 60079-1: 2007, EN 60079-11: 2012, EN 60079-31:2009 and the European Directive 2014/34/UE.			
IEC 60079-0: 2011, IEC 60079-1: 2007, IEC 60079-11: 2011, IEC 60079-31: 2008 RoHS Directive 2002/95/EC.			

Temperature class:

85°C (T6)			
-----------	--	--	--

Ambient Temperature:

-20°C +55°C			
-------------	--	--	--

Degree of protection:

IP66			
------	--	--	--



MECHANICAL FEATURES

Body and lid:	Low copper content aluminium alloy
Gasket:	Acid, hydrocarbon and high temperature resistant silicone positioned between the body and the lid
Certificate label:	Riveted aluminium on lid
Screws, bolts and nuts:	Stainless steel
Earthing screw:	Stainless steel M6. Inside and outside the body and on the lid, complete with anti-rotation brackets
Fastening brackets:	Electrolytically galvanized steel
Lever on lid:	In coated aluminium
Warning lights:	Impact and UV resistant polycarbonate
Coating:	Polyester RAL 7035 (Light grey)
Resistenza alla corrosione :	The STANDARD of the aluminium alloy used by Cortem has passed the tests required by standards EN60068-2-30 (hot-humid cycles) and EN60068-2-11 (salt fog test)
Inputs:	2 threaded holes 3/4" NPT. Complete with a PLG2N plug
Cable gland:	For non-armored cable, internally sealed, thread 3/4" NPT
Cable:	Yellow with trim in rubber resistant to oil and chemical substances. Suitable for extremely high mechanical stresses. Length 8 m.
Plier:	Bipolar, casting with aluminium with handles in neoprene, jaws with steel tips, auto-releasing. 16 mm opening.
Bracket for plier:	In stainless steel.

ELECTRICAL FEATURES

Rated voltage:	230 Vac o 110 Vac o 24 Vac dc
Rated frequency:	max. 50/60 Hz

GRD-4200		
Status:	Block	Consent
Current draw:	12 mA	24 mA
Power:	1.64 W	4.32 W
Power factor:	0.57	0.82

GRD-4200/110		
Status:	Block	Consent
Current draw:	22 mA	45 mA
Power:	1.52 W	4.18 W
Power factor:	0.62	0.84


GRD-4200/24				
Status:	Block		Consent	
Voltage:	24 Vac	24 Vdc	24 Vac	24 Vdc
Current draw:	64 mA	24 mA	64 mA	24 mA
Power:	1.64 W	4.32 W	1.64 W	4.32 W
Power factor:	0.57	0.82	0.57	0.82

ACCESSORIES UPON REQUEST / SPECIAL REQUESTS

Cable gland
Pliers PMT-B2

GRD-4200 Electronic earthing system

DIMENSIONAL DRAWING



Detail of connection pliers



SELECTION TABLE

Code	Power supply	Rated frequency	Weight Kg
GRD-4200	230 Vac	50 - 60 Hz	20
GRD-4200/110	110 Vac	50 - 60 Hz	20
GRD-4200/24	24 Vac dc	0 / 50 - 60 Hz	20

ELECTRICAL WIRING




ILLUSTRATION	DESCRIPTION	MODEL	CODE	LEGEND
	Special switch	GRD...	SEA10X2/12EZ16R	
	Monitoring logic	GRD-4200	LCZ-4200	
		GRD-4200/110	LCZ-4200/110	
		GRD-4200/24	LCZ-4200/24	
	Earthing pliers	GRD...	PZCC-4209	
	Yellow cable Length: 8 metres	GRD...	NSSHOU-02X2,5	
	Barrier cable gland	GRD...	NAV B2NB	

Earthing pliers

- Group IIC
- Zone 1, 2, 21, 22
- Robust and easy to handle
- High resistance to corrosion and extreme weather
- Safe and reliable over time



PMT Earthing pliers

The PMT pliers are used to connect tankers and tank trucks to ground during loading and unloading operations. The ground contact occurs inside the body of the pliers in an Ex d chamber, only after the pliers have been connected to the local earthing system.

Cortem Group applies a tamper-evident holographic security label to its products, complete with a unique authentication numeric code, to combat the illegal sale of imitations and counterfeits, as well as guarantee the authenticity of its products. Failure to observe international standards creates serious risks for the environment and, above all, for the personnel who work with the systems on a daily basis.



Sectors of application:



Petroleum
refineries



Chemical and
petrochemical
facilities



Onshore
facilities



Offshore
facilities



Petroleum load-
unloading
pontoons



Agribusiness
facilities



Fuel storage
facilities



100%
produced by
Cortem

CERTIFICATION DATA

Classification:

Group II

Category 2GD

Installation:

EN 60079-14

zone 1 - zone 2 (Gas)

zone 21 - zone 22 (Dust)

Marking:

CE 0722 II 2GD - Ex d IIC T6 Ex tD A21 IP65 T85°C

Certificate:

ATEX

[CESI 03 ATEX 201](#)

Standards:

CENELEC EN 60079-0: 2006, EN 60079-1: 2004, EN 61241-0: 2006, EN 61241-1: 2004
and European Directive 2014/34/EU.

Temperature class:

85°C (T6)

Ambient Temperature:

-20°C +55°C

Degree of protection:

IP65

PMT Earthing pliers



MECHANICAL FEATURES


Grip:	In black non-slip rubber
External contact elements:	In phosphorous bronze
Certificate label:	Riveted aluminium on the grip
Screws, bolts and nuts:	Stainless steel
Cable gland:	For non-armored cable, thread ISO M32

ELECTRICAL FEATURES

Isolating voltage:	3 kV
Rated current:	20 A


SELECTION TABLE

Code	Cable range	Connection plate thickness	Weight Kg
PMT-B2	$\varnothing 11 - 14$	4 - 7	0.8



PMT Earthing pliers

DIMENSIONAL DRAWING




Dimensions in mm




Junction boxes for control, monitoring and control panel 'Ex tb'


- Zone 21, 22
- Category 2D
- Aluminium, reinforced polyester or stainless steel enclosures
- Standard or custom products



Quick-break switches



Built-in /magnethermal circuit breakers



Junction boxes for monitoring and control panel 'Ex tb'

The control, monitoring and signaling units SA, SA/P, CTB include a series of enclosures with "Ex tb" protection available in aluminum, polyester or stainless steel and in different measures.

According to the size and the material chosen, there are three maximum dissipation limits that correspond to each of the three maximum optional ambient temperatures: + 40° C, + 55° C and + 60° C.

Several IECEx/ATEX certified devices can be mounted on the enclosure faces and a glass or polycarbonate window can also be fixed to the lid. Various electronic devices can be installed internally with a total power dissipation within the limits defined for each housing such as terminals, analog and digital instruments, control and measurement devices, circuit breakers and IECEx / ATEX certified battery packs. SA/SS series stainless steel command and control junction boxes may be provided for 'Ex tb' panels on request.

Cortem Group applies a tamper-evident holographic security label to its products, complete with a unique authentication numeric code, to combat the illegal sale of imitations and counterfeits, as well as guarantee the authenticity of its products. The failure to observe international standards involves serious hazards to the environment and, above all, personnel who work with the systems on a daily basis.



Sectors of application:



Petroleum
refineries



Chemical and
petrochemical
plants



Onshore
plants



Offshore
plants



Petroleum
loading/
unloading
pontoons



Low
temperatures



Mining
operations



100%
produced by
Cortem

CERTIFICATION DATA

Classification:

Group II

Category 2D

Installation:

EN 60079.14

zone 21 - zone 22 (Dust)

Marking:

CE 0722 Ex II 2D Ex tb IIIC T80°C Db IP66

Certification:

ATEX CML 17 ATEX 3307X

IEC Ex CML 17.0162X

All IEC Ex certification data can be downloaded
from www.cortemgroup.com

Standards:

CENELEC EN 60079-0: 2012+A11:2013, EN 60079-31: 2014 and EUROPEAN DIRECTIVE 2014/34/UE
IEC 60079-0: 2011, IEC 60079-31: 2013

Temperature class:



T80°C; T100°C; T135°C

Ambient temperature:

-40°C +40°C
-40°C +55°C
-40°C +60°C

When Cortem ammeters and/or voltmeters are installed on the cover, the enclosures shall be marked with a maximum ambient temperature no higher than +40°C.
For details see max power dissipation table

Degree of protection:

IP66

Junction boxes for monitoring and control panel 'Ex tb' SA

ALLUMINIUM CONTROL HOUSINGS SA-SAG SERIES



MECHANICAL FEATURES

Body and lid:

Low copper content aluminium alloy

Gaskets:

Acid, hydrocarbon and high temperature resistant silicon positioned between the body and the lid

Certificate plate:

Aluminium label riveted

Screws:

Stainless steel

Earth screw:

Stainless steel. On inside and outside of body complete with anti-rotation brackets

Mounting:

Cast aluminium lugs for M6 screw

Coating:

Polyester Ral 7035 (light grey)


MAX POWER DISSIPATION

Junction box	Power (W) - for T80°C			Power (W) - for T100°C		
	T.a. +40°C	T.a. +55°C	T.a. +60°C	T.a. +40°C	T.a. +55°C	T.a. +60°C
SA111108	25,1	14,2	10,9			
SAG111108	21,8	13,1	10,1	32,4		
SA171108	21,8	13,1	10,1	32,4		
SAG171108	21,8	13,1	10,1	32,4		
SA141410	37,3	21,6	16,2	55,3		
SAG141410	38,3	22,1	16,3	57,0		
SA202012	37,3	21,6	16,2	55,3		
SA301410	37,3	21,6	16,2	55,3		
SAG301410	37,3	21,6	16,2	55,3		
SA302310	55,6	34,4	27,9	83,0	62,3	
SAG302310	52,0	30,7	24,4	77,3	57,8	52,0
SA302318	55,6	34,4	27,9	83,0	62,3	
SAG302318	52,0	30,7	24,4	77,3	57,8	52,0
SA473018	100,8	59,1	47,0	154,2	114,2	
SAG473018	100,8	59,1	47,0	154,2	114,2	
SAG623018	124,6	75,9	60,7	190,2	141,0	
SAG606018	100,8	59,1	47,0	154,2	114,2	

Junction boxes for monitoring and control panel 'Ex tb' SA

DIMENSIONAL DRAWING

Ex e



Dimensions in mm

SELECTION CHART

Code	External dimensions			a	Inner dimensions				X	Y	X1	ØD	Weight Kg
	A	B	C		b	c	S1	S2					
SA111108	110	110	83	104	104	64	3	2,5	94	94	-	6,5	0,50
SAG111108	110	110	83	96	96	64	7	2,5	94	94	-	6,5	0,75
SA171108	170	110	83	164	104	65	3	2,5	154	94	-	6,5	0,80
SAG171108	170	110	83	156	96	65	7	2,5	154	94	-	6,5	1,55
SA141410	147	147	100	141	141	80	3	2,5	131	131	-	6,5	0,80
SAG141410	147	147	100	133	133	80	7	2,5	131	131	-	6,5	1,40
SA202012	200	200	120	192	192	98	4	3	180	180	-	6,5	1,70
SA301410	305	147	110	296	138	90	4,5	3	285	127	-	6,5	2,00
SAG301410	305	147	96	291	133	75	7	4	285	127	-	6,5	2,70
SA302310	305	230	110	296	221	90	4,5	3	285	210	-	6,5	2,80
SAG302310	305	230	100	291	216	75	7	4	285	210	-	6,5	3,40
SA302318	305	230	190	296	221	165	4,5	3	285	210	-	6,5	3,50
SAG302318	305	230	180	291	216	155	7	4	285	210	-	6,5	5,30
SA473018	475	305	195	465	295	174	5	4	450	285	225	6,5	6,50
SAG473018	475	305	195	461	294	174	7	4	450	285	225	6,5	8,90
SAG623018	625	305	195	613	293	174	6	5	605	285	302,5	6,5	11,3
SAG606018	600	600	205	584	584	177	10÷13	5	580	580	290	8	27,0

Junction boxes for monitoring and control panel 'Ex tb' SA

BODY DRILLING DATA

THREAD COMPARISON CHART

D Thread diameter	01	1	2	3	4	5	6	7	8
ISO228	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"
Through hole	Ø17	Ø22	Ø27.5	Ø34	Ø43	Ø48.5	Ø60.5	Ø76	Ø89




D Thread diameter	01	1	2	3	4	5	6	7	8
ISO 261/965	16x1.5	20x1.5	25x1.5	32x1.5	40x1.5	50x1.5	63x1.5	75x1.5	90x1.5
Through hole	Ø17	Ø20.5	Ø25.5	Ø32.5	Ø40.5	Ø50.5	Ø63.5	Ø75.5	Ø85.5

D Thread diameter	01	1	2	3	4	5	6	7	8
ANSI B.20.1 NPSM	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"
Through hole	Ø17.5	Ø22	Ø27.5	Ø34	Ø43	Ø48.5	Ø60.5	Ø76	Ø89



As required by the current standard, holes can be drilled by Cortem or by authorized partners who hold a production notification in accordance with ATEX Directive .

TYPE OF ENCLOSURE	HOLE DRILLING IN BODY												Sides A and C								Drilling area mm		Sides B and D										
	Drilling area mm		MAXIMUM QUANTITY PER HOLE TYPE										Drilling area mm		MAXIMUM QUANTITY PER HOLE TYPE																		
			01	1	2	3	4	5	6	7	8	01	1	2	3	4	5	6	7	8													
SA/SAG111108	58x55		3	2	1	1	-	-	-	-	-	58x55		Square box																			
SA/SAG171108	68x55		3	2	1	1	-	-	-	-	-	128x55		5	5	3	2	2	2	-	-	-											
SA/SAG141410	100x65		6	6	3	2	1	-	-	-	-	100x65		Square box																			
SA202012	145x75		8	7	6	3	2	1	-	-	-	145x75		Square box																			
SA/SAG301410	90x65		6	4	3	1	1	1	-	-	-	250x65		14	12	9	5	4	3	-	-	-											
SA/SAG302310	180x65		10	10	7	3	3	2	-	-	-	255x65		14	12	9	5	4	3	-	-	-											
SA/SAG302318	180x140		18	18	12	9	6	4	2	1	1	258x140		24	24	18	14	8	6	3	2	2											
SA/SAG473018	258x140		24	24	18	14	8	6	3	2	1	380x140		36	36	24	18	12	12	4	4	2											
SAG623018	250x140		24	24	18	14	8	6	3	3	2	525x140		48	48	36	28	16	12	6	4	4											
SAG606018	420x130		40	40	30	25	12	12	4	4	4	420x130		35	35	26	16	10	10	4	4	4											




LID DRILLING DATA

TYPE OF ENCLOSURE	Drilling area mm
SA/SAG111108	90x90
SA/SAG171108	90x150
SA/SAG141410	127x127
SA202012	180x180
SA/SAG301410	127x285
SA/SAG302310	210x285
SA/SAG302318	210x285
SA/SAG473018	285x450
SAG623018	280x595
SAG606018	505x505




TYPE OF HOLES


For handles
 M-0634/11 M-0634/12
 M-0634/13 M-0634/14
 M-0634/03 M-0634/06
 M-0634/07 M-0634/09




For handles
 M-0634/10
 M-0634/10L
 M-0634/01




For handles
 M-0639 M-0638
 M-0637 M-0635
 M-0636



For ammeters and voltmeters



For indicator light



Junction boxes for monitoring and control panel 'Ex tb' SA/P

POLYESTER CONTROL HOUSINGS SA/P SERIES



MECHANICAL FEATURES

Body and lid:

Black polyester resin with antistatic properties

Gaskets:

Acid, hydrocarbon and high temperature resistant silicon positioned between the body and the lid

Mounting:

Polyester lugs for M6 screws

Certificate plate:

In aluminum riveted

Screws:

Stainless steel captive variety


MAX POWER DISSIPATED

Junction box	Power (W) - for T80°C		
	T.a. +40°C	T.a. +55°C	T.a. +60°C
SA090907/P	7,7	4,7	3,7
SA111108/P	10,9	6,6	5,3
SA171108/P	14,3	8,5	6,6
SA141410/P	19,7	11,5	8,9
SA301410/P	26,9	15,3	11,9
SA302310/P	26,0	15,6	12,0
SA302318/P	50,2	30,0	19,5
SA473018/P	63,7	38,7	29,7
SA623018/P	58,1	34,4	26,9

Junction boxes for monitoring and control panel 'Ex tb' SA/P

DIMENSIONAL DRAWINGS

Ex e



Dimensions in mm

SELECTION CHART

Code	External dimensions			Inner dimensions					Fixing				Weight Kg
	A	B	C	a	b	c	s1	x	y	x1	Ød		
SA111108/P	110	110	83	104	104	65	3	94	94	-	6,5		0,40
SA171108/P	170	110	83	164	104	65	3	154	94	-	6,5		0,80
SA141410/P	147	147	100	135	135	79	3	131	131	-	6,5		1,00
SA301410/P	305	147	110	296	138	90	4,5	285	127	-	6,5		1,90
SA302310/P	305	230	110	296	221	90	4,5	285	210	-	6,5		2,50
SA302318/P	305	230	190	296	221	165	4,5	285	210	-	6,5		3,10
SA473018/P	470	305	195	460	295	175	5	450	285	225	6,5		4,70
SA623018/P	620	305	185	608	293	160	5	560	285	260-300	8		6,30

Junction boxes for monitoring and control panel 'Ex tb' SA/P

BODY DRILLING DATA




THREAD COMPARISON CHART

D Thread diameter	1	2	3	4	5	6	7	8
ISO 261/965	20x1.5	25x1.5	32x1.5	40x1.5	50x1.5	63x1.5	75x1.5	85x2
Through hole	Ø20.5	Ø25.5	Ø32.5	Ø40.5	Ø50.5	Ø63.5	Ø75.5	Ø85.5



As required by the current standard, holes can be drilled by Cortem or by authorized partners who hold a production notification in accordance with ATEX Directive .

TYPE OF ENCLOSURE	HOLE DRILLING IN BODY																				
	Sides A and C								Sides B and D												
	Drilling area mm	MAXIMUM QUANTITY PER HOLE TYPE							Drilling area mm	MAXIMUM QUANTITY PER HOLE TYPE											
		1	2	3	4	5	6	7		1	2	3	4	5	6	7	8				
SA111108/P	58x55	2	2	1	1	1	-	-	58x55	Square box											
SA171108/P	68x55	2	2	1	1	1	-	-	128x55	5	3	2	2	2	-	-	-	-	-	-	-
SA141410/P	100x65	6	3	2	1	1	1	-	100x65	Square box											
SA301410/P	100x65	6	3	2	1	1	1	-	255x65	12	11	5	4	4	3	-	-	-	-	-	-
SA302310/P	180x65	8	7	5	3	2	2	-	260x65	12	11	5	4	4	3	-	-	-	-	-	-
SA302318/P	180x140	16	14	9	8	5	4	2	258x140	24	22	14	11	8	6	3	2	-	-	-	-
SA473018/P	258x140	24	18	14	8	8	6	3	380x140	36	24	18	12	12	8	6	2	-	-	-	-
SA623018/P	248x117	18	15	10	8	6	3	2	434x117	32	26	16	14	12	6	4	4	-	-	-	-





LID DRILLING DATA

TYPE OF ENCLOSURE	Drilling area mm
SA111108/P	90x90
SA171108/P	90x150
SA141410/P	127x127
SA301410/P	127x285
SA302310/P	210x285
SA302318/P	210x285
SA473018/P	285x450
SA623018/P	596x280





TYPE OF HOLES



For handles
 M-0634/11 M-0634/12
 M-0634/13 M-0634/14
 M-0634/03 M-0634/06
 M-0634/07 M-0634/09




For handles
 M-0634/10
 M-0634/10L
 M-0634/01



For handles
 M-0639 M-0638
 M-0637 M-0635
 M-0636



For ammeters and voltmeters



For indicator light



Junction boxes for monitoring and control panel 'Ex tb' CTB

STAINLESS STEEL CONTROL HOUSINGS CTB SERIES



MECHANICAL FEATURES

Body and lid:	Stainless steel AISI 316L
Hinges:	Stainless steel AISI 316L
Gaskets:	Resistant to acids, hydrocarbons and high temperatures, located between body and lid. Ensures consistent protection to IP66 during use
Certificate plate:	Stainless steel riveted
Removable gland plates:	Stainless steel thickness 30/10
Bolts and Screws:	Stainless steel captive variety
Earth screws:	Brass. On inside and outside of body complete with anti-rotation brackets
Mounting:	Welded AISI 316L stainless steel lugs



MAX POWER DISSIPATION

Junction box	Power (W) - for T80°C			Power (W) - for T100°C			Power (W) - for T135°C		
	T.a. +40°C	T.a. +55°C	T.a. +60°C	T.a. +40°C	T.a. +55°C	T.a. +60°C	T.a. +40°C	T.a. +55°C	T.a. +60°C
CTB121208	8,9	6,0	5,0	13,5	9,9	8,9	21,3	18,0	16,8
CTB151509	8,9	6,0	5,0	13,5	9,9	8,9	21,3	18,0	16,8
CTB191910	8,9	6,0	5,0	13,5	9,9	8,9	21,3	18,0	16,8
CTB221513	8,9	6,0	5,0	13,5	9,9	8,9	21,3	18,0	16,8
CTB262616	18,6	10,4	8,1	30,3	21,4	18,6	48,9	40,9	38,2
CTB262620	18,6	10,4	8,1	30,3	21,4	18,6	48,9	40,9	38,2
CTB303016	18,6	10,4	8,1	30,3	21,4	18,6	48,9	40,9	38,2
CTB303020	18,6	10,4	8,1	30,3	21,4	18,6	48,9	40,9	38,2
CTB382616	18,6	10,4	8,1	30,3	21,4	18,6	48,9	40,9	38,2
CTB382620	20,5	10,0	5,0	32,0	23,3	20,5	51,3	43,1	40,4
CTB453816	25,0	12,5	6,0	39,0	28,4	25,0	62,6	52,5	49,3
CTB453820	34,0	17,0	6,0	53,1	38,7	34,0	85,1	71,4	67,1
CTB484816	31,0	15,5	6,5	48,4	35,2	31,0	77,6	65,1	61,2
CTB484820	43,0	21,5	6,5	67,1	48,9	43,0	107,6	90,3	84,8
CTB503516	26,0	13,0	6,0	40,6	29,6	26,0	65,1	54,6	51,3
CTB503520	35,0	17,5	6,0	54,7	39,8	35,0	87,6	73,5	69,0
CTB624516	38,0	19,0	7,0	59,3	43,2	38,0	95,1	79,8	75,0
CTB624520	55,0	27,5	7,5	85,9	62,5	55,0	137,7	115,6	108,5
CTB745520	77,0	37,5	8,5	120,2	87,5	77,0	192,8	161,8	151,9
CTB765020	77,0	37,5	8,5	120,2	87,5	77,0	192,8	161,8	151,9
CTB808030	77,0	37,5	8,5	120,2	87,5	77,0	192,8	161,8	151,9
CTB866420	99,0	49,5	9,0	154,6	112,6	99,0	247,8	208,0	195,3
CTB916120	103,0	51,5	9,0	160,8	117,1	103,0	257,9	216,4	203,2
CTB916130	103,0	51,5	9,0	160,8	117,1	103,0	257,9	216,4	203,2
CTB987420	125,0	62,5	9,0	195,2	142,1	125,0	312,9	262,6	246,6

Junction boxes for monitoring and control panel 'Ex tb' CTB

DIMENSIONAL DRAWING

Ex e



Dimensions in mm

SELECTION CHART

Code	External dimensions				Inner dimensions			Fixing	
	A	B	C	E	F	C	S	a1	b1
CTB221513	229	152	130	169	92	75	1,5	152	208
CTB262616	260	260	160	224	200	100	1,5	170	316
CTB262620	260	260	205	224	200	145	1,5	170	316
CTB303016	306	306	160	270	246	100	1,5	203	361
CTB303020	306	306	205	270	246	145	1,5	203	361
CTB382616	380	260	160	344	200	100	1,5	250	316
CTB382620	380	260	205	344	200	145	1,5	250	316
CTB453816	450	380	160	414	322	100	1,5	305	437
CTB453820	450	380	205	414	322	145	1,5	305	437
CTB484816	480	480	160	444	420	100	1,5	327	535
CTB484820	480	480	205	444	420	145	1,5	327	535
CTB503516	500	350	160	464	290	100	1,5	350	406
CTB503520	500	350	205	464	290	145	1,5	350	406
CTB624516	620	450	160	584	390	100	2	450	506
CTB624520	620	450	205	584	390	145	2	450	506
CTB745520	740	550	205	704	490	145	2	540	606
CTB765020	762	508	205	726	448	145	2	508	564
CTB808030	800	800	305	725	725	245	2	510	855
CTB866420	860	640	205	824	580	145	2	696	570
CTB916120	914	610	205	878	550	145	2	666	559
CTB916130	914	610	305	878	550	245	2	666	559
CTB987420	980	740	205	944	680	145	2	700	769

Junction boxes for monitoring and control panel 'Ex tb' CTB

BODY DRILLING DATA


THREAD COMPARISON CHART

D Thread diameter	01	1	2	3	4	5	6	7	8
ISO 261/965	16x1.5	20x1.5	25x1.5	32x1.5	40x1.5	50x1.5	63x1.5	75x1.5	90x1.5
Through hole	Ø17	Ø20.5	Ø25.5	Ø32.5	Ø40.5	Ø50.5	Ø63.5	Ø75.5	Ø90.5

As required by the current standard, holes can be drilled by Cortem or by authorized partners who hold a production notification in accordance with ATEX Directive .



TYPE OF ENCLOSURE	HOLE DRILLING IN BODY																			
	Sides A and C								Sides B and D											
	Drilling area mm	MAXIMUM QUANTITY PER HOLE TYPE								Drilling area mm	MAXIMUM QUANTITY PER HOLE TYPE									
		01	1	2	3	4	5	6	7	8	01	1	2	3	4	5	6	7	8	
CTB221513	105x55	5	5	2	2	1	-	-	-	-	165x55	8	8	3	3	3	-	-	-	-
CTB262616	195x80	10	10	7	4	3	3	2	-	-	210x80	10	10	8	4	3	3	2	-	-
CTB262620	215x125	15	15	14	8	6	3	2	2	1	195x125	15	15	12	6	6	3	2	2	1
CTB303016	260x80	12	12	10	9	8	3	2	2	-	245x80	12	12	10	9	8	3	2	2	-
CTB303020	260x125	18	18	17	10	8	6	3	2	2	245x125	18	18	15	10	8	6	3	2	2
CTB382616	215x80	10	10	10	7	3	3	2	2	-	315x80	16	16	14	11	5	4	3	3	-
CTB382620	215x125	15	15	12	8	6	6	2	2	1	315x125	24	24	21	12	10	8	3	3	2
CTB453816	335x80	16	16	14	6	5	4	3	2	-	385x80	20	20	16	7	6	5	4	3	-
CTB453820	335x125	24	24	21	12	10	8	3	3	2	335x125	30	30	24	14	12	10	4	3	3
CTB484816	435x80	22	22	18	8	7	6	4	3	-	405x80	20	20	18	8	6	5	4	3	-
CTB484820	435x125	32	32	26	16	13	11	4	3	3	405x125	30	30	26	14	12	10	4	3	3
CTB503516	305x80	14	14	12	5	4	4	3	2	-	440x80	22	22	19	8	7	6	4	4	-
CTB503520	305x125	21	21	18	12	10	7	3	2	2	440x125	33	33	27	16	14	11	4	4	3
CTB624516	405x80	20	20	18	7	6	5	4	3	-	555x80	28	28	24	10	9	7	6	5	-
CTB624520	405x125	30	30	26	14	12	10	4	3	2	550x125	39	39	36	20	18	15	6	5	3
CTB745520	505x125	36	36	32	16	16	13	5	4	3	670x125	50	50	42	24	21	17	7	6	4
CTB765020	465x125	33	33	29	18	14	11	5	4	3	690x125	50	50	44	26	22	18	7	6	4
CTB866420	595x125	44	44	38	22	18	15	6	5	4	780x125	57	57	51	28	24	20	8	6	5
CTB916120	565x125	41	41	35	20	18	14	6	5	3	830x125	60	60	53	30	26	22	9	7	5
CTB916130	565X224	65	65	60	40	27	21	12	9	3	833x228	80	80	75	48	33	27	14	12	5
CTB987420	700x125	50	50	44	26	22	18	7	6	4	840x125	63	63	59	34	28	24	9	8	6



Junction boxes for monitoring and control panel 'Ex tb' CTB

LID DRILLING DATA



TYPE ENCLOSURES	Drilling area mm
CTB221513	150x75
CTB262616	180x180
CTB262620	180x180
CTB303016	225x225
CTB303020	225x225
CTB382616	300x180
CTB382620	300x180
CTB453816	370x300
CTB453820	370x300
CTB484816	400x400
CTB484820	400x400
CTB503516	420x270
CTB503520	420x270
CTB624516	540x370
CTB624520	540x370
CTB745520	660x470
CTB765020	680x425
CTB866420	780x560
CTB916120	835x530
CTB916130	835x530
CTB987420	900x660
CTB808030	720x720





Ex e

TYPE OF HOLES



For handles
 M-0634/11 M-0634/12
 M-0634/13 M-0634/14
 M-0634/03 M-0634/06
 M-0634/07 M-0634/09




For handles
 M-0634/10
 M-0634/10L
 M-0634/01




For handles
 M-0639 M-0638
 M-0637 M-0635
 M-0636



For ammeters and voltmeters




For indicator light



Junction boxes for monitoring and control panel 'Ex tb' CTB

REMOVABLE GLAND PLATES ON CTB SERIES STAINLESS STEEL BOXES




Ordering code examples

- 1) CTB503516S3
500x350x160 stainless steel box with 3 removable gland plates
- 2) CTB624520S4
620x450x205 stainless steel box with 4 removable gland plates


Code	Removable gland plate dimensions			
	Side A	Side B	Side C	Side D
CTB221513S..	144x94	144x94	144x94	144x94
CTB262616S..	254x120	154x120	254x120	154x120
CTB262620S..	254x164	154x164	254x164	154x164
CTB303016S..	298x120	254x120	298x120	254x120
CTB303020S..	298x164	254x164	298x164	254x164
CTB382616S..	254x120	298x120	254x120	298x120
CTB382620S..	254x164	298x164	254x164	298x164
CTB453816S..	374x120	374x120	374x120	374x120
CTB453820S..	374x164	374x164	374x164	374x164
CTB484816S..	474x120	444x120	474x120	444x120
CTB484820S..	474x164	444x164	474x164	444x164
CTB503516S..	344x120	444x120	344x120	444x120
CTB503520S..	344x164	444x164	344x164	444x164
CTB624516S..	444x120	544x120	444x120	544x120
CTB624520S..	444x164	544x164	444x164	544x164
CTB745520S..	544x164	634x164	544x164	634x164
CTB765020S..	504x164	594x124	504x164	594x124
CTB808030S..	634x214	634x214	634x214	634x214
CTB866420S..	634x164	740x164	634x164	740x164
CTB916120S..	604x164	740x164	604x164	740x164
CTB916130S..	604x264	740x264	604x264	740x264
CTB987420S..	634x164	444x164 (x2)	634x164	444x164 (x2)

OVERVIEW OF SIZES



Junction boxes for monitoring and control panel 'Ex tb' CTB

Example of enclosure body featuring removable gland plate on just one side.



Ex e

TYPE OF ENCLOSURE	HOLE DRILLING IN REMOVABLE GLAND PLATES																
	Sides A and C								Sides B and D								
	Drilling area mm	MAXIMUM QUANTITY PER HOLE TYPE							Drilling area mm	MAXIMUM QUANTITY PER HOLE TYPE							
		01	1	2	3	4	5	6		01	1	2	3	4	5	6	7
CTB221513	98x54	3	3	2	1	1	1	-	-	104x54	3	3	2	1	1	1	-
CTB262616	214x80	10	10	8	4	3	2	-	-	114x80	6	6	3	2	1	1	-
CTB262620	214x124	15	15	12	8	6	3	-	-	114x124	9	9	6	4	2	1	-
CTB303016	258x80	12	12	10	4	4	3	2	-	214x80	10	10	8	4	3	3	2
CTB303020	258x124	18	18	13	8	4	3	-	-	214x124	15	15	10	8	3	2	-
CTB382616	214x80	10	10	8	4	3	3	-	-	258x80	12	12	9	4	3	3	-
CTB382620	214x124	15	15	12	8	6	4	-	-	258x124	18	18	15	8	5	3	-
CTB453816	334x80	16	16	14	6	5	4	3	-	334x80	16	16	14	6	5	4	3
CTB453820	334x124	24	24	20	12	8	4	3	-	334x124	24	24	20	12	8	4	3
CTB484816	434x80	22	22	18	7	5	5	4	-	404x80	20	18	14	6	5	4	3
CTB484820	434x124	32	32	24	14	12	5	4	-	404x124	29	27	21	12	8	4	3
CTB503516	304x80	14	14	12	5	4	4	3	-	404x80	19	16	12	5	4	4	3
CTB503520	304x124	21	21	17	10	8	4	3	2	404x124	29	24	18	10	8	4	3
CTB624516	404x80	19	19	16	7	6	5	4	-	504x80	24	22	16	7	6	5	4
CTB624520	404x124	29	29	23	14	10	5	4	3	504x124	36	33	24	14	12	5	3
CTB745520	504x124	36	36	30	16	13	7	5	4	594x124	42	42	30	18	14	7	5
CTB765020	464x124	33	33	16	14	10	5	4	3	594x124	42	42	22	22	16	8	5
CTB866420	594x124	44	44	36	20	16	8	6	5	700x124	51	48	36	20	16	8	4
CTB916120	564x124	41	41	22	16	8	8	4	4	700x124	51	48	22	22	8	8	5
CTB916130	564x224	65	65	60	40	27	21	12	9	700x224	80	80	75	48	33	27	14
CTB987420	594x124	44	44	36	20	16	8	6	4	404x124 (x2)	58	58	48	28	20	10	6


Junction boxes for monitoring and control panel 'Ex tb'

ELECTRICAL FEATURES


The command, control and signalling units SA, SA/P and CTB series junction boxes could mount certificated signal, control and command operators and maneuver on the lid while, internally, could mount analogic and digital instruments, electronic reactors/inverters, PLC, multiplexers, amplifier, measuring and control devices, automatic switches, fuses, relays, electronic control devices, contactors, timers, twilight relays capacitors, transformers, resistors, terminals, reactors, soft starter, heater, sensor boards, amperometer, battery pack.

Rated voltage max.:	1000 Vac/dc
Rated current max.:	312 A
Rated frequency:	50/60 Hz
Terminal section:	da 1,5 mm ² a 300 mm ²

EXAMPLE OF TYPICAL DISPOSAL OF INTERNAL AND EXTERNAL ACCESSORIES



EXAMPLE OF ASSEMBLING OF CORTEM G-0309 SERIES BATTERY UNIT



Special conditions for the use of the battery pack G-0309 .. and for the ammeter or voltmeter B-0140 ..:


- when the battery is installed (IECEx CES 13.0006U and CESI 00ATEX032U certificates), the maximum dissipated power must be reduced by 12.5% and the equipment must be marked with a minimum temperature not lower than -20° C;
- when the ammeter and/or the voltmeter (IECEx CES 12.0022U and CESI 04ATEX128U certificates) are installed, the equipment must be marked with a maximum temperature not higher than +40° C and the maximum power dissipated for an ambient with temperature +40° C is reduced by 31.25%.

ENCLOSURES WITH TRANSPARENT GLASS OR POLYCARBONATE ON THE LID

According to customer's request, standard windows are available for the different type of enclosures for uses such as visualization of analog or digital instruments or indicators.

Ex e


DIMENSIONAL DRAWING BOXES WITH WINDOWS



SELECTION TABLE

Transparent	Gasket	Ring	Material	H	A	B	Dimensions L	M
K12-373P	B12-446	K12-372P	polycarbonate	9	118	118	45	45
K151-373P	B151-446	K151-372P	polycarbonate	9	149	118	76	45
K15-373P	B15-446	K15-372P	polycarbonate	9	149	149	76	76
K191-373P	B191-446	K191-372P	polycarbonate	9	189	149	116	76
K19-373P	B19-446	K19-372P	polycarbonate	9	189	189	116	116
K22-373P	B22-446	K22-372P	polycarbonate	9	228	151	155	78
K26-373P	B26-446	K26-372P	polycarbonate	9	257	257	184	184
K12-373V	B12-446	K12-372V	glass	12	118	118	45	45
K151-373V	B151-446	K151-372V	glass	12	149	118	76	45
K15-373V	B15-446	K15-372V	glass	12	149	149	76	76
K191-373V	B191-446	K191-372V	glass	12	189	149	116	76
K19-373V	B19-446	K19-372V	glass	12	189	189	116	116
K22-373V	B22-446	K22-372V	glass	12	228	151	155	78
K26-373V	B26-446	K26-372V	glass	12	257	257	184	184

M-0



M-0 series control, monitoring and signalling devices are installed as external accessories on Cortem 'Ex d' enclosures used in any industrial environment where an explosive atmosphere may be present, classified as Zone 1, 2, 21, 22. M-0 control devices can be used to close or open electrical or mechanical devices fitted inside the 'Ex d' enclosures while the signalling devices feature lights to indicate their operating status. The control and signalling device components are made from stainless steel to deliver unbeatable efficiency under any environmental conditions. Levers are made from aluminium while the plastic parts on push-buttons are designed to provide lengthy service life even when used in a highly corrosive atmosphere. M-0 control and signalling devices have an IP66 protection degree.

CERTIFICATION DATA FOR CONTROL DEVICES

Classification:	Group 2	Category 2D					
Installation: EN 60079.14	zone 21 - zone 22 (Dust)						
Marking:	CE 0722 Ex II 2D Ex tb IIIC Db IP66						
Certification:	ATEX CML 17 ATEX 3111U	All IEC Ex certification data can be downloaded from www.cortemgroup.com					
Standards:	CENELEC EN 60079-0: 2012+A11:2013, EN 60079-31:2014 and EUROPEAN DIRECTIVE 2014/34/UE IEC 60079-0: 2011, IEC 60079-31: 2013						
Degree of protection:	IP66						

MECHANICAL FEATURES OF CONTROL DEVICES

Outer body:	Aluminium
Internal bush:	Stainless steel
Internal pin:	Stainless steel
Gaskets:	Acid/hydrocarbon-resistant silicone
Push-button:	Coloured nylon
Illuminated push-button:	Clear coloured polycarbonate
Handle levers:	Aluminium
Coating:	Polyester coating RAL 7035 (Light grey), where this is an option
Device mounting:	Screws into lid
Contact mounting:	Snaps onto special flange, which assures quick connection of the whole contact block to the device or boxed type installed on DIN rails directly on the internal frame

Ex e

ELECTRICAL FEATURES (Contact block for push-buttons)

Rated voltage:	600V
Rated current:	10A
Impulse withstand voltage:	4kV
Insulation category:	Group C as per VDE 0110
Degree of protection of terminals:	IP2x as per CENELEC EN 60529
Contact operation:	<ul style="list-style-type: none"> – slow acting – self-cleaning (wiping action) – NC contact forced opening – double movable bridge – four points of contact – double break
Contact resistance	≤ 25 mΩ as per IEC 255.7 category 3

Electrical performance

Rated thermal current I_{th} = 10 A

Operational limits as per IEC 947.5.1:

Category AC15							
Voltage U_e (V)	24	48	60	110	220	380	500
Current I_e (A)	10	10	10	6	3	2	1.5
Category DC13							
Voltage U_e (V)	24	48	60	110	220	300	
Current I_e (A)	2.5	1.5	1	0.22	0.27	0.2	

Operational limits as per IEC 947.5.1:

AC Heavy Duty	(A600)
DC Standard Duty	(Q300)

ELECTRICAL FEATURES (CONTACT BLOCK FOR M-0553.. HANDLES)

Alternating current

Series		10	16	20	32	40/63
Rated voltage	U_e VDE/IEC	V	690	690	690	690
Rated current	I_{th} VDE/IEC	A	20	25	32	45
	220V-240V	kW	2.2	4.5	5.5	7.5
	380V-440V	kW	4.0	7.5	9.0	11.0
AC3 VDE/IEC, Direct starting of squirrel cage motor, stop during operation	660V-690V	kW	4.0	7.5	11.0	15.0
	110V	kW	0.4	1.5	1.5	2.5
	220V-240V	kW	0.75	2.5	4.5	4.0
	400V	kW	1.3	4.0	5.5	7.5


M-0... control, monitoring and signalling devices

Ex e

ILLUSTRATION



DIMENSIONS mm




DESCRIPTION

Normal push-button with standard 10A 600V 1NO+1NC contacts.
Button comes in choice of six colours.

Blue (B)	M-0639../B..
White (BI)	M-0639../BI..
Yellow (G)	M-0639../G..
Black (N)	M-0639../N..
Red (R)	M-0639../R..
Green (V)	M-0639../V..

Add IN for stainless steel body

Note:
For the padlockable push-button add
CODE + L (e.g. M- 0639/RL)



Normal push-button with standard 10A 600V 1NO+1NC contacts.


Emergency stop pushbutton with release	M-0638
--	--------

Black push-pull, stop push-button	M-0638../N
-----------------------------------	------------

Emergency stop pushbutton with key release	M-0638../K
--	------------

Push-pull, stop pushbutton	M-0638../P
----------------------------	------------

Add IN for stainless steel body



Illuminated push-button with standard 10A 600V 1NO+1NC contacts. (lamps on request)
Illuminated button comes in choice of five colours.


Blue	M-0637../B
White	M-0637../I
Yellow	M-0637../G
Red	M-0637../R
Green	M-0637../V

Add IN for stainless steel body

ILLUSTRATION



DIMENSIONS mm



DESCRIPTION

CODE

Indicator light with 3W lamps (on request*),
12/240 Vac/dc.

Lens comes in choice of five colours.

Blue

M-0636/B

Yellow

M-0636/G

White

M-0636/I

Red

M-0636/R

Green

M-0636/V


* lamp

12V: **LAMPBA9S12V**

24V: **LAMPBA9S24V**

110V: **LAMPBA9S110V**

240V: **LAMPBA9S240V**



Multi-LED indicators come with lenses in different colours. Reliability with a LED service life of 50,000 hours.

Blue

M-0612/3B..

Yellow

M-0612/3G..

Colourless

M-0612/3I..

Red

M-0612/3R..

Green

M-0612/3V..


Can be ordered in 4 possible voltages:

110 Vac/dc = **M-0612/..110**

12 Vac/dc = **M-0612/..12**

230 Vac = **M-0612/..230**

24 Vac/dc = **M-0612/..24**



Indicator light with one high-brightness LED, for a consumption of 20 mA and estimated life of around 50,000 hours.

LED in 5 colours available.

Complete with locknut.


Color	If (mA)	Vf Tip. (V)	Vf max. (V)	
Red	20	2.1	2.6	M-0487
Yellow	20	2.1	2.4	M-0487/G
Clear	20	3.2	4.0	M-0487/I
Green	20	3.2	4.0	M-0487/V
Bicolor	20	2.0	2.5	M-0487/1

ILLUSTRATION

DIMENSIONS mm

DESCRIPTION

CODE




Quick-connect handle for cam or rotary switch.
Fixed pin length.
Complete with locknut.

M-0634/10..

Add suffix **IN** for stainless steel body and handle

Note:
contact block is supplied on request.
Please contact our sales department if you need advice




Quick-connect padlockable handle for cam or rotary switch.
Fixed pin length. Complete with locknut.

M-0634/10L..

Add suffix **IN** for stainless steel body and handle

Note:
contact block is supplied on request.
Please contact our sales department if you need advice



Padlockable handle for cam switch.
Complete with locknut.

Fixed pin length

M-0634../11F

Variable pin length

M-0634../11V

Add **IN** for stainless steel body and handle




ILLUSTRATION	DIMENSIONS mm	DESCRIPTION	CODE
		Padlockable handle for special switches. (3RV motor protectors). Complete with locknut.	
		Variable pin length	M-0634.. /12V
		Fixed pin length	M-0634.. /12F
		Add IN for stainless steel body and handle	
		Padlockable handle for switches with Ø6 shaft. Complete with locknut.	
		Variable pin length	M-0634.. /13V
		Fixed pin length	M-0634.. /13F
		Add IN for stainless steel body and handle	
		Padlockable handle for enclosed circuit breakers. Complete with locknut.	
		Variable pin length (size to order)	M-0634.. /14V
		Fixed pin length	M-0634.. /14F
		Add IN for stainless steel body and handle	








ILLUSTRATION	DIMENSIONS mm	DESCRIPTION	CODE
		Padlockable handle for heavy-duty series enclosed circuit breakers. Complete with locknut.	
		Variable pin length	M-0634../01V
		Fixed pin length	M-0634../01F
		Add IN for stainless steel body and handle	
		Padlockable handle for modular circuit breakers. Complete with locknut.	
		Fixed pin length	M-0634../03F
		Variable pin length	M-0634../03V
		Add IN for stainless steel body and handle	
		Knob for potentiometers with Ø6 shaft	M-0634/06

ILLUSTRATION	DIMENSIONS mm	DESCRIPTION	CODE
		Handle for enclosed circuit breakers. Wall mounting. Complete with locknut.	M-0634/07
		Handle for modular circuit breakers. Wall mounting. Complete with locknut.	M-0634/09


Type of handle padlocking devices




Code **M-698/5**



Code **M-698/6**



Code **M-698/7**




Code **M-698/8**

ILLUSTRATION



DIMENSIONS mm




DESCRIPTION

CODE

Selector with 0A 600V 1NO+1NC contacts.

Selector R arrangement	M-0635/R
Left selector RSX arrangement	M-0635/RSX
Selector X arrangement	M-0635/X
Selector 1C arrangement	M-0635/1C
Selector 1I arrangement	M-0635/1I
Selector 1M arrangement	M-0635/1M
Selector 1W arrangement	M-0635/1W
Selector 1Z arrangement	M-0635/1Z
Selector 2C arrangement	M-0635/2C
Selector 2I arrangement	M-0635/2I
Selector 2W arrangement	M-0635/2W
Selector 2Z arrangement	M-0635/2Z
Selector 3I arrangement	M-0635/3I
Selector 4I arrangement	M-0635/4I



The Cortem certified ammeter and voltmeter are suitable for measuring electrical values when the situation demands the utmost accuracy. The internal faces featuring the measuring range scale are produced to the customer's specifications.

Ammeter **B-0140A**

voltmeter **B-0140V**


Maximum voltage:	600 V
Nominal frequency:	40 ÷ 60 Hz
Precision class:	1.5
Dissipated power:	1.1 VA (B-0140A) 3.0 VA (B-0140V)

Measurement range - Direct measurement:

0 ÷ 40 mA	0 ÷ 0.1 A
0 ÷ 60 mA	0 ÷ 1.5 A
0 ÷ 100 mA	0 ÷ 2.5 A
0 ÷ 250 mA	0 ÷ 5 A
0 ÷ 400 mA	0 ÷ 6 A
0 ÷ 600 mA	0 ÷ 15 A

Measuring range - With current transformer:

0 ÷ 2.5 mA	0 ÷ 50 A
0 ÷ 5 mA	0 ÷ 60 A
0 ÷ 10 mA	0 ÷ 75 A
0 ÷ 15 mA	0 ÷ 100 A
0 ÷ 20 mA	0 ÷ 150 A
0 ÷ 25 mA	0 ÷ 200 A
0 ÷ 30 mA	0 ÷ 300 A
0 ÷ 40 mA	0 ÷ 400 A



Product modifications and warranty

Cortem Group reserves the right, at its sole discretion, to make any modifications (at any time and without notice) in order to improve the functionality and performance of its products or meet technical and manufacturing requirements. The measurements and drawings of the products and their parts are indicative only and not binding, because they can be modified without notice.

The latest updated information, data and certificates of our products are available on www.cortemgroup.com web site.

All Cortem Group products are covered by warranty for a period of twelve months from the delivery date. For more information, refer to the "General Terms and Conditions of Sale" on www.cortemgroup.com web site.

Copyright

In accordance with copyright laws, the Italian Civil Code and other regulations in effect in the markets where the Cortem Group operates, all the information, images, photographs, drawings, tables and anything else contained in the Cortem Group's illustrative/promotional material are the exclusive property of the Cortem Group, which has all the moral rights to the aforesaid material as well as the right to use it for commercial and economic purposes.

It is therefore forbidden to reproduce all or part of the Cortem Group's illustrative/promotional material in any way, unless otherwise authorized by the Cortem Group in writing. Any violation of the above is against the law.

© by Cortem - Villesse - Italy. All rights reserved



Sales

Piazzale Dateo 2
20129 Milano, Italia

Domestic Sales

tel. +39 02 76 1103 29 r.a.
fax +39 02 73 83 402
infomilano@cortemgroup.com

Export Sales

tel. +39 02 76 1105 01 r.a.
fax +39 02 73 83 402
export@cortemgroup.com
saleseurope@cortemgroup.com

Works and Headquarters

Via Aquileia 10, 34070 Villesse (GO), Italia
tel. +39 0481 964911 r.a.
fax +39 0481 964999
info@cortemgroup.com



Works and Headquarters

Via Aquileia 12, 34070 Villesse (GO), Italia
tel. +39 0481 964911 r.a.
fax +39 0481 964999
info@elfit.com
vendite@elfit.com
www.elfit.com



Sales

Piazzale Dateo 2
20129 Milano, Italia

Domestic Sales

tel. +39 02 76 1103 29 r.a.
fax +39 02 73 83 402
infomilano@cortemgroup.com

Export Sales

tel. +39 02 76 1105 01 r.a.
fax +39 02 73 83 402
export@cortemgroup.com
saleseurope@cortemgroup.com

Works and Headquarters

Via Aquileia 10, 34070 Villesse (GO), Italia
tel. +39 0481 964911 r.a.
fax +39 0481 964999
info@cortemgroup.com



To be sure to be safe.

www.cortemgroup.com

